Understanding the reduction of the edge safety factor during hot VDEs and fast edge cooling events

Citation for published version (APA):

Artola, F. J., Lackner, K., Huijsmans, G. T. A., Hoelzl, M., Nardon, E., & Loarte, A. (2020). Understanding the reduction of the edge safety factor during hot VDEs and fast edge cooling events. *Physics of Plasmas*, 27(3), [032501]. <https://doi.org/10.1063/1.5140230>

DOI:

[10.1063/1.5140230](https://doi.org/10.1063/1.5140230)

Document status and date:

Published: 01/03/2020

Document Version:

Publisher's PDF, also known as Version of Record (includes final page, issue and volume numbers)

Please check the document version of this publication:

- A submitted manuscript is the version of the article upon submission and before peer-review. There can be important differences between the submitted version and the official published version of record. People interested in the research are advised to contact the author for the final version of the publication, or visit the DOI to the publisher's website.
- The final author version and the galley proof are versions of the publication after peer review.
- The final published version features the final layout of the paper including the volume, issue and page numbers.

[Link to publication](#)

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal.

If the publication is distributed under the terms of Article 25fa of the Dutch Copyright Act, indicated by the "Taverne" license above, please follow below link for the End User Agreement:

www.tue.nl/taverne

Take down policy

If you believe that this document breaches copyright please contact us at:

openaccess@tue.nl

providing details and we will investigate your claim.

Understanding the reduction of the edge safety factor during hot VDEs and fast edge cooling events

Cite as: Phys. Plasmas **27**, 032501 (2020); <https://doi.org/10.1063/1.5140230>

Submitted: 26 November 2019 . Accepted: 11 February 2020 . Published Online: 04 March 2020

F. J. Artola , K. Lackner, G. T. A. Huijsmans , M. Hoelzl , E. Nardon, and A. Loarte

View Online

Export Citation

CrossMark

ARTICLES YOU MAY BE INTERESTED IN

[Runaway electron transport in stochastic toroidal magnetic fields](#)

Physics of Plasmas **27**, 032502 (2020); <https://doi.org/10.1063/1.5135588>

[A new explanation of the sawtooth phenomena in tokamaks](#)

Physics of Plasmas **27**, 032509 (2020); <https://doi.org/10.1063/1.5140968>

[Time-dependent modeling of coupled plasma-wall dynamics](#)

Physics of Plasmas **27**, 032503 (2020); <https://doi.org/10.1063/1.5140183>

NEW: TOPIC ALERTS

Explore the latest discoveries in your field of research

SIGN UP TODAY!

Understanding the reduction of the edge safety factor during hot VDEs and fast edge cooling events

Cite as: Phys. Plasmas **27**, 032501 (2020); doi: 10.1063/1.5140230

Submitted: 26 November 2019 · Accepted: 11 February 2020 ·

Published Online: 4 March 2020

View Online

Export Citation

CrossMark

F. J. Artola,^{1,a)} K. Lackner,² G. T. A. Huijsmans,^{3,4} M. Hoelzl,² E. Nardon,³ and A. Loarte¹

AFFILIATIONS

¹ITER Organization, Route de Vinon sur Verdon, 13067 St. Paul Lez Durance Cedex, France

²Max Planck Institute for Plasma Physics, Boltzmannstr. 2, 85748 Garching, Germany

³CEA, IRFM, F-13108 St. Paul-lez-Durance Cedex, France

⁴Eindhoven University of Technology, 5612 AP Eindhoven, The Netherlands

^{a)}Author to whom correspondence should be addressed: javier.artola@iter.org

ABSTRACT

In the present work, a simple analytical approach is presented in order to clarify the physics behind the edge current density behavior of a hot plasma entering in contact with a resistive conductor. As has been observed in recent simulations [C. R. Sovinec and K. J. Bunkers, Plasma Phys. Controlled Fusion **61**(2), 024003 (2019)], when a plasma comes in contact with a highly resistive wall, large current densities appear at the edge of the plasma. The model shows that this edge current originates from the plasma response, which attempts to conserve the poloidal magnetic flux (Ψ) when the outer current is being lost. The loss of outer current is caused by the high resistance of the outer current path compared with the plasma core resistance. The resistance of the outer path may be given by plasma contact with a very resistive structure or by a sudden decrease in the outer plasma temperature (e.g., due to a partial thermal quench or due to a cold front penetration caused by massive gas injection). For general plasma geometries and current density profiles, the model shows that, given a small change in minor radius (δa), the plasma current is conserved to first order [$\delta I_p = 0 + \mathcal{O}(\delta a^2)$]. This conservation comes from the fact that total inductance remains constant ($\delta L = 0$) due to an exact compensation of the change in external inductance with the change in internal inductance ($\delta L_{\text{ext}} + \delta L_{\text{int}} = 0$). As the total current is conserved and the plasma volume is reduced, the edge safety factor drops according to $q_a \propto a^2/I_p$. Finally, the consistency of the resulting analytical predictions is checked with the help of free-boundary MHD simulations.

Published under license by AIP Publishing. <https://doi.org/10.1063/1.5140230>

I. INTRODUCTION

The onset of vertical displacement events (VDEs) or axisymmetric modes in tokamaks is a well-known phenomenon that arises in elongated plasmas. Uncontrolled VDEs can reduce the lifetime of the in-vessel components due to the large thermal and electromagnetic loads that they are able to produce. The type of VDEs with highest loads is often referred to as “hot” VDEs, where the plasma enters in contact with the wall keeping its initial thermal and magnetic energy. During such events, the plasma can develop additional asymmetric MHD instabilities that lead to further localization and intensification of the loads. A particular concern for large scale tokamaks such as ITER and DEMO is the rotation of the electromagnetic load asymmetry. This rotation could resonate with the mechanical frequencies of the vessel, creating a significant amplification of the vessel forces.^{2,3}

The destabilization of toroidally asymmetric modes is typically associated with the onset of external MHD modes, which are driven by large edge current densities and a low edge safety factor.⁴ Experimental observations of hot VDEs indicate that the edge safety factor (q_a) drops as the plasma cross section is reduced,⁵ which is thought to cause the onset of external MHD modes. The change in q_a and in the equilibrium parameters can lead to a fast stochastization of the field line topology and to a resulting thermal quench, which is observed with different large scale MHD simulation codes.^{1,6–8} Relevant references summarizing the theory of disruptions are given in Refs. 9 and 10. In the present work, a simple analytical approach is presented in order to clarify the origin of the reduction of q_a for hot VDEs as well as for fast cooling events of the plasma edge.

The kink edge safety factor¹¹ of an elongated plasma is defined as

$$q_a = 2\pi \left(\frac{1 + \kappa^2}{2} \right) \frac{B_\phi}{\mu_0 R_0} \frac{a^2}{I_p}, \quad (1)$$

where κ is the plasma elongation, I_p is the total plasma current, a is the plasma minor radius, and B_ϕ is the toroidal magnetic field at the plasma geometric center placed at major radius R_0 . This relation shows that, for fixed B_ϕ , κ , and R_0 , a small variation of q_a is given by

$$\frac{\delta q_a}{q_a} = -2 \frac{\delta a}{a} - \frac{\delta I_p}{I_p}, \quad (2)$$

where the change in minor radius is imposed as $-\delta a$, with δa positive. In order to decrease the edge safety factor over time, the following condition must be satisfied:

$$\frac{\delta I_p}{I_p} = -\frac{\partial I_p}{\partial a} \frac{\delta a}{I_p} > -2 \frac{\delta a}{a} \rightarrow \frac{\partial I_p}{\partial a} < 2 \frac{I_p}{a}. \quad (3)$$

Therefore, in order to know if q_a will be reduced after a change in plasma minor radius δa , a relation between δI_p and δa is needed. Note that we consider only hot plasmas with a resistive decay time (at fixed minor radius) much longer than the time scales of interest. In the case where the resistive decay of I_p is comparable to the considered time-scales, q_a could increase even when $\partial_a I_p = 0$. In Sec. II, an analytical relation between δI_p and δa is obtained for highly conducting plasmas including the effect of a nearby conducting wall. The expression found is verified with the use of free-boundary MHD simulations in Sec. III and finally our conclusions are given in Sec. IV.

II. ANALYTICAL CALCULATION FOR δI_p

In the following, we consider that a plasma has lost current in its outer region (it has been scraped-off) and that consequently its minor radius has been reduced by δa . This process could take place due to conduction of edge current through a highly resistive wall which has entered in contact with the plasma. This could be interpreted as a grounding effect. Equivalently, a sudden drop of the edge plasma temperature due to a radiative collapse or due to the penetration of a cold pellet would cause a similar effect, which does not require a plasma motion into the wall. If the total resistance of the current path at the outer plasma is much larger than the core plasma resistance, the outer plasma current will vanish and the plasma minor radius will be reduced.

In order to describe the scraping-off process, we consider the plasma defined by Fig. 1, which consists of three separated plasma regions

- Scraped-off domain: existing from $r = a - \delta a$ to $r = a$. All plasma currents that were initially belonging to this region of thickness (δa) will vanish after the scraping-off process. Formally, this is described by setting an infinite resistivity ($\eta = \infty$) at a certain time.
- Hot plasma domain: existing from $r = 0$ to $r = a - (w + \delta a)$. This region is assumed to be ideally conducting on the considered time scales and therefore described by the setting ($\eta = 0$). It is also assumed that this region remains unperturbed and static during the scraping-off process.
- Induced edge current domain: existing from $r = a - (w + \delta a)$ to $r = a - \delta a$. In this region of thickness (w), currents coming from

FIG. 1. Geometry and coordinates for the analytical description of the scraping-off process.

the scraped-off domain can be induced. The width (w) can be approximated with the skin depth given by $w \sim \sqrt{\eta \tau / \pi \mu_0}$, where τ is the timescale of the scraping-off mechanism. Therefore, for ideally conducting plasmas ($\eta = 0$) or for very fast current losses ($\tau \rightarrow 0$), the skin depth becomes infinitely thin ($w \rightarrow 0$).

Note that Fig. 1 and the cylindrical radial coordinate r are used for illustrative purposes; however, the given geometry can be generalized to represent arbitrary shaped flux-surfaces ($\hat{r} = \hat{r}(r, \theta)$). Replacing r by $\hat{r}$ gives identical final conclusions and expressions and, therefore, the symbol r is used without loss of generality. In order to find the change in plasma current, we will use the conservation of poloidal magnetic flux that the hot plasma can provide. The time derivative of the poloidal magnetic flux (Ψ_S) contained in a toroidal ribbon (S) that extends from the major radius R_1 to R_2 is

$$\frac{\partial \Psi_S}{\partial t} = -2\pi [R_2 E_\phi(R_2) - R_1 E_\phi(R_1)], \quad (4)$$

where $E_\phi(R)$ is the toroidal electric field at the R position. This equation can be found by applying Stoke's theorem to Faraday's law, where the flux is defined here as $\Psi = \int \mathbf{B} \cdot d\mathbf{S}$. In order to conserve the flux, both terms on the RHS of Eq. (4) should vanish or cancel each other. The first term will vanish by choosing $R_2 = R_0 - (a - (\delta a + w))$, where the plasma is considered to be ideal (see Fig. 1) and therefore $E_\phi(R_2) = 0$. In ideal MHD, the electric field is zero in the frame of reference of the plasma ($\mathbf{E}' = \mathbf{E} + \mathbf{v} \times \mathbf{B} = 0$) even in the presence of flows. Consider a rigid displacement of the plasma column at a speed $\mathbf{v} = \mathbf{v}_{\text{VDE}}$. In this case, the flux conservation is still verified by placing ourselves into the frame of reference of the plasma. In this idealized model, we only consider vertical rigid displacements and therefore the effects of equilibrium flows and complex VDE generated flows are not taken into account. By placing an ideally conducting wall at $R_1 = R_w^{\text{in}}$, the second term will also vanish as $E_\phi = 0$ inside ideal conductors. In the case without wall, the second term will vanish by extending the toroidal ribbon (S) to the origin of coordinates where $R_1 = 0$. Considering these choices for the boundaries of S , the flux Ψ_S is conserved ($\partial_t \Psi_S = 0$).

Before the plasma current has been scraped-off, the poloidal flux within the toroidal ribbon S can be decomposed as

$$\Psi_{S,0} = \Psi_{\text{bulk}} + \Psi_{\text{out}}^{\text{ext}} + \Psi_{\text{out}}^{\text{int}}, \quad (5)$$

where Ψ_{bulk} is the flux produced by the hot plasma region and $\Psi_{\text{out}} = \Psi_{\text{out}}^{\text{ext}} + \Psi_{\text{out}}^{\text{int}}$ is the flux produced by the outer region, which includes both the region which will be scraped-off and the induced edge current domain [see Fig. 2(a)]. The total initial current within this outer region is represented by δI_{out} . After the reduction of the plasma minor radius, the final flux is

$$\Psi_{S,f} = \Psi_{\text{bulk}} + \Psi_{\text{skin}}^{\text{ext}} + \Psi_{\text{skin}}^{\text{int}} + \Psi_w, \quad (6)$$

where Ψ_w is the flux produced by the ideally conducting wall ($\Psi_w = 0$ in the case of no wall and $R_1 = 0$) and $\Psi_{\text{skin}} = \Psi_{\text{skin}}^{\text{ext}} + \Psi_{\text{skin}}^{\text{int}}$ is the flux produced by the induced edge current domain [see Fig. 2(b)]. By using the conservation of poloidal flux ($\Psi_{S,f} = \Psi_{S,0}$), we find

$$\Psi_{\text{skin}}^{\text{ext}} + \Psi_{\text{skin}}^{\text{int}} + \Psi_w = \Psi_{\text{out}}^{\text{ext}} + \Psi_{\text{out}}^{\text{int}}, \quad (7)$$

This expression can be used to calculate the final current in the induced edge current domain (δI_{skin}), which is related to the total

change in plasma current by $\delta I_p = \delta I_{\text{skin}} - \delta I_{\text{out}}$. In order to do that we express the flux contributions as function of their associated currents

- $\Psi_{\text{out}}^{\text{ext}} = L_{\text{ext}}(a) \delta I_{\text{out}}$,
- $\Psi_{\text{skin}}^{\text{ext}} = L_{\text{ext}}(a - \delta a) \delta I_{\text{skin}}$,
- $\Psi_{\text{out}}^{\text{int}} = c_{\text{out}} \delta I_{\text{out}} (\delta a + w)$,
- $\Psi_{\text{skin}}^{\text{int}} = c_{\text{skin}} \delta I_{\text{skin}} w$,
- $\Psi_w = -c_w \delta I_p$,

where $L_{\text{ext}}(r)$ is the effective external inductance of a plasma with minor radius r and (c_{out} , c_{skin} , and c_w) are geometrical constants. We define the effective plasma external inductance as $L_{\text{ext}}(r) = 2\pi[\psi_p(R_0 - r) - \psi_p(R_1)]/I_p(r)$, where ψ_p is the flux per radian produced by the plasma current $I_p(r)$. For the flux produced by the wall (Ψ_w), we have used that $\delta I_w \propto -\delta I_p$, which results from the fact that the magnetic field outside the wall is conserved due to the screening effect of the ideally conducting wall. With these considerations, Eq. (7) is

$$(L_{\text{ext}}(a - \delta a) + c_{\text{skin}} w - c_w) \delta I_p = (L_{\text{ext}}(a) - L_{\text{ext}}(a - \delta a) + c_{\text{out}} \delta a + (c_{\text{out}} - c_{\text{skin}}) w) \delta I_{\text{out}}, \quad (8)$$

and finally by regrouping terms and using the following Taylor expansion $L_{\text{ext}}(a) = L_{\text{ext}}(a - \delta a) + \partial_a L_{\text{ext}} \delta a$, we find

$$\delta I_p = \frac{(\partial_a L_{\text{ext}} + c_{\text{out}}) \delta a + (c_{\text{out}} - c_{\text{skin}}) w}{L_{\text{ext}}(a) - \partial_a L_{\text{ext}} \delta a + c_{\text{skin}} w - c_w} \delta I_{\text{out}}. \quad (9)$$

Considering that $L_{\text{ext}}(a)$ is a quantity of zero order, for finite initial edge current densities $\delta I_{\text{out}} \propto J_{\text{edge}} \delta a$ and $w \sim \delta a$, we find that

$$\delta I_p = \mathcal{O}(\delta a^2), \quad (10)$$

which demonstrates that for ideally conducting plasmas with arbitrary shape, the current is conserved up to second order. We define the quantity ϵ_{ind} as the relative amount of re-induced current as

$$\epsilon_{\text{ind}} \equiv \frac{\delta I_{\text{skin}}}{\delta I_{\text{out}}} = 1 + \frac{(\partial_a L_{\text{ext}} + c_{\text{out}}) \delta a + (c_{\text{out}} - c_{\text{skin}}) w}{L_{\text{ext}}(a) - \partial_a L_{\text{ext}} \delta a + c_{\text{skin}} w - c_w}. \quad (11)$$

With this definition, $\epsilon_{\text{ind}} = 1$ if $\delta I_p = 0$ and all the current from the scraped-off region is re-induced into the new plasma boundary and $\epsilon_{\text{ind}} = 0$ when $\delta I_p = -\delta I_{\text{out}}$.

The conclusion drawn from Eq. (10) can be interpreted as a first order cancellation of the change in external inductance (δL_{ext}) with the change in internal inductance (δL_i). As the total plasma flux (Ψ) contained in the toroidal ribbon that extends from R_1 to R_0 is conserved $\delta \Psi = \delta(L I_p) = 0$, the total current is conserved up to second order only if $\delta L = \mathcal{O}(\delta a^2)$, which implies that $\delta L_{\text{ext}} + \delta L_i = \mathcal{O}(\delta a^2)$.

Note however that the scraped-off current (δI_{out}) can grow to order zero as the edge current builds up from the previous reductions of the minor radius. If $\delta I_{\text{out}} = \mathcal{O}(I_p)$, the change in the total current grows to first order according to Eq. (9). In the case where ($w \ll \delta a$), the rate at which the current is lost with respect to the change in minor radius is

FIG. 2. Flux contributions to Ψ_S before (a) and after (b) the scraping-off process. The colors associate the different current domains with their produced fluxes (colored rectangles).

$$\frac{\partial I_p}{\partial a} \approx -\frac{\partial_a L_{\text{ext}} + c_{\text{out}}}{L_{\text{ext}}(a)} \delta I_{\text{out}} = -\frac{\partial_a L_{\text{ext}} + c_{\text{out}}}{L_{\text{ext}}(a)} (\Delta I_{\text{out}} + \Delta I_p), \quad (12)$$

where $\Delta I_p(a) \equiv I_p(a) - I_p(a_0)$ is the total change in plasma current and $\Delta I_{\text{out}} \equiv I_0(a_0) - I_0(a)$ is the total scraped-off current with respect to the initial plasma state with radius a_0 and current profile $I_0(r)$. Note that the non-indexed minor radius is a function of time $a(t)$. After a time interval δt , the new radius is $a(t + \delta t) = a(t) - \delta a$, with δa being positive. The subscript “0” indicates quantities at the initial plasma before any plasma “peeling” has taken place $a_0 = a(t = 0)$. Similarly, the profile of total toroidal current as a function of the radial coordinate $I(r, t)$ at $t = 0$ is $I_0(r)$. In the latter expression, we have used that δI_{out} is the current in the skin layer before the small δa reduction ($\delta I_{\text{out}} = I_{\text{skin}}(t - \delta t) = \Delta I_{\text{out}} + \Delta I_p$).

A. Limit for a circular plasma with large aspect ratio

For a large aspect ratio circular plasma enclosed by a wall with minor radius (b), the previous quantities are

$$\hat{L}_{\text{ext}}(a) \equiv \frac{L_{\text{ext}}(a)}{\mu_0 R_0} = \begin{cases} [\ln(8R_0/a) - 2] & \text{no wall} \\ \ln(b/a) & \text{ideal wall,} \end{cases}$$

- $\partial_a L_{\text{ext}} = -\mu_0 R_0/a$,
- $c_{\text{out}} = c_{\text{skin}} = \mu_0 R_0/(2a)$,
- $c_w = 0$,
- $\delta I_{\text{out}} = 2(J_{\text{edge}}/\langle J_0 \rangle)(\delta a + w)I_p/a$,

where $\langle J_0 \rangle$ is the initial averaged current density $\langle J_0 \rangle \equiv I_p/(\pi a^2)$ and J_{edge} is the initial current density in the scraped-off domain. For the calculation of $(c_{\text{out}}, c_{\text{skin}})$, we have assumed that the current density in the perturbed region is spatially constant. The flux within the wall produced by the wall itself is taken to be zero ($c_w = 0$) as it is expected from a circular wall in the large aspect ratio assumption.¹² With these quantities, Eqs. (2), (9), and (11) give

$$\delta I_p = -\frac{J_{\text{edge}}/\langle J_0 \rangle}{\hat{L}_{\text{ext}}(a) + \delta a/a + w/(2a)} \frac{\delta a}{a} \frac{\delta a + w}{a} I_p, \quad (13)$$

$$\epsilon_{\text{ind}} = 1 - \frac{1}{2} \frac{\delta a/a}{\hat{L}_{\text{ext}}(a) + \delta a/a + w/(2a)}, \quad (14)$$

$$\frac{\delta q_a}{q_a} = \left(-2 + \frac{J_{\text{edge}}/\langle J_0 \rangle}{\hat{L}_{\text{ext}}(a) + \delta a/a + w/(2a)} \frac{\delta a + w}{a} \right) \frac{\delta a}{a}, \quad (15)$$

and from Eq. (13), the rate at which I_p varies with a is

$$\frac{\partial I_p}{\partial a} = \frac{1}{2a} \frac{1}{\hat{L}_{\text{ext}}(a) + \delta a/a + w/(2a)} \delta I_{\text{out}}. \quad (16)$$

For finite $\hat{L}_{\text{ext}}(a)$, the latter expression together with (3) gives a condition for the minimum value of δI_{out} to stop the drop of q_a

$$\frac{\delta I_{\text{out}}}{I_p} > 4\hat{L}_{\text{ext}}(a). \quad (17)$$

For a typical tokamak aspect ratio of 3, the latter expression implies that the accumulated edge current should be 4.7 times larger than the total plasma current, which is an absurd situation that proves that the safety factor always decreases.

Nevertheless, the effect of a close enough ideally conducting wall can change this situation as $\hat{L}_{\text{ext}}(a) \rightarrow 0$ when $b/a \rightarrow 1$. If the ideal wall is located exactly at the plasma boundary ($b/a = 1$) and $w = 0$, half of the current in the scraped-off region can be re-induced in the wall ($\epsilon_{\text{ind}} = 1/2$). For this special case, the change in the edge safety factor is

$$\frac{\delta q_a}{q_a} = \left(-2 + \frac{J_{\text{edge}}}{\langle J_0 \rangle} \right) \frac{\delta a}{a}, \quad (18)$$

which gives $\delta q_a/q_a > 0$ if $J_{\text{edge}}/\langle J_0 \rangle > 2$.

III. SIMULATIONS

In order to check the consistency of the previous analytical expressions, we perform simulations with the reduced MHD model of the non-linear code JOEKEK.¹³ A circular plasma is constructed with an initially flat current density profile (see Fig. 3), a minor radius ($a = 0.97$ m), a major radius ($R_0 = 10$ m), and a poloidal beta ($\beta_p = 0.004$). The plasma is held in toroidal equilibrium thanks to the vertical field produced by a set of external PF coils situated at $R = 8$ m and at $R = 12$ m. Free-boundary conditions are used by coupling JOEKEK with the code STARWALL,¹⁴ which allow the plasma to move radially and vertically. The boundary condition for the toroidal current density is simply given by Ampère’s law ($J_\phi = -\Delta^* \psi/(\mu_0 R)$). The chosen polar grid is formed by 140 (radial) $\times$ 42 (poloidal) Bézier elements with radial refinement in order to resolve the thin skin currents that appear at the edge of the plasma. The resistivity is chosen to be independent of the plasma temperature and it is given by

$$\eta = \eta_0 + \eta_Z/2(1 + \tanh[(Z_{\text{th}} - Z)/\sigma_Z]), \quad (19)$$

where $\eta_0 = 1.95 \times 10^{-8} \Omega \text{ m}$, $\eta_Z = 10^4 \eta_0$, $Z_{\text{th}} = -0.95$ m, and $\sigma_Z = 0.003$ m. The second term is chosen to act as the scraping-off mechanism, which creates a highly resistive region at the lower plasma edge that makes the current decay in a fast time scale compared to the resistive time of the plasma core. With this setting, the resulting change in minor radius is $\delta a = 3.5$ cm. As it can be seen in Fig. 3, after 1.96 ms, skin currents appear at the edge of the plasma. The resulting thickness of the skin current during this time is $w = 2.3$ cm.

FIG. 3. Current density contour plots for the case without wall at $t = 0$ ms and at $t = 1.96$ ms.

FIG. 4. Simulation results and analytical predictions for $\delta I_p / I_{p0}$ (left) and ϵ_{ind} (right) for different ideal wall minor radii.

An ideal wall is placed near the plasma at different minor radii (b). The obtained $\delta I_p / I_{p0}$ and ϵ_{ind} in the simulations are shown together with the analytical prediction given by Eqs. (13) and (14) in Fig. 4. The change in safety factor is shown in Fig. 5, where the analytical prediction is given by Eq. (15). The results show an excellent agreement between theory and simulations which validates the analytical model.

More complex JOREK simulations also show this behavior as it can be observed in the following VDE simulation where a hot NSTX plasma enters in contact with a highly resistive wall (see Fig. 6), which has also been used in benchmarks with other non-linear MHD codes recently in Ref. 15. During the simulation, a Spitzer-like resistivity profile $\eta = \eta_0 (T_{e0} / T_e)^{3/2}$ is chosen where the core electron temperature is $T_{e0} = 1$ keV. The temperature at the wall has a fixed value of $T_e = 1$ eV, which imposes a large plasma resistivity at the wall that scrapes-off the plasma edge when the plasma becomes limited. For the chosen wall resistivity, the plasma minor radius is reduced by a factor 2 in 6 ms, which is a short enough timescale to consider the plasma as highly conducting for the given plasma resistivity.

As it can be inferred from Fig. 7(b), the evolution of the safety factor is dominated by the change in plasma minor radius and the change in I_p starts influencing q_a when the minor radius has already dropped by a factor of 2. Here, the averaged minor radius is defined as $\langle a \rangle \equiv l_p / (2\pi)$, where l_p is the length of the poloidal flux contour of the plasma boundary. In Fig. 7(a), the obtained $\partial I_p / \partial a$ is compared with the prediction given by Eq. (16), where

FIG. 5. Simulation results and analytical predictions for $\delta q_a / q_a$ for different ideal wall minor radii.

the effective external inductance is calculated from the simulation with $L_{\text{ext}}(a) = 2\pi\psi_{p,\text{bnd}} / I_p$ as well as δI_{out} . Although the model and the simulation results do not agree as well as for the simple case shown in Fig. 3, the analytical model gives the correct behavior and order of magnitude of $\partial I_p / \partial a$. Discrepancies may be caused by the effect of a finite wall conductivity or the effect complex VDE generated flows breaking the rigid displacement assumption. The assessment of these effects is left for the future work.

IV. CONCLUSIONS

In the typical case where the effective external inductance $L_{\text{ext}}(a)$ and the edge current density J_{edge} are finite, we have demonstrated that $\delta I_p = \mathcal{O}(\delta a^2)$ for highly conducting plasmas that are scraped-off by a change in plasma radius of δa . In this case, the edge safety drops according to

FIG. 6. NSTX hot VDE at two different times showing the induction of edge currents. The toroidal current density is shown together with the wall boundary (black line) and the last closed flux surface (gray line).

FIG. 7. (a) Rate of change in plasma current with respect to the change in minor radius and (b) computed kink edge safety factor as a function of the averaged minor radius during an NSTX VDE simulation. The resulting q_a computed with Eq. (1) is compared with its value assuming a constant I_p during the simulation (dashed curve).

$$\frac{\delta q_a}{q_a} = -2 \frac{|\delta a|}{a} + \mathcal{O}(\delta a^2/a^2) < 0. \quad (20)$$

The analytical expression found for δI_p in general plasmas [Eq. (9)] has been validated in the limit of a circular plasma with a large aspect ratio with the help of free-boundary MHD simulations. Additional simulations for a realistic NSTX plasma qualitatively agree with the analytical predictions and prove the validity of (20). The change in current (δI_p) can grow to first order in δa when the accumulated edge current is comparable to the total current $\delta I_{\text{out}} = \mathcal{O}(I_p)$. Nevertheless, for typical tokamak values of $L_{\text{ext}}(a)$, the decay of I_p cannot stop the reduction of the edge safety factor [Eq. (17)]. The model and the simulations show that the plasma current is reduced by 15% after decreasing its minor radius by a factor of 2 which, for typical initial edge safety factors ($q_a \sim 3$), implies that $q_a < 1$ before $a < a_0/2$.

In the special case where a highly conducting wall is placed at the plasma boundary ($L_{\text{ext}}(a) \rightarrow 0$), half of the plasma current in the scraped-off domain can be induced in the wall implying that $\delta I_p = \mathcal{O}(\delta a)$. In this situation, δq_a is given by Eq. (18). Note, however, that during hot VDEs, the surrounding conducting structures are highly resistive compared to the plasma by definition. Therefore, during hot VDEs, q_a should evolve according to Eq. (20). Nevertheless, the ideal wall effect could play a role during phenomena like fast cold front penetration given by massive gas injection (MGI) or by shattered pellet injection (SPI) as planned for mitigation of such disruption events.¹⁶

ACKNOWLEDGMENTS

This work was supported by the ITER Monaco Fellowship. ITER is the Nuclear Facility INB No. 174. This paper explores physics processes during the plasma operation of the tokamak when disruptions take place; nevertheless, the nuclear operator is not constrained by the results presented here. The views and opinions expressed herein do not necessarily reflect those of the ITER organization.

REFERENCES

- ¹C. R. Sovinec and K. J. Bunkers, "Effects of asymmetries in computations of forced vertical displacement events," *Plasma Phys. Controlled Fusion* **61**(2), 024003 (2019).
- ²T. Schioler, C. Bachmann, G. Mazzone, and G. Sannazzaro, "Dynamic response of the ITER tokamak during asymmetric VDEs," *Fusion Eng. Des.* **86**(9-11), 1963–1966 (2011).
- ³S. N. Gerasimov, T. C. Hender, J. Morris, V. Riccardo, L. E. Zakharov, and JET EFDA Contributors, "Plasma current asymmetries during disruptions in JET," *Nucl. Fusion* **54**(7), 073009 (2014).
- ⁴J. A. Wesson, "Hydromagnetic stability of tokamaks," *Nucl. Fusion* **18**(1), 87 (1978).
- ⁵D. A. Humphreys and A. G. Kellman, "Analytic modeling of axisymmetric disruption halo currents," *Phys. Plasmas* **6**(7), 2742–2756 (1999).
- ⁶D. Hu, E. Nardon, M. Lehnen, G. T. A. Huysmans, D. C. van Vugt, and JET Contributors, "3D non-linear MHD simulation of the MHD response and density increase as a result of shattered pellet injection," *Nucl. Fusion* **58**(12), 126025 (2018).
- ⁷H. Strauss, "Reduction of asymmetric wall force in ITER disruptions with fast current quench," *Phys. Plasmas* **25**(2), 020702 (2018).
- ⁸D. Pfefferlé, N. Ferraro, S. C. Jardin, I. Krebs, and A. Bhattacharjee, "Modelling of NSTX hot vertical displacement events using M3D-C1," *Phys. Plasmas* **25**(5), 056106 (2018).
- ⁹EDA ITER et al., "MHD stability, operational limits and disruptions," *Nucl. Fusion* **39**(12), 2251–2389 (1999).
- ¹⁰A. H. Boozer, "Theory of tokamak disruptions," *Phys. Plasmas* **19**(5), 058101 (2012).
- ¹¹J. P. Freidberg, *Ideal MHD* (Cambridge University Press, 2014).
- ¹²R. Dengler, "Self inductance of a wire loop as a curve integral," *arXiv:1204.1486* (2012).
- ¹³G. T. A. Huysmans, "External kink (peeling) modes in x-point geometry," *Plasma Phys. Controlled Fusion* **47**(12), 2107 (2005).
- ¹⁴M. Hölzl, P. Merkel, G. T. A. Huysmans, E. Nardon, E. Strumberger, R. McAdams, I. Chapman, S. Günter, and K. Lackner, "Coupling JOREK and STARWALL codes for non-linear resistive-wall simulations," *J. Phys.: Conf. Ser.* **401**(1), 012010 (2012).
- ¹⁵I. Krebs, F. J. Artola, C. R. Sovinec, S. C. Jardin, K. J. Bunkers, M. Hoelzl, and N. M. Ferraro, "Axisymmetric simulations of vertical displacement events in tokamaks: A benchmark of M3D-C1, NIMROD and JOREK," *arXiv:1908.02387* (2019).
- ¹⁶M. Lehnen, K. Aleynikova, P. B. Aleynikov, D. J. Campbell, P. Drewelow, N. W. Eidietis, Yu. Gasparyan, R. S. Granetz, Y. Gribov, N. Hartmann et al., "Disruptions in ITER and strategies for their control and mitigation," *J. Nucl. Mater.* **463**, 39–48 (2015).