Hydrogen chloride gas in solvent-free continuous conversion of alcohols to chlorides in micro flow

Citation for published version (APA):

Borukhova, S., Noël, T., & Hessel, V. (2016). Hydrogen chloride gas in solvent-free continuous conversion of alcohols to chlorides in micro flow. *Organic Process Research & Development*, 20(2), 568-573.
<https://doi.org/10.1021/acs.oprd.6b00014>

DOI:

[10.1021/acs.oprd.6b00014](https://doi.org/10.1021/acs.oprd.6b00014)

Document status and date:

Published: 05/02/2016

Document Version:

Accepted manuscript including changes made at the peer-review stage

Please check the document version of this publication:

- A submitted manuscript is the version of the article upon submission and before peer-review. There can be important differences between the submitted version and the official published version of record. People interested in the research are advised to contact the author for the final version of the publication, or visit the DOI to the publisher's website.
- The final author version and the galley proof are versions of the publication after peer review.
- The final published version features the final layout of the paper including the volume, issue and page numbers.

[Link to publication](#)

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal.

If the publication is distributed under the terms of Article 25fa of the Dutch Copyright Act, indicated by the "Taverne" license above, please follow below link for the End User Agreement:

www.tue.nl/taverne

Take down policy

If you believe that this document breaches copyright please contact us at:

openaccess@tue.nl

providing details and we will investigate your claim.

Hydrogen chloride gas in solvent-free continuous conversion of alcohols to chlorides in micro flow

*Svetlana Borukhova, Timothy Noël, Volker Hessel**

Department of Chemical Engineering and Chemistry, Technische Universiteit Eindhoven, De Rondon 70, 5612 AP Eindhoven, The Netherlands.

Table of Contents

Abstract

Chlorides represent a class of valuable intermediates that are utilized in the preparation of bulk and fine chemicals. An earlier milestone to convert bulk alcohols to corresponding chlorides was reached when hydrochloric acid was used instead of toxic and wasteful chlorinating agents. This paper presents the development of an intensified solvent-free continuous process by using hydrogen chloride gas only. The handling of corrosive hydrogen chloride became effortless when the operating platform was split into dry and wet zones. The dry zone is used to deliver gas and prevent corrosion, while the wet zone is used to carry out the chemical transformation. The use of gas instead of hydrochloric acid allowed a decrease in hydrogen chloride equivalents from 3 to 1.2. In 20 min residence time, full conversion of benzyl alcohol yielded 96wt% of benzyl chloride in the product stream. According to green chemistry and engineering principles, the developed process is of an exemplary type due to its truly continuous nature, no use of solvent and formation of water as a sole by-product.

Keywords: micro flow, continuous synthesis, solvent-free, chlorodehydroxylation, process intensification

Introduction

Sustainable manufacturing of active pharmaceutical ingredients (APIs) encompasses several aspects such as continuous processing, process intensification, minimization of solvent use and advances in bioprocesses.¹ Currently, continuous processing is one aspect within process intensification, which targets the reduction of equipment size, costs, energy consumption, solvent utilization and waste generation.² Micro reactor technology is an actively studied platform aiming at implementing continuous processing, achieving process intensification and finally assisting in delivering sustainable processes for the production of APIs.³

In case of biologically active compound synthesis, the final target is constructed from intermediates. The quality of the final product and its cost are inevitably dependent on the manner intermediates are produced. Chlorides serve as good intermediates in the synthesis of APIs, usually in nucleophilic substitutions exemplified on Scheme 1, where a chloride atom is substituted by a nucleophile in the subsequent step.⁴ Due to the lower molecular weight of chloride, when compared to other halogens, substitution of chloride generates less waste.⁵ Unfortunately, synthesis of chlorides from alcohols requires highly toxic and waste-intensive chlorinating agents such as thionyl chloride,⁶ phosphorus chlorides⁷, pivaloyl chloride⁸, Vilsmeier reagent⁹, tosyl chloride¹⁰, 2,4,6-trichloro-[1,3,5]triazine with DMF¹¹, oxalyl chloride¹² and phosgene¹³. Mostly, chlorinating agents are used in stoichiometric or excessive amounts that lead to high generation of waste.¹⁴

Therefore, the ideal process would involve conversion of neat alcohols to chlorides by hydrogen chloride (HCl). This will minimize waste generation since the sole by-product is water. Kappe et

al. showed utilization of 30 wt% aqueous hydrochloric acid in chlorination of 1-butanol, 1-hexanol and 1-decanol within a micro reactor.¹⁵ In 15 min residence time, with 3 equivalents of 30 wt% aqueous HCl and at elevated temperatures quantitative yields were obtained. We recently realized a process utilizing 37 wt% aqueous HCl to afford a wider scope of aliphatic and benzylic substrates in the same time range.¹⁶ Furthermore, prepared chlorides were coupled with piperazine derivatives to synthesize cinnarizine, cyclizine and buclizine derivatives in multi-step continuous synthesis. The main drawback of both processes was the need for 3 equivalents of hydrochloric acid to prevent synthesis of by-products, such as ethers. In addition, continuity of the process was limited by the need to stop to refill the hydrochloric acid loop, which was used to circumvent corrosion of the pumps.

Scheme 1. Possible scaffolds that can be synthesized from chloroalkanes.

The limited solubility of hydrogen chloride in water leads to a limitation in its concentration. The maximum available concentration in hydrochloric acid is 37wt%, meaning that in the nucleophilic substitution case chloride competes with water as nucleophile. In order to maximize the concentration of hydrogen chloride within a medium, pure hydrogen chloride gas can be used. Using hydrogen chloride gas can also solve the problem of the aforementioned limited continuity and allows truly continuous processing. Large pressurized reaction vessels need to be under constant observation when such toxic and corrosive gases are used, requiring special precautions such as dedicated high-pressure facilities to avoid any leakages and allow moderate solubility of gaseous reagents in the reaction media. Gas-liquid reactions in large batch reactors are usually performed at lower temperatures to increase gas solubility and minimize associated risks. Finally, due to the low interfacial areas in batch reactors and low temperatures, reactions take place in extended times, which most of the times does not justify the effort.

Meanwhile, microreactors offer a great platform for gas-liquid reactions due to the formation of distinct, regular flow patterns with high periodicity or symmetry.¹⁷ These offer a high surface-to-volume ratio leading to high heat and mass transfer rates.¹⁸ Moreover, due to the low operating volumes of micro reactors only small volumes are pressurized at a time, while continuously performing the reaction. The higher safety associated with micro reactors allows investigation of a wide range of process conditions, usually leading to process intensification. A number of examples utilizing gases as reagents within micro flow reactors, such as CF_3I ,¹⁹ C_2H_2 ,²⁰ C_2H_4 ,²¹ CH_2O ,²² CH_2N_2 ,²³ Cl_2 ,²⁴ CO ,²⁵ CO_2 ,²⁶ F_2 ,²⁷ H_2 ,²⁸ NH_3 ,²⁹ O_2 ³⁰ and O_3 ³¹ have been published.

Herein, we report for the first time the use of hydrogen chloride gas as a reagent for a continuous synthesis of chloroalkanes in micro flow. Highly corrosive in the presence of moisture, hydrogen chloride requires special precautions during the design of the process. We

present related challenging aspects and corresponding solutions. Finally, the merit of the use of hydrogen chloride along with its limitations are presented.

Experimental platform

In order to control the flow rate of hydrogen chloride, a gas mass flow controller is needed. In general, mass flow controllers are made of stainless steel and hastelloy, which are susceptible to corrosion. Hydrogen chloride in its pure state is harmless to stainless steel and hastelloy. However, the moment the moisture content rises above 10 ppm, severe corrosion starts to take place. Therefore, absolute dry conditions are needed to prevent the corrosion of the device. By splitting the experimental setup into two zones, dry and wet, first as a hydrogen chloride gas delivery unit and second as a reaction rig, the corrosion was circumvented.

Hydrogen chloride delivery unit

Figure 1 (top) shows the assembly of the hydrogen chloride supply unit. In order to keep moisture out of the unit all connections were of VCR type from Swagelok. Moreover, due to the fact that polymer based tubing is permeable to moisture, stainless steel tubing of 1/4" size was used. One out of three nitrogen bottles was set to 40 bar for startups and shutdowns of the system. The other two were set to 15 bar pressure to be used in constant purging of the system in between experiments to prevent diffusion of moisture into the mass flow controller. Despite purging, a diffusion front is still present, which takes place in the direction opposite to the flowing nitrogen. Therefore, a stainless steel 2 m long 'pig tail' with 250 μm internal diameter was added following the last valve of the delivery unit. In our experience, inline non-metallic check valves sometimes fail at high pressures and allow liquid to enter the gas stream. In case of

such an unexpected failure, the liquid shall destroy the mass flow controller upon reaching it due to corrosion.

Figure 1. Hydrogen chloride gas delivery unit (top, dry zone) and chlorodehydroxylation rig (bottom, wet zones), where reaction takes place.

In order to visually verify if any liquid ever was moving towards the mass flow controller, transparent ethylene tetrafluoroethylene (ETFE) tubing of 250 μm was added after stainless steel tubing. A polyether ether ketone (PEEK) valve was attached, which can be shut in case liquid

flow was detected. Another 2 m of ETFE tubing of 750 μm was added after, followed by an inline check valve.

In order to enhance desorption of water molecules from the surface of the tubing used in construction of the setup, a vacuum line was installed. A cyclic vacuum-purge procedure was applied before the start of the operation and before disassembling the setup. It is important to mention that in case of no vacuum, and sole purging, components of the setup corrode upon disassembly and exposure to air. A by-pass around the mass flow controller was installed to assist vacuuming of the mass flow controller from both ends. Before introducing hydrogen chloride into the unit for the first time, a dew point transmitter was used to measure moisture content. A moisture content of 0.8 ppm was typical for our system due to the dry nitrogen that was used for purging after purge-vacuum procedure. Pictures with a more detailed information regarding the setup are enclosed in the supporting information.

Chlorodehydroxylation rig

Alcohols that are liquid under atmospheric conditions were pumped with a Knauer HPLC pump. A gas-liquid slug flow initiated in a Y-mixer and continued into the ETFE reactor as shown in Figure 1 (bottom). (NOTE: a T-mixer was not suitable due to the liquid slugs appearing on the gas feed line prior to the mixer. As a result, these penetrations brought about fluctuations in the gas flow rate observed on the mass flow controller.) The reactor was made of ETFE tubing of 762 μm internal diameter. When 1 mm inner diameter tubing was used instead, escape of gas into the heating media upon operation was observed, due to the thinner wall thickness. A hot product stream was allowed to flow through 30 cm long tubing prior to entering the Equilibar back pressure regulator (BPR) to allow cooling. For present application, an Equilibar BPR

demonstrated a unique ability to apply pressure and keep gas-liquid flows stable up to 16 bar pressure. Its use circumvented the need for gas-liquid separation prior to the pressurization unit. (NOTE: Inline cartridge based BPRs could not provide constant flow, and resulted rather in stop-flow behavior, which affected the operation of the mass flow controller, thus causing inaccuracy in the gas flow rate.) Table 1 demonstrates the window of operating conditions of the operating platform.

Table 1. Operating parameters of chlorodehydroxylation flow setup

Parameter	Range
Reactor volume	4 ml
Reactor internal diameter	762 μm
Gas mass flow rate	0.001-0.600 g/min (0.1-80 ml/min)
Reactant flow rate	0.09-0.15 ml/min
Temperature	25-120°C
Pressure	16 bar

Results and Discussion

Benzyl chloride is used as an intermediate in the preparation of pharmaceuticals, flavorants, plasticizers and perfumes. According to Gerrard et al., hydrogen chloride dissolves in benzyl alcohol under atmospheric pressure to a significant extent as shown in Figure 2^[32]. Significant absorption of gas, as shown in Figure 3, was observed when benzyl alcohol and hydrogen chloride were mixed in the tubing prior to entering the reactor coil (at room temperature under 5 bar pressure). In theory, the solubility of gas in liquid increases with pressure and decreases with temperature. In addition, throughout the reactor the gas is consumed as the reaction progresses.

With an increase in temperature, the extent of gas expansion, and thus residence time as well, are hard to quantify due to its substantial expansion and faster consumption. Therefore, the sole measure of success of a reaction was based on the yield of synthesized chloride, while residence time was estimated based on flow behavior. In-line absorption measurements to determine the residence time were avoided due to the corrosive nature of the product stream.

Figure 2. Solubility of hydrogen chloride gas in 1-butanol and benzyl alcohol (redrawn with permission of John Wiley and Sons from).³²

Figure 3. Gas slug size with respect to distance from the mixing point of gas and liquid, Y-mixer.

One of the goals in using gas was to minimize excess of HCl used, thus generated waste. In our previous investigations with 3 equivalents hydrochloric acid, in 15 min residence time at 120°C >99% yield of benzyl chloride was obtained. Decreasing equivalents of HCl gas to one and allowing the same residence time resulted in 80wt% at 60°C and 89wt% at 100°C. Higher temperatures were not investigated due to a significant expansion of gas slugs, leading to significantly reduced residence time. Dibenzyl ether was formed as a sole side-product in 3wt% at 60°C and 5wt% at 100°C. Important to stress is that no gas slugs were observed at the inlet of BPR, and minor amount of gas slugs was observed at the outlet.

To see whether benzyl ether formation could be minimized, while maximizing the yield of benzyl chloride, the effect of hydrogen chloride excess was studied. Gradually, increasing equivalents from 1.0 to 2.0 led to no change in side-product formation at 100°C. We therefore

decided to screen different reaction temperatures at 1.1 and 1.5 equivalents. The results tabulated in Table 2 show that the selectivity does not improve with excess of hydrogen chloride. With the increase of equivalents, gas-hold up in the reactor increased, which led to a marginal decrease in residence time.

Assuming that dibenzyl ether is formed due to insufficient hydrogen chloride, prompted us to increase the system pressure to allow a higher concentration of hydrogen chloride within the liquid phase. Figure 4 shows the pressure effect on the reactant, product and side-product weight distribution at 80 °C. Benzyl chloride production increases with pressure from 79wt% at 5 bar to 93wt% at 16 bar, while the formation of byproduct stays the same and equal to 3-4wt%. Thus, higher concentration of hydrogen chloride increased the conversion, while showing no effect on

Table 2. Effect on benzyl chloride and dibenzyl ether formation at various temperatures and equivalents of hydrogen chloride.

Entry	Eq HCl	T (°C)	BenzCl (wt%)	DBE (wt%)
1	1.1	80	89	3
2	1.1	90	92	5
3	1.1	100	95	5
4	1.5	80	87	3
5	1.5	90	96	4
6	1.5	100	95	5
7	2.0	100	95	5

selectivity. No change in conversion was observed with increasing pressure at 90 °C and 100 °C. Dibenzyl ether formed in 4wt% at 90 °C with 92wt% of benzyl chloride, and in 5wt% at 100 °C with 95wt% of benzyl chloride. We proceeded further with increasing equivalents at higher

pressure (10, 12, 16 bar) at 100°C. The minimum concentration of dibenzyl ether was 4% at 10 bar at 1.2 and more equivalents. Therefore, those conditions, i.e. 100°C, 1.2 equivalents, 20 min residence time and 10 bar were set as optimal, yielding full conversion and 96wt% of benzyl chloride.

Expansion of scope

Optimized conditions for benzyl alcohol were applied to a range of aliphatic and benzylic alcohols. Scheme 2 shows corresponding yields at 100°C, 1.2 equivalents and 10 bar. When, aliphatic alcohols were used a significant decrease in gas solubility was observed that lead to large gas slugs both at the Y-mixer and at the BPR outlet. Increase in gas slugs drastically decreased the residence time to <5 min in the reactor (4 ml) used for benzyl alcohol. In order to

Figure 4. Pressure effect on weight distribution among benzyl chloride (red), benzyl alcohol (blue) and dibenzyl ether (green).

have a similar residence time as for benzyl alcohol experiments, a 10 ml reactor was used instead, which led to residence time ranging from 15-20 min depending on the substrate used. The difference in residence time is due to the different extent of gas absorption within the liquid phase.

The rate of nucleophilic substitution reactions depends on the type of nucleophile, electrophile, solvent and leaving group. In order to assist nucleophilic substitution, either polar protic (S_N1) or aprotic (S_N2), solvents are used as solvents. One of the frequently used reaction systems in solvent-free nucleophilic substitutions is solvolysis, when the solvent is used as a nucleophile. The current investigation comprises a reverse system, where electrophile is a solvent. While the nucleophile is a chloride anion resulting from dissociation of hydrogen chloride.

Scheme 2. Prepared chloroalkanes at optimal for benzyl chloride conditions, i.e. 120 °C, 10 bar with 1.2 equivalents of hydrogen chloride. *-reactions carried out in 10 ml reactor.

Primary alkanes undergo S_N2 type of nucleophilic substitution, which occurs via a back-attack of an electrophile.³³ Due to insufficient polarity and relatively low hydrogen bonding in primary aliphatic alcohols, dissociation to release a free chloride anion as a nucleophile is not favorable. In contrast, due to the higher polarity and/or stronger hydrogen bonding present within pentanediol, both solubility of HCl gas and conversion of the alcohol were significantly increased. Conversion of pentanediol increased to 98%, resulting in the formation of 1,5-dichloro pentane as a sole side product. Secondary alkanes can react via S_N2 or S_N1 depending on the steric hindrance of an electrophilic carbon or stabilization of the cationic intermediate. Higher yields in isopropyl alcohol and cyclohexyl alcohol cases can be explained by this additional path being available. Among benzylic species 3-methoxy benzyl alcohol resulted in the largest gas consumption and the highest yield with no traces of a dibenzyl ether derivative forming. Conversion decreased when 2,6-difluorobenzyl alcohol was used, while no side product was formed. In case of 2-phenylethanol absolutely no conversion was observed. These observations indicate that resonance stabilization of the benzyl cation is responsible for better yields when compared to aliphatic substrates and that S_N1 is a main path for the reactions to take place.

In case with secondary and benzylic alcohols dissociation of protonated alcohols results in water and carbocation. As the reaction proceeds, more of the water is formed promoting dissociation of hydrogen chloride, increasing not only the absorption of HCl, but also the rate of S_N1 reactions. Looking back at the optimization of benzyl alcohol, it can be concluded that at the start of the reaction when limited water is formed as a by-product, resulting in a limited amount of chloride anion, benzyl cation associates with both benzyl alcohol and chloride. Once a certain threshold concentration of water is reached, the chloride prevails in the reaction to combine with the

benzyl cation. The S_N1 reaction pathway is also supported by the fact that no effect on the selectivity was observed when an excess of hydrogen chloride was used.

Conclusion

A continuous synthesis of chlorides from bulk alcohols via use of hydrogen chloride gas instead of toxic and wasteful chlorinating agents is demonstrated. The most challenging aspect of safe handling of this corrosive gas was its continuous controlled delivery into the reacting system. The elimination of moisture by continuous purging of the setup with dry nitrogen solved any corrosion issues.

The use of a micro flow reactor allowed the application of process conditions that are beyond the limits of conventional batch technology. High temperature and pressure, easily applicable within the reacting system allowed reaching the initial objective of minimizing the excess of HCl used from 3 equivalents to 1.2. However, the developed process is more beneficial for S_N1 type reactions than S_N2 . As a result, further investigations are needed for the synthesis of specific target chloroalkanes. One of the possible steps is minimal addition of polar aprotic solvents to promote S_N2 . Based on green chemistry and engineering principles, a significant improvement is demonstrated due to the truly continuous nature of the process, no use of solvent and formation of only water as a by-product.

ASSOCIATED CONTENT

Supporting Information. Experimental procedure along with a more detailed description of operating platform are available free of charge via the Internet at <http://pubs.acs.org>.

AUTHOR INFORMATION

Corresponding Author

*Email: v.hessel@tue.nl

ACKNOWLEDGMENT

We would like to thank Erik van Herk, Bert Metten and Bart van Heugten for their help during different stages of our investigation. Funding by the Advanced European Research Council Grant “Novel Process Windows – Boosted Micro Process Technology” (Grant number: 267443) is kindly acknowledged.

References

- (1) Jiménez-González, C.; Poechlauer, P.; Broxterman, Q. B.; Yang, B.-S.; am Ende, D.; Baird, J.; Bertsch, C.; Hannah, R. E.; Dell’Orco, P.; Noorman, H.; Yee, S.; Reintjens, R.; Wells, A.; Massonneau, V.; Manley, J. *Org. Process Res. Dev.* **2011**, *15*, 900–911.
- (2) Poechlauer, P.; Colberg, J.; Fisher, E.; Jansen, M.; Johnson, M. D.; Koenig, S. G.; Lawler, M.; Laporte, T.; Manley, J.; Martin, B.; O’Kearney-McMullan, A. *Org. Process Res. Dev.* **2013**, *17*, 1472–1478.
- (3) (a) Vaccaro, L.; Lanari, D.; Marrocchi, A.; Strappaveccia, G. *Green Chem.* **2014**, *16*, 3680–3704; (b) Hessel, V.; Kralisch, D.; Kockmann, N.; Noël, T.; Wang, Q.; *ChemSusChem* **2013**, *6*, 746–789; (c) Tambarussi Baraldi, P.; Hessel, V. *Green Process Synth* **2012**, *1*, 149–168; (d) Borukhova, S. and Hessel, V. **2015**, in *Continuous Manufacturing of Pharmaceuticals* (eds. P. Kleinebudde, J. Khinast and J. Rantanen), Wiley Inc.
- (4) (a) Carey, J. S.; Laffan, D.; Thomson, C.; Williams, M. T. *Org. Biomol. Chem.* **2006**, *4*, 2337–2347; (b) Carey, J. S.; Laffan, D. In *Pharmaceutical Process Development: Current Chemical and Engineering Challenges*; The Royal Society of Chemistry, **2011**; pp. 39–65.
- (5) Anastas, P.; Eghbali, N. *Chem. Soc. Rev.* **2010**, *39*, 301–312.
- (6) Chaudhari, S. S.; Akamanchi, K. G. *Synlett* **1999**, 1763–1765.
- (7) Weiss, R. G.; Snyder, E. I. *Chem. Commun. (London)* **1968**, 1358–1359.
- (8) Dubey, A.; Upadhyay, A. K.; Kumar, P. *Tetrahedron Lett.* **2010**, *51*, 744–746.
- (9) Kimura, Y.; Matsuura, D. *Ijoc* **2013**, *2013*, 1–7.
- (10) Ding, R.; He, Y.; Wang, X.; Xu, J.; Chen, Y.; Feng, M.; Qi, C. *Molecules* **2011**, *16*, 5665–5673.
- (11) De Luca, L.; Giacomelli, G.; Porcheddu, A. *Org. Lett.* **2002**, *4*, 553–555.
- (12) Denton, R. M.; An, J.; Adeniran, B. *Chem. Commun.* **2010**, *46*, 3025–3027.
- (13) Ayala, C. E.; Villalpando, A.; Nguyen, A. L.; McCandless, G. T.; Kartika, R. *Org. Lett.* **2012**, *14*, 3676–3679.
- (14) Adams, J. P.; Alder, C. M.; Andrews, I.; Bullion, A. M.; Campbell-Crawford, M.; Darcy, M. G.; Hayler, J. D.; Henderson, R. K.; Oare, C. A.; Pendrak, I.; Redman, A. M.; Shuster, L. E.; Sneddon, H. F.; Walker, M. D. *Green Chem.* **2013**, *15*, 1542–1549.
- (15) Reichart, B.; Tekautz, G.; Kappe, C. O. *Org. Process Res. Dev.* **2013**, *17*, 152–157.
- (16) Borukhova, S.; Noël, T.; Hessel, V. *ChemSusChem* **2016**, *9*, 67–74.
- (17) (a) Hessel, V.; Angeli, P.; Gavriilidis, A.; Löwe, H.; *Ind. Eng. Chem. Res.* **2005**, *44*, 9750–9769. (b) Gunther, A.; Khan, S. A.; Thalmann, M.; Trachsel, F.; Jensen, K. F. *Lab Chip* **2004**, *4*, 278–286. (c) Dencic, I.; Hessel, V.; De Croon, M. H. J. M.; Meuldijk, J.; Van Der Doelen, C. W. J.; Koch, K. *ChemSusChem* **2012**, *5*, 232–245. (d) Dencic, I.; Hessel, V. In *Microrreactors in Organic Chemistry and Catalysis*; 2013; pp. 221–288. (e) Chen, G.; Yue, J.; Yuan, Q. *Chinese J. Chem. Eng.* **2008**, *16*, 663–669.

- (f) Sobieszuk, P.; Aubin, J.; Pohorecki, R. *Chem. Eng. Technol.* **2012**, *35*, 1346–1358.
- (18) (a) Mallia, C. J.; Baxendale, I. R. *Org. Process Res. Dev.* **2015**. (b) Su, Y.; Hessel, V.; Noël, T. *AIChE J.* **2015**, *61*, 2215–2227.
- (19) (a) Straathof, N. J. W.; Gemoets, H. P. L.; Wang, X.; Schouten, J. C.; Hessel, V.; Noël, T. *ChemSusChem* **2014**, *7*, 1612–1617. (b) Straathof, N. J. W.; Tegelbeckers, B. J. P.; Hessel, V.; Wang, X.; Noel, T. *Chem. Sci.* **2014**, *5*, 4768–4773. (c) Straathof, N.; Osch, D.; Schouten, A.; Wang, X.; Schouten, J.; Hessel, V.; Noël, T. *J. Flow Chem.* **2014**, *4*, 12–17.
- (20) Deng, Q.; Shen, R.; Ding, R.; Zhang, L. *Adv. Synth. Catal.* **2014**, *356*, 2931–2936.
- (21) (a) Samuel, C.; Bourne, L.; Koos, P.; Brien, M. O.; Martin, B.; Schenkel, B.; Baxendale, I. R.; Ley, S. V. **2011**. (b) Terao, K.; Nishiyama, Y.; Tanimoto, H.; Morimoto, T.; Oelgemöller, M.; Morimoto, T. *J. Flow Chem.* **2012**, *2*, 73–76.
- (22) Buba, A. E.; Koch, S.; Kunz, H.; Löwe, H. *European J. Org. Chem.* **2013**, *2013*, 4509–4513.
- (23) (a) Maurya, R. A.; Park, C. P.; Lee, J. H.; Kim, D.-P. *Angew. Chemie Int. Ed.* **2011**, *50*, 5952–5955. (b) Pinho, V. D.; Gutmann, B.; Miranda, L. S. M.; de Souza, R. O. M. A.; Kappe, C. O. *J. Org. Chem.* **2014**, *79*, 1555–1562.
- (24) Hrich, H.; Linke, D.; Morgenschweis, K.; Baerns, M.; Jähnisch, K. *Chim. Int. J. Chem.* **2002**, *56*, 647–653.
- (25) (a) Gong, X.; Miller, P. W.; Gee, A. D.; Long, N. J.; de Mello, A. J.; Vilar, R. *Chem. – A Eur. J.* **2012**, *18*, 2768–2772. (b) Miller, P. W.; Long, N. J.; de Mello, A. J.; Vilar, R.; Audrain, H.; Bender, D.; Passchier, J.; Gee, A. *Angew. Chem. Int. Ed. Engl.* **2007**, *46*, 2875–2878. (c) Miller, P. W.; Long, N. J.; de Mello, A. J.; Vilar, R.; Passchier, J.; Gee, A. *Chem. Commun.* **2006**, 546–548. (d) Murphy, E. R.; Martinelli, J. R.; Zaborenko, N.; Buchwald, S. L.; Jensen, K. F. *Angew. Chem. Int. Ed. Engl.* **2007**, *46*, 1734–1737. (e) Koos, P.; Gross, U.; Polyzos, A.; O'Brien, M.; Baxendale, I.; Ley, S. V. *Org. Biomol. Chem.* **2011**, *9*, 6903–6908. (f) Gross, U.; Koos, P.; O'Brien, M.; Polyzos, A.; Ley, S. V. *European J. Org. Chem.* **2014**, *2014*, 6418–6430. (g) Mercadante, M. a; Leadbeater, N. E. *Org. Biomol. Chem.* **2011**, *9*, 6575–6578. (h) Takebayashi, Y.; Sue, K.; Yoda, S.; Furuya, T.; Mae, K. *Chem. Eng. J.* **2012**, *180*, 250–254.
- (26) (a) Wu, J.; Yang, X.; He, Z.; Mao, X.; Hatton, T. A.; Jamison, T. F. *Angew. Chemie Int. Ed.* **2014**, *53*, 8416–8420. (b) Pieber, B.; Glasnov, T.; Kappe, C. O. *RSC Adv.* **2014**, *4*, 13430–13433. (c) Kupracz, L.; Kirschning, A. *Adv. Synth. Catal.* **2013**, *355*, 3375–3380. (d) van Gool, J. J. F.; van den Broek, S. A. M. W.; Ripken, R. M.; Nieuwland, P. J.; Koch, K.; Rutjes, F. P. J. T. *Chem. Eng. Technol.* **2013**, *36*, 1042–1046. (e) Sci, C.; Brien, M. O.; Taylor, N.; Polyzos, A.; Baxendale, I. R.; Ley, S. V. **2011**, 1250–1257.
- (27) McPake, C. B.; Sandford, G. *Org. Process Res. Dev.* **2012**, *16*, 844–851.
- (28) Cossar, P. J.; Hizartzidis, L.; Simone, M. I.; McCluskey, A.; Gordon, C. P. *Org. Biomol. Chem.* **2015**, *13*, 7119–7130.
- (29) Cranwell, P. B.; O'Brien, M.; Browne, D. L.; Koos, P.; Polyzos, A.; Pena-Lopez, M.; Ley, S. V. *Org. Biomol. Chem.* **2012**, *10*, 5774–5779.
- (30) (a) Gemoets, H. P. L.; Hessel, V.; Noël, T. *Org. Lett.* **2014**, *16*, 5800–5803. (b) Vanoye, L.; Aloui, A.; Pablos, M.; Philippe, R.; Percheron, A.; Favre-Réguillon, A.; de Bellefon, C. *Org. Lett.* **2013**, *15*, 5978–5981. (c) Chaudhuri, S. R.; Hartwig, J.; Kupracz, L.; Kodanek, T.; Wegner, J.; Kirschning, A. *Adv. Synth. Catal.* **2014**, *356*, 3530–3538. (d) Sipos, G.; Gyollai, V.; Sipőcz, T.; Dormán, G.; Kocsis, L.; Jones, R. V.; Darvas, F. *J. Flow Chem.* **2013**, *3*, 51–58. (e) Pieber, B.; Kappe, C. O. *Green Chem.* **2013**, *15*, 320–324. (f) Gemoets, H. P. L.; Su, Y.; Shang, M.; Hessel, V.; Luque, R.; Noel, T. *Chem. Soc. Rev.* **2016**, *45*, 83–117. (g) Talla, A.; Driessen, B.; Straathof, N. J. W.; Milroy, L.-G.; Brunsveld, L.; Hessel, V.; Noël, T. *Adv. Synth. Catal.* **2015**, *357*, 2180–2186.
- (31) (a) Wada, Y.; Schmidt, M.A.; Jensen, K.F. *Ind. Eng. Chem. Res.* **2006**, *45*, 8036–8042. (b) O'Brien, M.; Baxendale, I. R.; Ley, S. V. *Org. Lett.* **2010**, *12*, 1596–1598. (c) Irfan, M.; Glasnov, T. N.; Kappe, C. O. *Org. Lett.* **2011**, *13*, 984–987. (d) Zak, J.; Ron, D.; Riva, E.; Harding, H. P.; Cross, B. C. S.; Baxendale, I. R. *Chem. – A Eur. J.* **2012**, *18*, 9901–9910.
- (32) Gerrard, W.; MacKlen, E. *J. Appl. Chem.* **1956**, *6*, 241–244.
- (33) Streitwieser, A. *Chem. Rev.* **1956**, *56*, 571–752.