Experimental demonstration of advanced service management in SDN/NFV Fronthaul Networks deploying ARoF and PoF

Citation for published version (APA):

Muñoz, R., Vilalta, R., Manso, C., Rodríguez, L., Fàbrega, J. M., Brenes, J., Landi, G., Capitani, M., Otero, G., Larrabeiti, D., Vazquez, C., Lopez-Cardona, J. D., Grivas, E., Lagkas, T., Klonidis, D., Rommel, S., Martínez, R., Casellas, R., & Tafur Monroy, I. (2020). Experimental demonstration of advanced service management in SDN/NFV Fronthaul Networks deploying ARoF and PoF. In *Proceedings of the 45th European Conference on Optical Communication (ECOC 2019)* (IET Conference Publications; No. CP765). Institution of Engineering and Technology (IET). <https://doi.org/10.1049/cp.2019.1191>

DOI:

[10.1049/cp.2019.1191](https://doi.org/10.1049/cp.2019.1191)

Document status and date:

Published: 30/06/2020

Document Version:

Accepted manuscript including changes made at the peer-review stage

Please check the document version of this publication:

- A submitted manuscript is the version of the article upon submission and before peer-review. There can be important differences between the submitted version and the official published version of record. People interested in the research are advised to contact the author for the final version of the publication, or visit the DOI to the publisher's website.
- The final author version and the galley proof are versions of the publication after peer review.
- The final published version features the final layout of the paper including the volume, issue and page numbers.

[Link to publication](#)

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal.

If the publication is distributed under the terms of Article 25fa of the Dutch Copyright Act, indicated by the "Taverne" license above, please follow below link for the End User Agreement:

www.tue.nl/taverne

Take down policy

If you believe that this document breaches copyright please contact us at:

openaccess@tue.nl

providing details and we will investigate your claim.

EXPERIMENTAL DEMONSTRATION OF ADVANCED SERVICE MANAGEMENT IN SDN/NFV FRONTHAUL NETWORKS DEPLOYING ARoF AND PoF

R. Muñoz^{1}, R. Vilalta¹, C. Manso¹, L. Rodríguez¹, J. M. Fàbrega¹, J. Brenes², G. Landi², M. Capitani², G. Otero³, D. Larrabeiti³, C. Vazquez³, J. D. Lopez-Cardona³, E. Grivas⁴, T. Lagkas⁵, D. Klonidis⁵, S. Rommel⁶, R. Martínez¹, R. Casellas¹, I. Tafur Monroy⁶*

¹Centre Tecnològic de Telecomunicacions de Catalunya (CTTC/CERCA), Castelldefels (Barcelona), Spain

²Nextworks, Pisa, Italy

³Universidad Carlos III de Madrid (UC3M), Madrid, Spain

⁴Eulambia Advanced Technologies, Athens, Greece

⁵Athens Information Technology, Athens, Greece

⁶Eindhoven University of Technology, Eindhoven, Netherlands

*E-mail: raul.munoz@cttc.es

Keywords: OPTICAL FRONTHAUL, SDN AND NFV, vCDN VERTICAL SERVICE, PoF, ARoF

Abstract

We demonstrate two advanced services deployed in a novel SDN/NFV optical fronthaul network combining analog radio over fiber (ARoF) and power over fiber (PoF); vertical service management for virtual content delivery networks (vCDNs), and user mobility and remote optical power management for femto cells

1 Introduction

Current fronthaul transport networks are based on point-to-point optical/WDM links between the radio cells and the central office (CO) using digital radio over fiber (DRoF) transceivers [1]. In this paper we consider the novel optical fronthaul architecture shown in Fig.1 [2]. It deploys a passive optical distribution network (ODN) based on space division multiplexing (SDM) for further increasing the network capacity [3]. It makes use of the already deployed bundles of single mode fibers (SMF) or multi-core fibers (MCF). Analog radio over fiber (ARoF) transceivers are used between analog BBUs and RRHs instead of DRoF transceivers to reduce the bandwidth and latency requirements. ARoF transceivers in combination with SDM enable to directly modulate the radio waveforms onto light and transmit them in parallel over different spectral frequencies and spatial cores. Another novelty introduced is the transmission of optical power through the fiber. Although power over fiber (PoF) is at a very early development stage, the interest of this technology for 5G is big, given the high costs of deployment of base stations in areas where no power supply is easily available to feed femto cells [4]. It would enable to remotely sleep/awake the base station based on the user occupancy. Finally, the CO also deploys edge computing for virtual network functions (VNF) or mobile edge computing (MEC) applications.

This novel optical fronthaul architecture brings many innovations in the SDN/NFV management and orchestration (MANO) layer that need to be faced [5]:

- ARoF transceivers must be integrated in the SDN controller in order to provision optical transport connections
- The analog RRHs and BBUs must be managed as physical network functions (PNF) and integrated with the NFV orchestrator in order to provide NFV network services.
- A network slice manager (NSM) must be deployed on top of the NFV orchestrator to deploy network slices for vertical services
- PoF devices need to be managed and integrated with the user mobility manager to enable the optimization of the femto cells management based on the user occupancy.

This paper presents, first, the innovations of the target SDN/NFV fronthaul test scenario, and second, two use cases that will be experimentally demonstrated, the vertical service for virtual content delivery network (vCDN), and the user mobility and remote power management for femto cells.

Fig. 1. Proposed optical fronthaul architecture

computing and network resources required for the VNFs and the virtual links, and (iii) the ARoF transceivers parameters' configuration. Starting from these outputs, the NFV manager instantiates the VNFs and the virtual networks interacting with the OpenStack-based VIM. As additional steps, specific for the proposed architecture, the NFV Service Platform also drives the configuration of the BBU and RRH PNFs and creates transport connections in the fronthaul segment.

The PNF configuration is handled through the PNFM, which interacts with the PNF Agents. For the configuration of the SDM/WDM enabled fronthaul, the NFVO interacts with the transport SDN controller using the TAPI interface. Such approach allows to abstract the network configuration complexity from the orchestrator perspective, handling all the SDM/WDM technology details within the transport SDN controller. In fact, as shown in Fig.3, the NFV service platform selects only the TAPI service interface points (SIPs) and the high-level path resources to carry the CDN traffic flows, while the enforcement of network connectivity is fully handled at the transport SDN controller level, including the configuration of the ARoF transceivers at the CO and RU.

3.2 User mobility and remote power management

The second use case demonstrated is user mobility and power management of remotely fed femto cell RRHs. User mobility is modelled by the mobility manager (top-left box on Fig.2). This entity models both the movement of user equipment (UE) through a 5G radio access network and its observable behaviour regarding cell binding, handovers, radio resource allocation and data packet transfer of that UE. This 5G signalling process is abstracted within the mobility manager but in reality it is carried out by several 5G entities: the UE, the gNBs (5G

base stations), the mobility management entity (MME) and the 5G core (5GC). In our use case, we focus on the NFV/SDN-based provisioning of vertical services and powering resources implied by handovers to cells with the sleep/awake capability envisioned for 5G. To this end, user mobility is enhanced with a novel remote power management extension. Thus, whereas the mobility manager denotes what base station to sleep or awake, the power manager is in charge of deciding which cells need to be remotely powered by PoF at any given time, not just those with users. The concrete target simulated scenario is the phantom cell scenario with PoF pooling [4]. In this scenario, the geographical area is covered by a set of macro-cells, which are complemented with a set of low power millimeter-wave femto cells (a.k.a. phantom cells) equipped with batteries that are awakened and powered when the UE enters the cell. Under PoF pooling, a pool of high-power laser diodes (HPLDs) is shared by a large number of femto cells and the power manager tries to keep all their batteries at full charge.

In the demonstration, the following steps take place: (1) a user enters a phantom femto cell and the source gNB (the macro cell base station) issues a handover request ; (2) then the visited phantom cell is started by its owner macro cell; this is modelled by: (2.1) the mobility manager requests a vertical service for the phantom cell by calling the network slice manager (this implicitly launches the ARoF system for the cell); and (2.2) the power manager, which is subscribed to mobility manager events, starts a PoF session to feed the phantom cell (provided that this is the most suitable allocation for one of the HPLDs); this is done by: (2.2.1) selecting and configuring a HPLD by calling the CO-PoF Agent, (2.2.2) selecting and configuring a photovoltaic converter (PVC) by calling the RU-PoF Agent and, if HPLD and PVC are not statically attached, by (2.2.3) issuing a request to the SDN network controller to request a power fiber core to be switched between the HPLD and the PVC. (3) once the RoF session is started, the handover takes place and the UE makes use of the phantom cell; (4) the power manager polls periodically the PoF agents to supervise phantom cell battery status, temperature, output voltage, etc. (5) the UE leaves the cell and the resources are released. The demonstration includes a 2D graphical representation of UEs moving in an area covered by the CO with a number of macro and phantom cells.

4 Conclusions

This paper has provided a description of the implemented SDN/NFV MANO layer developed to control and orchestrate the resources and services of the novel optical 5G fronthaul network. A vertical service based on virtual CDN and remote optical power management to sleep/awake the femtocells based on the users' location have been presented.

5 Acknowledgements

This work is supported by EC H2020 blueSPACE (GA no. 762055) project and AURORAS (RTI2018-099178-B-100) .

Fig. 3. NFV-MANO/SDN workflow for service provisioning

6 References

- [1] R. Muñoz et al., “SDN control and monitoring of SDM/WDM and packet transport networks for 5G fronthaul/backhaul”, IEEE Summer Topicals Meetings Series, 2018.
- [2] R. Muñoz, M. Capitani, S. Rommel, et al. SDN/NFV 5G Fronthaul Networks Integrating Analog/Digital RoF, Optical Beamforming, Power over Fiber and Optical SDM Technologies, in Proceedings of European Conference on Networks and Communications (EUCNC), 18-21 June 2019, Valencia, Spain. Slovenia.
- [3] S. Rommel et al., “High-capacity 5G fronthaul networks based on optical space division multiplexing,” IEEE Transactions on Broadcasting, 2019.
- [4] G. Otero, et al. “SDN-based Multi-Core Power-over-Fiber (PoF) System for 5G Fronthaul: Towards PoF Pooling”, in Proceeding of European Conference on Optical Communication (ECOC), Sept 2018, Rome, Italy.
- [5] R. Muñoz, R. Vilalta, J. M. Fabrega, et al., BlueSPACE’s SDN/NFV Architecture for 5G SDM/WDM-enabled Fronthaul with Edge Computing , in Proceedings of European Conference on Networks and Communications (EUCNC), 18-21 June 2018, Ljubljana, Slovenia.
- [6] R. Vilalta, R. Muñoz, G. Landi, L. Rodríguez-Navas, M. Capitani, R. Casellas, R. Martínez, Experimental Demonstration of the BlueSPACE’s NFV MANO Framework for the Control of SDM/WDM-enabled Fronthaul and Packetbased Transport Networks by Extending the TAPI , in Proceedings of European Conference on Optical Communications (ECOC), 23-27 September 2018, Roma (Italy).
- [7] Online at <https://github.com/CTTC-ONS/bluespace>, May 2019.
- [8] G. Landi, P. Giardina, M. Capitani, K. Kondepu, L. Valcarenghi, G. Avino: ‘Demo: provisioning and automated scaling of network slices for virtual Content Delivery Networks in 5G infrastructures’, ACM MOBIHOC 2019