Axial segregation in high intensity discharge lamps measured by laser absorption spectroscopy

Citation for published version (APA):

Flikweert, A. J., Nimalasuriya, T., Groothuis, C. H. J. M., Kroesen, G. M. W., & Stoffels, W. W. (2005). Axial segregation in high intensity discharge lamps measured by laser absorption spectroscopy. *Journal of Applied Physics*, 98(7), 073301-1/5. [073301]. <https://doi.org/10.1063/1.2073970>

DOI:

[10.1063/1.2073970](https://doi.org/10.1063/1.2073970)

Document status and date:

Published: 01/01/2005

Document Version:

Publisher's PDF, also known as Version of Record (includes final page, issue and volume numbers)

Please check the document version of this publication:

- A submitted manuscript is the version of the article upon submission and before peer-review. There can be important differences between the submitted version and the official published version of record. People interested in the research are advised to contact the author for the final version of the publication, or visit the DOI to the publisher's website.
- The final author version and the galley proof are versions of the publication after peer review.
- The final published version features the final layout of the paper including the volume, issue and page numbers.

[Link to publication](#)

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal.

If the publication is distributed under the terms of Article 25fa of the Dutch Copyright Act, indicated by the "Taverne" license above, please follow below link for the End User Agreement:

www.tue.nl/taverne

Take down policy

If you believe that this document breaches copyright please contact us at:

openaccess@tue.nl

providing details and we will investigate your claim.

Axial segregation in high intensity discharge lamps measured by laser absorption spectroscopy

A. J. Flikweert,^{a)} T. Nimalasuriya, C. H. J. M. Groothuis, G. M. W. Kroesen, and W. W. Stoffels

Department of Applied Physics, Eindhoven University of Technology, P.O. Box 513, 5600 MB Eindhoven, The Netherlands

(Received 10 March 2005; accepted 22 August 2005; published online 3 October 2005)

High intensity discharge lamps have a high efficiency. These lamps contain rare-earth additives (in our case dysprosium iodide) which radiate very efficiently. A problem is color separation in the lamp because of axial segregation of the rare-earth additives, caused by diffusion and convection. Here two-dimensional atomic dysprosium density profiles are measured by means of laser absorption spectroscopy; the order of magnitude of the density is 10^{22} m^{-3} . The radially resolved atomic density measurements show a hollow density profile. In the outer parts of the lamp molecules dominate, while the center is depleted of dysprosium atoms due to ionization. From the axial profiles the segregation parameter is determined. It is shown that the lamp operates on the right-hand side of the Fischer curve [J. Appl. Phys. **47**, 2954 (1976)], i.e., a larger convection leads to less segregation. © 2005 American Institute of Physics. [DOI: 10.1063/1.2073970]

I. INTRODUCTION

The goal of this research is to gain a better understanding of the metal halide (MH) lamp, which is a high intensity discharge (HID) lamp,¹ with a high efficiency (up to 40%), so that it can be improved. These lamps contain usually mercury as buffer gas and often rare-earth additives which radiate very efficiently in the visible spectrum. Ideally the lamp radiates white light, but when the lamp burns vertically, color separation takes place because of segregation of the rare-earth additives. A picture of the color separation is shown in Fig. 1.

The color separation is caused by a combination of radial and axial segregations; the latter is caused by the combination of convection and diffusion.^{2–6} Fischer⁷ has formulated a simplified theory explaining the segregation based on the diffusion and convection in the lamp. Convection is caused by gravity and in order to understand its influence the lamp has recently been investigated under microgravity conditions so that no convection flows were present. To obtain microgravity, experiments during parabolic flights and at the International Space Station have been performed.

To get more insight in the flow phenomena and the segregation in the lamp, we present absorption measurements of atomic dysprosium. From this a two-dimensional density profile of the rare-earth atoms is obtained. We want to understand the theory about radial and axial segregations (depicted by Fischer) quantitatively by means of a model and experimental verification.

First we briefly introduce the theory of diffusion, convection, and axial segregation in the lamp. Next absorption spectroscopy is discussed and the experimental setup is presented. Finally the results of measurements on a lamp for

two different input powers is given; the density profiles are shown and the segregation parameters are obtained from these profiles.

II. THEORY

The segregation theory on MH lamps has been invented by Fischer.⁷ It will be briefly summarized here for our specific case of a DyI_3 containing lamp (burner height of 20 mm, diameter of 8 mm).

A. Radial segregation

The center of the burner is much hotter ($\sim 5500 \text{ K}$) than the wall ($\sim 1200 \text{ K}$).⁸ Because of this large temperature gradient a multistep process of dissociation of DyI_3 molecules near the center and association of atoms at the wall takes place:⁹

With increasing temperature the equilibrium moves to the right-hand side. Furthermore in the center of the burner ion-

FIG. 1. (Color online) Picture of a HID lamp burner (real size $8 \times 20 \text{ mm}^2$); the color separation is clearly visible.

^{a)}Electronic mail: A.J.Flikweert@tue.nl

FIG. 2. (Color online) Schematic view of the burner in a HID lamp; the diffusion and convection of atoms (A) and molecules (M) are indicated by arrows.

ization of Dy atoms takes place because of the high temperature:¹⁰

The diffusion velocities of atoms, molecules, and ions are different. Due to the different velocities the particles in the hotter part diffuse faster than the particles in the colder part. This results in a hollow profile of the elemental density of dysprosium; this is called radial segregation. Elemental density means that contributions from all molecules, atoms, and ions of a particular element are included. Note that this is in addition to the ideal-gas law $p = nkT$; a higher temperature gives a lower density.

B. Convection and axial segregation

In addition to radial segregation the radial temperature gradient is also related to convection in the lamp. The gas in the hot center moves upward whereas the gas at the wall moves downward. As discussed in Sec. II A, the maximum of the elemental Dy density lies in the part where the gas moves downward. This causes the Dy density to be higher near the bottom than near the top of the burner: axial segregation occurs.^{2,3} A picture of the diffusion and convection flows of the atoms and molecules is given in Fig. 2.

The simple axial segregation model by Fischer results in an exponential decrease of the axial Dy density $n_{\text{Dy}}(z)$ with increasing height in the plasma:⁷

$$n_{\text{Dy}}(z) = n_{\text{Dy},0} \exp(-\lambda z), \quad (3)$$

where the axial segregation is described by the segregation parameter λ and $n_{\text{Dy},0}$ is the atomic dysprosium density at the bottom of the lamp.

As explained, axial segregation is due to the combined effect of radial segregation and axial convection. In the absence of convection, or in the limit of extremely high convection speeds, there is no axial segregation and consequently the segregation parameter λ is zero (no axial color separation). In the intermediate region λ has a maximum. This is depicted by the so-called Fischer curve,⁷ shown in

FIG. 3. The Fischer curve, giving the dependence of the segregation parameter λ [Eq. (3)] on the convection in the lamp.

Fig. 3, which gives the dependence of λ on the amount of convection inside the lamp. The amount of convection increases with the pressure in the lamp (Fischer), the input power,^{4,5} the gravity,¹¹ and radius of the burner.

III. EXPERIMENTAL SETUP

To get insight into axial and radial segregations, the absolute number density of ground-state atomic dysprosium is measured by means of laser absorption spectroscopy.

The lamp that is measured is shown schematically in Fig. 4. It contains 10 mg of mercury as buffer gas, 300 mbar Ar/Kr as starting gas, and 4.2 mg DyI_3 as salt additive. The lamp driver that is used (Philips HID-DynaVision type LA 03 07) delivers a square-wave current to the lamp with a frequency of 125 Hz. The lamp is measured at two different input powers (113.5 and 151 W) to see the dependence of segregation on the input power. The input power is determined by using a power analyzer (Lem Norma 3000).

A diode laser (Sacher TEC 500 645-5, typical line width ≤ 2 MHz or ≤ 3 fm) scans a small wavelength range (0.14 nm) around the absorption wavelength $\lambda = 642.19$ nm [transition from ground state $[\text{Xe}].4f^{10}6s^25I_8$ to excited state $[\text{Xe}].4f^{10}(^5I_8)6s6p(^3P_0)(8,0)_8$] by changing the piezovolt-

FIG. 4. Schematic picture of the HID lamp: (1) outer bulb; (2) burner with height 20 mm and diameter of 8 mm; (3) electrodes, distance between both electrodes ~ 18 mm.

FIG. 5. Schematic overview of the absorption setup to measure the ground-state Dy density in a HID lamp: (1) diode laser; (2) cylindrical lens $f=-12.7$ mm; (3) slit; (4) cylindrical lens $f=+62.9$ mm; (5) lamp; (6) spherical lens $f=+100$ mm; (7) slit; (8) interference filter; (9) diode array.

age of the grating. The line strength of this transition is $S = 6.65 \times 10^{-9} \text{ m}^2 \text{ C}^2$.^{12,13} The line strength is related to the oscillator strength f_{qp} by $S = (3g_q h e^2 \lambda) / (8\pi^2 m_e c) \times f_{qp}$ where g_q is the allowed number of states of the ground level q . The line is pressure broadened with an experimentally determined width of around 40 pm.

A schematic overview of the setup for laser absorption on a HID lamp is given in Fig. 5. The laser beam (beam height ~ 1 mm) passes two cylindrical lenses; in this way the laser spot is transformed to a parallel sheet inside the lamp burner. The width of the slit (no. 3 in the picture) is chosen so that exactly the whole width of the burner is illuminated. The inner and outer bulbs of the lamp act as negative cylindrical lenses. The beam passes the plasma in the burner as is shown in Fig. 6. Also indicated are the laser intensity $I_{\lambda,0}(x)$ in the absence of the plasma and the laser intensity $I_{\lambda,d}(x)$ with the plasma. After the laser beam has passed through the lamp it is converged to a parallel beam by a lens. Next it passes an interference filter and is detected by the diode array, which consists of 32 evenly spaced photodiodes. The detector channel is converted into a lateral position and corrected for nonlinearities. Each detector channel corresponds to a unique lateral position in the lamp burner. The lamp is translated in height in steps of 0.5 mm to measure the density at different axial positions. In this way a two-dimensional mapping (lateral and axial) is obtained.

To obtain the spatially dependent dysprosium density first, for every position, the spectrally resolved relative transmission curve (shown in Fig. 7) is measured by taking the ratio of the transmitted laser intensity with the lamp on (corrected for the lamp emission) and off. In order to obtain the lateral dysprosium density, the logarithm of the transmission curve is fitted assuming a Lorentzian line shape (Fig. 8). The measurement and fit fully coincide; no difference is seen.

FIG. 6. The laser beam $I_{\lambda,0}$ enters the inner bulb as a parallel beam. Inside the plasma with boundary R it is partially absorbed; $I_{\lambda,d}$ is the transmitted laser beam at the lateral position x . The local dysprosium density $n_q(x,y) = n_q(r)$ is indicated; however, laser absorption samples the integrated line of sight $d(x)$ or column density.

FIG. 7. Typical relative transmission curve [lamp on $I_{\lambda,0}(x)$ divided by lamp off $I_{\lambda,d}(x)$] at a certain position x ; the wavelength is relative to the absorption wavelength (642.19 nm).

The area under the Lorentz curve is proportional to the line-of-sight (column) density of the dysprosium:^{11,14}

$$n_{\text{col},q}(x) = \int_{-(1/2)d(x)}^{(1/2)d(x)} n_q(x,y) dy, \quad (4)$$

where $n_q(x,y)$ refers to the local dysprosium density of level q at position (x,y) in the plasma and $d(x) = 2\sqrt{R^2 - x^2}$ corresponds to the line-of-sight boundaries at lateral position x (see Fig. 6). The relation between the area under the Lorentz curve and the column density can be determined using the Lambert-Beer law for absorption:

$$\frac{dI_\nu(s)}{ds} = -\kappa(\nu,s)I_\nu(s), \quad (5)$$

where $I_\nu(s)$ is the spectral intensity of the laser beam (in $\text{W m}^{-2} \text{ sr}^{-1} \text{ Hz}^{-1}$) and $\kappa(\nu,s)$ the absorption coefficient (m^{-1}) at frequency ν at location s . After using the relation $\kappa(\nu,s) = S n_q \phi(\nu,s)$ with $\phi(\nu,s)$ the line shape and integration over the frequency ν one obtains:

$$\begin{aligned} \int_0^\infty \ln\left(\frac{I_{\lambda,d}(x)}{I_{\lambda,0}(x)}\right) d\lambda \\ = -\frac{S\lambda^2}{c} n_{\text{col},q} = -2\frac{S\lambda^2}{c} \int_x^R \frac{n_q(r)}{\sqrt{r^2 - x^2}} r dr. \end{aligned} \quad (6)$$

Note that by this technique the result is independent of the actual line shape.

Finally the measured column density data are converted into a radial density profile.^{8,15,16} In order to minimize errors in the central region we choose to approximate the radial density profile by a polynomial series:

$$n_q(r) = a_0 + \sum_{n=2}^{\infty} a_n r^n \quad \text{for } r \geq 0. \quad (7)$$

The term $a_1 r$ is omitted because of the derivative of the dysprosium density at the axis of the burner should be zero. Using a least-square fitting procedure to the measured data the column values a_n are obtained and the radial profile is constructed.

Using this approach the density is independent of the actual line shape and depends linearly on the accuracy of the line strength S only.

FIG. 8. Logarithm of the relative transmission curve; the minus sign at the right-hand side of Eq. (6) is already included.

IV. RESULTS

A. Lateral and radial profile

The lateral atomic dysprosium column density profile and the reconstructed radial profile 2 mm above the lower electrode of the lamp (151 W) are shown in Fig. 9. For fitting the radial profile, the terms until $n=6$ are used [Eq. (7)].

In Fig. 9(b) we see a hollow profile; this is in agreement with the theory (Sec. II A). Atomic dysprosium is mainly present in a region around the central parts of the lamp (off-axis maximum), where the DyI_3 molecules are fully dissociated. Close to the center the temperature is even higher than at the off-axis maximum, resulting in lower overall densities and a partial ionization of the atomic dysprosium.

Around $r=1$ mm a small minimum is seen; this is an artifact caused by the limited number of lateral data points and the resulting incomplete reconstruction of the radial profile.

The order of magnitude of the dysprosium density (10^{22} m^{-3}) corresponds with the expected values based on the cold spot temperature of DyI_3 of $\sim 1100 \text{ K}$.^{8,11}

B. Two-dimensional profile

The two-dimensional profiles of the dysprosium column density of the lamp at 151 and 113.5 W are given in Fig. 10.

FIG. 9. (a) Lateral dysprosium column density and (b) radial dysprosium density at 151 W; 2 mm above the lower electrode.

FIG. 10. (Color) Two-dimensional profile of atomic dysprosium column density for (a) 151 W and (b) 113.5 W. The axial position of 0 mm is just above the lower electrode.

The curve in Fig. 9(a) corresponds to the horizontal line located at axial position of 2 mm in Fig. 10(a).

The detection limit of the absorption measurement is around $2 \times 10^{18} \text{ m}^{-2}$ as is seen in the top of Fig. 10(b). Near the bottom one sees that the column density gets low towards the wall. This is because of the arc contraction at the electrode. Furthermore the burner is not exactly cylindrical; the bottom area of the burner is somewhat curved (see Fig. 4).

The structure of the two-dimensional dysprosium column density in Fig. 10 is also remarkable. The dysprosium column density right at the center is lower than the dysprosium column density close to the center. When convection (upward in the center; downward near the wall) and diffusion (direction towards the wall) are combined, the flow lines of atomic dysprosium look like Fig. 11, which qualitatively explains the observed structure.

C. Axial segregation

To obtain the axial segregation parameter λ , the measurements shown in Fig. 10 are converted into a radially averaged profile.

In Fig. 12 the atomic dysprosium density is shown as a function of axial position for 151 and 113.5 W. For both curves an exponential function is fitted according to Eq. (3) and the segregation parameters λ are obtained. The fit is not applied to the round dots; here deviation is present because of the electrodes and the not fully developed arc. The radial segregation at 113.5 W is larger ($\lambda=0.28 \pm 0.01 \text{ mm}^{-1}$) than at 151 W ($\lambda=0.20 \pm 0.01 \text{ mm}^{-1}$).

As already mentioned in the theory, the convection speed increases with increasing power. An explanation for the decreasing value of the segregation parameter λ with increas-

FIG. 11. Representative flow lines of atomic dysprosium of what is believed to exist in the burner. The thick lines give a high dysprosium density whereas the thin lines give a low density.

ing power is that we are at the right part of the Fischer curve (Fig. 3); this agrees with previous findings on this lamp (parabolic flights where it is observed that the segregation decreased during a quick changeover to a 1.8g hypergravity situation¹¹).

V. CONCLUSIONS

The radially and axially resolved absolute number density of atomic dysprosium in a HID lamp was measured by means of laser absorption spectroscopy; this has been performed for two different input powers (113.5 and 151 W). The order of magnitude of the atomic dysprosium density is about 10^{22} m^{-3} .

The radially resolved atomic density measurements show that there is a hollow density profile with a maximum in the Dy density between the center and the boundary of the plasma. In the outer parts of the lamp molecules dominate, while the center is depleted due to ionization of dysprosium. Furthermore the overall density decreases towards the center because of the higher temperature.

Due to diffusion and convection there is a strong axial segregation in the lamp. Apart from the electrode regions the average axial dysprosium density follows the theoretically predicted exponential dependence, and corresponding segregation parameters have been found: $\lambda = 0.28 \pm 0.01 \text{ mm}^{-1}$ at 113.5 W and $\lambda = 0.20 \pm 0.01 \text{ mm}^{-1}$ at 151 W. This shows that the lamp is operating at the right-hand side of the Fischer curve (more power means more convection and lower segregation). In the future a more careful analysis of the two-dimensional data will be compared to a numerical model of the lamp.

FIG. 12. Dysprosium density as a function of axial position in the lamp (0 mm is just above the lower electrode). For the radial fit only a_0 [Eq. (7)] is taken into account. The segregation fit [Eq. (3)] is only applied to the square dots. The segregation parameters for two different input powers are (a) 151 W: $n_{Dy,0} = (2.3 \pm 0.1) \times 10^{22} \text{ m}^{-3}$; $\lambda = 0.20 \pm 0.01 \text{ mm}^{-1}$; (b) 113.5 W: $n_{Dy,0} = (7.2 \pm 0.2) \times 10^{21} \text{ m}^{-3}$; $\lambda = 0.28 \pm 0.01 \text{ mm}^{-1}$.

ACKNOWLEDGMENTS

The authors are grateful to J.J.A.M. van der Mullen and M. Haverlag for the discussion about the theory of the lamps, M. van Kemenade for his contribution to developing the measurement method, and Senter-Novem (Project No. EDI 03146) for funding the research.

- ¹G. G. Lister, J. E. Lawler, W. P. Lapatovich, and V. A. Godyak, *Rev. Mod. Phys.* **76**, 541 (2004).
- ²H.-P. Stormberg, *J. Appl. Phys.* **52**, 3233 (1981).
- ³G. L. Rogoff, A. E. Feuersanger, J. P. Drummey, and H. L. Rothwell, Jr., *J. Appl. Phys.* **62**, 4084 (1987).
- ⁴R. J. Zolweg, *J. IES* **5**, 12 (1975).
- ⁵J. T. Dakin and W. Shyy, *J. Electrochem. Soc.* **136**, 1210 (1989).
- ⁶J. T. Dakin, T. H. Rautenberg, Jr., and E. M. Goldfield, *J. Appl. Phys.* **66**, 4074 (1989).
- ⁷E. Fischer, *J. Appl. Phys.* **47**, 2954 (1976).
- ⁸X. Zhu, Ph.D. thesis, Eindhoven University of Technology 2005.
- ⁹M. Yamane and M. Suenaga, *J. Appl. Phys.* **54**, 107 (1982).
- ¹⁰J. J. A. M. van der Mullen, Ph.D. thesis, Eindhoven University of Technology 1986.
- ¹¹M. van Kemenade, Master's thesis, Eindhoven University of Technology 2004.
- ¹²Harvard-Smithsonian Center for Astrophysics, Kurucz Atomic Line Database, <http://cfa-www.harvard.edu/amdata/ampdata/kurucz23/sekur.html>
- ¹³N. V. Gorshkov, V. A. Komarovski, A. L. Osherovich, N. P. Penkin, and R. Khefferlin, *Opt. Spectrosc.* **48**, 362 (1980).
- ¹⁴E. A. H. Timmermans, Ph.D. thesis, Eindhoven University of Technology 1999.
- ¹⁵J. J. Curry, M. Sakai, and J. E. Lawler, *J. Appl. Phys.* **84**, 3066 (1998).
- ¹⁶M. J. Buie, J. T. P. Pender, J. P. Holloway, T. Vincent, P. L. G. Ventzek, and M. L. Brake, *J. Quant. Spectrosc. Radiat. Transf.* **55**, 231 (1996).