16x40 Gb/s over 800km of SSMF using mid-link spectral inversion

Citation for published version (APA):

Jansen, S. L., Spälter, S., Khoe, G. D., Waardt, de, H., Escobar, H. E., Marshall, L., & Sher, M. (2004). 16x40 Gb/s over 800km of SSMF using mid-link spectral inversion. *IEEE Photonics Technology Letters*, 16(7), 1763-1765. <https://doi.org/10.1109/LPT.2004.828546>

DOI:

[10.1109/LPT.2004.828546](https://doi.org/10.1109/LPT.2004.828546)

Document status and date:

Published: 01/01/2004

Document Version:

Publisher's PDF, also known as Version of Record (includes final page, issue and volume numbers)

Please check the document version of this publication:

- A submitted manuscript is the version of the article upon submission and before peer-review. There can be important differences between the submitted version and the official published version of record. People interested in the research are advised to contact the author for the final version of the publication, or visit the DOI to the publisher's website.
- The final author version and the galley proof are versions of the publication after peer review.
- The final published version features the final layout of the paper including the volume, issue and page numbers.

[Link to publication](#)

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal.

If the publication is distributed under the terms of Article 25fa of the Dutch Copyright Act, indicated by the "Taverne" license above, please follow below link for the End User Agreement:

www.tue.nl/taverne

Take down policy

If you believe that this document breaches copyright please contact us at:

openaccess@tue.nl

providing details and we will investigate your claim.

16 × 40 Gb/s Over 800 km of SSMF Using Mid-Link Spectral Inversion

Sander L. Jansen, *Student Member, IEEE*, Stefan Spälter, Giok-Djan Khoe, *Fellow, IEEE*, Huug de Waardt, Hector E. Escobar, Larry Marshall, and Mark Sher

Abstract—We demonstrate the feasibility of a cost-effective 640 Gb/s (16×40 Gb/s) wavelength-division-multiplexed (WDM) transmission system over 800 km of conventional standard single-mode fiber (SSMF) without using in-line dispersion management. Instead for chromatic-dispersion compensation, a Magnesium-oxide-doped periodically poled lithium niobate (MgO:PPLN)-based polarization-diverse subsystem is used to phase conjugate all 16 channels. The transmission line uses all erbium-doped fiber amplifiers and has an amplifier spacing of 100 km. All channels launched were copolarized. To the best of our knowledge, this is the first WDM transmission experiment with a channel data rate of 40 Gb/s using a PPLN as chromatic-dispersion compensator.

Index Terms—Fiber nonlinearity, fiber-optics communications, mid-link spectral inversion (MLSI), optical phase conjugation, optical transmission.

I. INTRODUCTION

IN HIGH bit-rate wavelength-division-multiplexed (WDM) systems using dispersion compensating fiber (DCF) as chromatic-dispersion compensation, the dispersion management has a great impact on the system performance. Many studies have been conducted to maximize system performance by optimizing the dispersion map [1], [2]. Still the optimal dispersion map is dependent on many aspects of the system including the total transmission length, the span length, the number of channels, the channel spacing, the channel data rate, etc.; hence, every link needs its own custom dispersion map.

A more cost-effective solution would be to use mid-link spectral inversion (MLSI). In a system based on MLSI, no in-line dispersion compensation is needed. Instead in the middle of the link, an optical phase conjugator inverts the frequency spectrum and phase of the distorted signals caused by chromatic dispersion. As the signals propagate to the end of the link, the accumulated spectral phase distortions are reverted back to the value at the beginning of the link if perfect symmetry of the link is assumed. The great advantage of using MLSI is that in such a system no custom dispersion map needs to be designed for each specific link; also, different modulation formats (nonre-

Fig. 1. Experimental setup.

turn-to-zero, return-to-zero, differential phase-shift keying, etc.) and different channel data rates (10 Gb/s, 40 Gb/s, etc.) can be used on the same link. Another advantage of MLSI systems is that they are realized without using DCF, which results in a simplified and cost-efficient amplifier design.

In this letter, we show successful transmission of 640 Gb/s (16×40 Gb/s) over 8×100 km SSMF at 100-GHz channel spacing. In [3], five 40-Gb/s channels are transmitted over 105 km of SSMF using highly nonlinear fiber as spectral inverter. All other experiments reported so far at 40-Gb/s channel data rate (or higher) using MLSI were single-channel experiments [4]–[7]. To the best of our knowledge, 640 Gb/s is the highest total data rate reported using a phase conjugator as chromatic-dispersion compensator.

II. EXPERIMENTAL SETUP

Fig. 1 shows the experimental setup of the straight line transmission link. The WDM transmitter consisted of 16 distributed feedback lasers with wavelengths ranging from 1548.5 to 1560.6 nm (100-GHz spacing). The 16 continuous wave channels were multiplexed in an arrayed-waveguide grating multiplexer and modulated at 42.6 Gb/s.

Each channel was generated using a $2^{31} - 1$ pseudorandom bit sequence (PRBS). After modulation, the data was sent into the transmission link, consisting of eight spans of 100 km of SSMF (SMF-28) with each span loss varying between 21 and 24 dB. The noise figure of the in-line erbium-doped fiber amplifiers (EDFAs) was 4.5 dB. No DCF was used in the transmission link for in-line dispersion compensation. Instead, a polarization-diverse phase (PDL < 0.5 dB) conjugator subsystem, utilizing Magnesium-oxide-doped periodically poled lithium niobate (MgO:PPLN), was placed after four spans in the middle of the link. Quasi-phase matching inside the PPLN was realized with a phase matching period of $17.1 \mu\text{m}$ and a temperature

Manuscript received January 21, 2004; revised March 25, 2004. This work was supported by the University of Technology Eindhoven, The Netherlands, by Siemens AG, Munich, Germany, and by Lightbit, Mountain View, CA.

S. L. Jansen, G.-D. Khoe, and H. de Waardt are with the COBRA Institute, Eindhoven University of Technology, Eindhoven 5612 AZ, The Netherlands (e-mail: s.l.jansen@tue.nl).

S. Spälter is with Siemens AG, ICN, Carrier Products, Optical Solutions, D-81359 Munich, Germany (e-mail: stefan.spaelter@siemens.com).

H. E. Escobar, L. Marshall, and M. Sher are with Lightbit, Mountain View, CA 94043 USA (e-mail: hescobar@lightbit.com).

Digital Object Identifier 10.1109/LPT.2004.828546

Fig. 2. (a) Optical spectrum at the output of the optical phase conjugator (spectral resolution of 0.1 nm). (b) Optical spectrum at the end of 800 km (spectral resolution of 0.1 nm).

controller at 90 °C. Inside the PPLN, the incoming data signals (ω_{input}) were mirrored with respect to the pump frequency at 1546.12 nm (ω_{pump}) according to

$$\omega_{\text{output}} = 2\omega_{\text{pump}} - \omega_{\text{input}}. \quad (1)$$

Hence, the array of wavelengths of the data signals were converted from 1548.5–1560.6 to 1543.7–1531.9 nm, as can be seen in the optical spectrum depicted in Fig. 2(a). For the PPLN itself, no optical signal-to-noise ratio (OSNR) degradation was measured. One can see this in Fig. 2(a), since the OSNR for the input and the output data signals is equal. The noise output of the phase conjugator unit, with no input signals, was measured at less than -65 dBm per 0.1-nm bandwidth. For further transmission, the input channels were filtered out. The net loss of the phase conjugator plus filters was 23 dB which equals the loss of one SSMF span. However, this loss does not represent a fundamental limitation of the PPLN's conversion efficiency and can be further reduced. Since in this setup no in-line DCF was needed, one-stage amplifiers were used for in-line amplification. Hence, instead of one preamplifier per span for the PPLN, only one extra amplifier is required for the whole link. At the receiver, the chromatic dispersion was optimized for each channel using a variable dispersion compensator. Accordingly, the signal

was properly amplified, filtered with a 0.8-nm (full-width at half-maximum) tunable bandpass filter, and detected using a bit-error-rate (BER) detector.

III. RESULTS

Fig. 2(a) depicts the optical spectrum of all channels after they are spectrally inverted by the PPLN. On the right part of the plot, the 16 input channels can be seen (1548.5–1560.6 nm), and the left part shows the 16 output channels (1531.9–1543.7 nm). In the middle (at 1546.12 nm), the residual of the suppressed pump can be seen (for illustration purposes). Fig. 2(b) depicts the spectrum of the WDM signals at the receiver. The measured OSNR at the receiver was larger than 23.5 dB for all 16 channels, which is in good agreement with what would be expected from launch power, loss, and amplifier noise considerations.

In the optical spectrum, after transmission Fig. 2(b), a ripple is clearly visible. This ripple, created by unequal gain of the EDFAs in the system, introduced a nonuniform channel performance. In DCF-based transmission systems, channel equalization is classically done by designing the two-stage amplifiers to result in a flat gain spectrum. Since this MLSI system is built up with single-stage amplifiers only and without a channel equalizer, no active channel equalization was conducted. The ripple after transmission was reduced to 7 dB by lowering the output power of the boosters. Instead of the optimal input power of 4 dBm we measured in single-channel performance, 3 dBm per channel (15 dBm total power) was the setting with the most equal channel performance.

The optimal channel power in this experiment is higher than the optimal channel power used for the 10-Gb/s/channel dense WDM experiment (1 dBm) we reported earlier [8]. Even though the spectral efficiency of both experiments is equal (0.4 b/s/Hz), the 10-Gb/s experiment was cross-phase modulation (XPM)-limited due to the narrow channel spacing of 25 GHz. In the case of the 40-Gb/s/channel transmission, the XPM effect is not the limiting factor. Instead the performance is OSNR-limited, since the BER performance after transmission [Fig. 3(b)] is very similar to the BER (3.5×10^{-6}) measured in a back-to-back configuration at the same OSNR of 23.5 dB.

In order to see the effect of precompensation, the dispersion tolerance of Channel 8 (1537.4 nm after spectral inversion) was assessed for the following precompensations -640 , -510 , -340 , -170 , 40 , and 220 ps/nm. Please note that for this measurement, the PRBS length used was $2^7 - 1$. Fig. 3(a) shows the contour plot of the BER as a function of the precompensation and postcompensation. From Fig. 3, it can be seen that the BER performance is not seriously affected as long as the precompensation is smaller than 220 ps/nm and larger than -640 ps/nm. The best result, e.g., the lowest BER, was obtained at a precompensation of -510 ps/nm. Fig. 3(b) depicts the BER of all 16 channels before forward-error correction (FEC) [PRBS $2^{31} - 1$]. The precompensation in this configuration was -510 ps/nm. The BER of the best and the worst channel were 2.1×10^{-6} and 7.1×10^{-6} , respectively. These BER rates are more than two decades below the FEC threshold of the concatenated code RS(255, 247) + RS(247, 239) with a 7% redundancy, for which a BER of 2.3×10^{-3} corresponds to error-free transmission after

Fig. 3. (a) Measured contour plot of the BER as a function of the precompensation and postcompensation. (b) BER performance for all 16 WDM channels.

FEC (BER after FEC $< 10^{-13}$) [9]. For all measured channels, the post dispersion was optimized. The inlay of Fig. 3(b) depicts the eye pattern obtained for Channel 8 (1537.4 nm after transmission).

The PPLN inverts the chromatic dispersion of the data signal. What it does not compensate for is the slope of the fiber. For a 40-Gb/s channel, the slope has almost no influence on the performance since the optical spectrum is small (>0.8 nm), however, due to the slope, the effective accumulated dispersion before the postcompensation unit varies for different channels, which results in different optimal postcompensations. Based on a typical dispersion slope of 0.057 ps/nm for SSMF, the com-

puted difference in optimal dispersion between the first and the 16th channel is 551 ps/nm for the 800-km link. This is in excellent agreement with the measured value of 560 ps/nm.

In this experiment, a dispersion compensator was used to maximize the BER performance per channel. Alternatively, a slope compensator could be used instead of the channel dispersion compensator at any point of the transmission link. In a similar but different experiment at 10 Gb/s, the PPLN optical phase conjugator with a slope compensator adequately and effectively compensated for chromatic dispersion and dispersion slope. The main advantage of the slope compensator is that it compensates the slope for all channels at once.

IV. CONCLUSION

Using a polarization-diverse MgO : PPLN optical phase conjugator, we have shown successful transmission of 16 40-Gb/s channels over 800 km of SSMF. By using this technique, we eliminated the need for in-line dispersion compensation in the transmission link.

REFERENCES

- [1] G. Mohs *et al.*, "Optimized inline dispersion compensation for self-phase modulation limited transmission," in *Proc. OECC/OOC*, 2001, pp. 262–262.
- [2] G. Lehmann and E. Meissner, "Dispersion management for the transmission of mixed data rates of 40 Gb/s and 10 Gb/s in the same fiber," in *Proc. Asian Pacific Optical and Wireless Communication Conf.*, vol. 4906, 2002, pp. 253–260.
- [3] S. Watanabe *et al.*, "Simultaneous wavelength conversion and optical phase conjugation of 200 Gb/s (5×40 Gb/s) WDM signal using a highly nonlinear fiber four-wave mixer," in *Proc. Eur. Conf. Optical Communication*, Sept. 1997, Postdeadline, pp. 1–4.
- [4] I. Brener *et al.*, "160 Gbit/s wavelength shifting and phase conjugation using periodically poled LiNbO₃ waveguide parametric converter," *Electron. Lett.*, vol. 36, pp. 1788–1790, Oct. 2000.
- [5] J. Inoue, H. Sotobayashi, W. Chujo, and H. Kawaguchi, "80 Gbit/s OTDM signal transmission over 208 km standard fiber using midspan optical phase conjugation based on four-wave mixing in semiconductor optical amplifiers," *Electron. Lett.*, vol. 38, pp. 819–821, July 2002.
- [6] U. Feiste *et al.*, "40 Gbit/s transmission over 434 km standard-fiber using polarization independent mid-span spectral inversion," in *Proc. Eur. Conf. Optical Communication*, vol. 3, Sept. 1998, pp. 113–117.
- [7] D. D. Marcenac *et al.*, "40 Gbit/s transmission over 406 km of NDSF using mid-span spectral inversion by four-wave-mixing in a 2 mm long semiconductor optical amplifier," *Electron. Lett.*, vol. 33, pp. 879–880, May 1997.
- [8] S. L. Jansen *et al.*, "10 Gbit/s, 25 GHz spaced transmission over 800 km without using dispersion compensation modules," in *Proc. Optical Fiber Conf.*, Feb. 1997, Paper ThT1.
- [9] T. Tsuritani *et al.*, "70 GHz-spaced 40 × 42.7 Gbit/s transmission over 8700 km using CS-RZ DPSK signal, all-Raman repeaters and symmetrically dispersion managed fiber span," in *Proc. Optical Fiber Conf.*, Mar. 2003, Paper PD23-1.