On the equivalence covering number of splitgraphs

Citation for published version (APA):

Blokhuis, A., & Kloks, A. J. J. (1994). *On the equivalence covering number of splitgraphs*. (Computing science reports; Vol. 9439). Technische Universiteit Eindhoven.

Document status and date:

Published: 01/01/1994

Document Version:

Publisher's PDF, also known as Version of Record (includes final page, issue and volume numbers)

Please check the document version of this publication:

- A submitted manuscript is the version of the article upon submission and before peer-review. There can be important differences between the submitted version and the official published version of record. People interested in the research are advised to contact the author for the final version of the publication, or visit the DOI to the publisher's website.
- The final author version and the galley proof are versions of the publication after peer review.
- The final published version features the final layout of the paper including the volume, issue and page numbers.

[Link to publication](#)

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal.

If the publication is distributed under the terms of Article 25fa of the Dutch Copyright Act, indicated by the "Taverne" license above, please follow below link for the End User Agreement:

www.tue.nl/taverne

Take down policy

If you believe that this document breaches copyright please contact us at:

openaccess@tue.nl

providing details and we will investigate your claim.

Eindhoven University of Technology
Department of Mathematics and Computing Science

On the equivalence covering number of splitgraphs

by

A. Blokhuis and T. Kloks

94/39

ISSN 0926-4515

All rights reserved
editors: prof.dr. J.C.M. Baeten
prof.dr. M. Rem

Computing Science Report 94/39
Eindhoven, September 1994

On the equivalence covering number of splitgraphs

A. Blokhuis* and T. Kloks†

Department of Mathematics and Computing Science

Eindhoven University of Technology

P.O.Box 513, 5600 MB Eindhoven, The Netherlands

Keywords: Graph algorithms, equivalence covering, splitgraphs.

Abstract

An equivalence graph is a disjoint union of cliques. For a graph G let $eq(G)$ be the minimum number of equivalence subgraphs of G needed to cover all edges of G . We call $eq(G)$ the equivalence covering number of G . We show that the equivalence covering number for splitgraphs can be approximated within an additive constant 1. We also show that obtaining the exact value of the equivalence number of a splitgraph is an NP-hard problem. Using a similar method we also show that the computation of the equivalence number remains NP-complete for graphs with maximum degree 6 and with maximum clique number 4.

1 Introduction

Definition 1 *An equivalence graph is a vertex disjoint union of cliques. An equivalence covering of a graph G is a family of equivalence subgraphs of G such that every edge of G is an edge of at least one member of the family. The equivalence covering number of G , denoted by $eq(G)$, is the minimum cardinality of all equivalence coverings of G .*

The equivalence covering number was studied first in [2]. Interesting bounds for the equivalence covering number in terms of maximal degree of the complement were obtained in [1]. In this note we mainly consider the computation of the equivalence covering number of splitgraphs. We first show an approximation within an additive constant 1. Then we show that obtaining the exact value is an NP-hard problem.

Definition 2 *A graph $G = (V, E)$ is a split graph, if there is a partition $V = S + K$ of its vertex set into a stable set S and a clique K .*

There is no restriction on edges between vertices of S and vertices of K . Notice that in general the partition into S and K need not be unique. Splitgraphs are exactly those graphs which, together with their complements, are chordal. For more general information on splitgraphs we refer to [4].

2 Approximation

In this section we show that the equivalence covering number of a splitgraph can be approximated within an additive constant 1. Consider a partition $V = S + K$ of the vertex set into an independent set S and a clique K . For a vertex x in K let $\delta(x)$ be the number of neighbors of x in S . Let $\Delta = \max\{\delta(x) \mid x \in K\}$.

Lemma 1 $eq(G) \geq \Delta$.

*Email: aartb@win.tue.nl

†Email: ton@win.tue.nl

Proof. Consider a vertex $x \in K$ with $\delta(x) = \Delta$ and its neighbors in S . This is a $K_{1,\Delta}$ induced subgraph of G . This induced subgraph has equivalence covering number Δ , since each equivalence graph in the covering can have only one edge. This proves the lemma. $\square$

Lemma 2 $eq(G) \leq \Delta + 1$.

Proof. Let $y_1, \dots, y_t$ be the vertices of S . For each vertex x in K consider an arbitrary ordering of its neighbors in S . For $i = 1, \dots, \Delta$ define the equivalence graph G_i as follows. G_i is the disjoint union of cliques $W_{i,j} = \{y_j\} \cup \{x \in K \mid \text{the } i\text{th neighbor of } x \text{ is } y_j\}$, for $j = 1, \dots, t$. It is easy to check that the cliques $W_{i,j}$ for $j = 1, \dots, t$ are all disjoint. We define one more equivalence graph $G_{\Delta+1}$ consisting of the clique K . Obviously, this gives an equivalence covering with $\Delta + 1$ equivalence graphs. $\square$

The approximation given in Lemma 2 can be computed in linear time. This proves the following theorem.

Theorem 1 *There exists a linear time algorithm to compute an equivalence covering of a splitgraph G with at most $eq(G) + 1$ equivalence graphs.*

Remark 1 *Notice that, in case the splitgraph is a threshold graph (see, e.g., [4]), its equivalence number can easily be computed exactly.*

3 NP-completeness

We use a reduction from EDGE-COLORING.

The *chromatic index* of a graph G , denoted by $\chi'(G)$, is the number of colors required to color the edges of the graph in such a way that no two adjacent edges have the same color. By Vizing's theorem (see, e.g., [3]) the chromatic index is either d or $d + 1$, where d is the maximum vertex degree.

Notice that, in general, the chromatic index is an upperbound for the equivalence covering number. Also, these parameters coincide for triangle-free graphs. It follows that, for bipartite graphs, the equivalence covering number equals the maximum degree. Unfortunately, for splitgraphs the bound is not of much use, which is illustrated by a clique.

It is by now well-known that it is NP-complete to determine the chromatic index of an arbitrary graph [5, 6]. Holyer [5] obtained the following result.

Theorem 2 *It is NP-complete to determine whether the chromatic index of a cubic graph is 3 or 4.*

Consider a cubic graph G and construct a graph H as follows. For each edge e of G introduce a new vertex x_e and make this adjacent to the two endvertices of e . We call x_e the *special vertex* at e .

Lemma 3 $\chi'(G) = 3 \Leftrightarrow eq(H) = 3$.

Proof. First assume $\chi'(G) = 3$. Notice that $eq(H) \geq 3$ since H has an induced $K_{1,3}$ subgraph. (If p is a vertex of G incident with edges e, f and g in G , then $\{p, x_e, x_f, x_g\}$ induces a $K_{1,3}$ in H .) Consider an edge coloring of G with three colors. For each color class define an equivalence graph as follows. For each edge in that color class, the triangle consisting of the edge and the special vertex at that edge is a clique of the equivalence graph. It is easy to check that this defines an equivalence covering with three equivalence graphs.

Now assume H has an equivalence covering with three equivalence graphs H_1, H_2 and H_3 . We claim that no triangle of G is contained in a clique of one of the equivalence graphs. Assume, by way of contradiction, that $\{a, b, c\}$ is a triangle of G which is contained in a clique of H_1 . Vertex a is adjacent to three special vertices, say x_1, x_2 and x_3 . Then each of the edges (a, x_i) is contained in a clique of an equivalence graph, and no two are in a clique of the same equivalence graph. Without loss

of generality we may assume that (a, x_i) is contained in a clique of H_i . But then H_1 cannot contain the triangle $\{a, b, c\}$ since x_1 has degree two and hence the clique containing a and x_1 can have at most two vertices of G .

We can color the edges of G as follows. If the edge e is contained in a clique of H_i then we give it color i . (If e is contained in cliques of more than one equivalence graph, we can choose one arbitrarily). By the remark above this gives a correct edge-coloring with three colors. $\square$

Corollary 1 *It is NP-complete to determine whether the equivalence covering number of a graph with maximum degree ≤ 6 and without induced K_4 is 3 or 4.*

Given a cubic graph G we construct a split-graph G^* as follows. The vertex set of G^* is split into a clique K and an independent set S . The vertices of K are the vertices of G . For each edge e of G introduce two new vertices $x_{e,1}$ and $x_{e,2}$ which are both made adjacent to the endvertices of e . For each nonedge f of G , we introduce *one* new vertex y_f which is made adjacent to the endvertices of f . We again call the new vertices, which are the vertices of S , special vertices.

Lemma 4 $\chi'(G) = 3 \Leftrightarrow eq(G^*) = n + 2$, where n is the number of vertices of G .

Proof. The proof goes along the same lines as the proof of Lemma 3. Assume G can be edge-colored with three colors. Notice that $eq(G^*) \geq n + 2$ since $K_{1,n+2}$ is an induced subgraph. Since G is cubic, n is even. We can construct an equivalence covering for G^* as follows. First, consider an edge-coloring of K with $n - 1$ colors (see [3]). For each color class, define an equivalence graph as follows. For each edge in K in that color class, add one special vertex at that edge and let that triangle be a clique of the equivalence graph.

Next consider an edge-coloring of G with three colors. For each color class define an

equivalence graph as follows. For each edge in that color class add the other special vertex and let that triangle be a clique of the equivalence graph.

Clearly, this defines an equivalence covering of G^* with $n + 2$ equivalence graphs.

Assume that G^* has an equivalence covering with $n + 2$ equivalence graphs. Consider a vertex $a \in K$. This vertex a is adjacent to $n + 2$ special vertices, and each of the edges between a and a special vertex defines a unique equivalence graph. It follows that no triangle of G can be contained in a clique of an equivalence graph. We thus obtain a correct edge-coloring of G in the same manner as in the proof of Lemma 3. $\square$

Corollary 2 *It is NP-complete to determine whether the equivalence covering number of a splitgraph, in which every vertex of the independent set has degree two, is Δ or $\Delta + 1$, where $\Delta = \max\{\delta(x) \mid x \in K\}$ for a given partition of the vertex set into a clique K and an independent set S .*

4 Concluding remarks

In this note we considered the equivalence covering number for splitgraphs. Related problems are the clique covering number, and the clique partition number. The clique covering number is the minimum number of cliques which cover all the edges of the graph. It was shown in [8] that the clique covering number can be computed in linear time for chordal graphs. The clique partition number is the minimum number of cliques such that every edge is contained in *exactly* one clique. Determining the clique partition number is NP-hard for chordal graphs [9]. It would be interesting to determine the complexity of the computation of the clique partition number for split graphs. It should be remarked however that it is unlikely that a polynomial time algorithm exists, due to the following [10, 7]. Consider the following splitgraph G . Take a

clique with $m^2+m+1-r$ vertices and an independent set with r vertices. Make every vertex of the independent set adjacent to every vertex of the clique. (G is sometimes denoted as $K_{m^2+m+1} \setminus K_r$.) If $2 < r < m^2 + m + 1$ then the clique partition number of G is at least $m^2 + m$ with equality holding if and only if a projective plane of order m exists and $r = m + 1$.

number problem, *Congressus Num.* **66**, (1988), pp. 157–164.

- [10] Pullman, N. J., Clique coverings of graphs – A survey, *Proceedings of the Xth Australian Conference on Combinatorial Mathematics*, Adelaide 1982.

References

- [1] Alon, N., Covering graphs by the minimum number of equivalence relations, *Combinatorica* **6**, (1986), pp. 201–206.
- [2] Duchet, P., *Représentations, noyaux en théorie des graphes et hypergraphes*, Thèse de doctoral d'état, Université Paris VI (1979).
- [3] Fiorini, S. and R. J. Wilson, *Edge-colourings of Graphs*, Pitman, London, 1977.
- [4] Golumbic, M. C., *Algorithmic graph theory and perfect graphs*, Academic Press, New York, 1980.
- [5] Holyer, I., The NP-completeness of edge-coloring, *SIAM J. Comput.* **10**, 1981, pp. 718–720.
- [6] Johnson, D. S., The NP-completeness column: an ongoing guide. *J. Algorithms* **6**, (1985), pp. 434–451.
- [7] Klotz, W., Clique covers and coloring problems of graphs, *Journal of Combinatorial Theory Series B* **46**, (1989), pp. 338–345.
- [8] Ma, S., W. D. Wallis and J. Wu, Clique covering of chordal graphs, *Utilitas Mathematica* **36**, (1989), pp. 151–152.
- [9] Ma, S., W. D. Wallis and J. Wu, The complexity of the clique partition

In this series appeared:

91/01	D. Alstein	Dynamic Reconfiguration in Distributed Hard Real-Time Systems, p. 14.
91/02	R.P. Nederpelt
H.C.M. de Swart	Implication. A survey of the different logical analyses "if...,then...", p. 26.
91/03	J.P. Katoen
L.A.M. Schoenmakers	Parallel Programs for the Recognition of <i>P</i> -invariant Segments, p. 16.
91/04	E. v.d. Sluis
A.F. v.d. Stappen	Performance Analysis of VLSI Programs, p. 31.
91/05	D. de Reus	An Implementation Model for GOOD, p. 18.
91/06	K.M. van Hee	SPECIFICATIEMETHODEN, een overzicht, p. 20.
91/07	E.Poll	CPO-models for second order lambda calculus with recursive types and subtyping, p. 49.
91/08	H. Schepers	Terminology and Paradigms for Fault Tolerance, p. 25.
91/09	W.M.P.v.d.Aalst	Interval Timed Petri Nets and their analysis, p.53.
91/10	R.C.Backhouse
P.J. de Bruin
P. Hoogendijk
G. Malcolm
E. Voermans
J. v.d. Woude	POLYNOMIAL RELATORS, p. 52.
91/11	R.C. Backhouse
P.J. de Bruin
G.Malcolm
E.Voermans
J. van der Woude	Relational Catamorphism, p. 31.
91/12	E. van der Sluis	A parallel local search algorithm for the travelling salesman problem, p. 12.
91/13	F. Rietman	A note on Extensionality, p. 21.
91/14	P. Lemmens	The PDB Hypermedia Package. Why and how it was built, p. 63.
91/15	A.T.M. Aerts
K.M. van Hee	Eldorado: Architecture of a Functional Database Management System, p. 19.
91/16	A.J.J.M. Marcelis	An example of proving attribute grammars correct: the representation of arithmetical expressions by DAGs, p. 25.

91/17	A.T.M. Aerts P.M.E. de Bra K.M. van Hee	Transforming Functional Database Schemes to Relational Representations, p. 21.
91/18	Rik van Geldrop	Transformational Query Solving, p. 35.
91/19	Erik Poll	Some categorical properties for a model for second order lambda calculus with subtyping, p. 21.
91/20	A.E. Eiben R.V. Schuwer	Knowledge Base Systems, a Formal Model, p. 21.
91/21	J. Coenen W.-P. de Roever J.Zwiers	Assertional Data Reification Proofs: Survey and Perspective, p. 18.
91/22	G. Wolf	Schedule Management: an Object Oriented Approach, p. 26.
91/23	K.M. van Hee L.J. Somers M. Voorhoeve	Z and high level Petri nets, p. 16.
91/24	A.T.M. Aerts D. de Reus	Formal semantics for BRM with examples, p. 25.
91/25	P. Zhou J. Hooman R. Kuiper	A compositional proof system for real-time systems based on explicit clock temporal logic: soundness and completeness, p. 52.
91/26	P. de Bra G.J. Houben J. Paredaens	The GOOD based hypertext reference model, p. 12.
91/27	F. de Boer C. Palamidessi	Embedding as a tool for language comparison: On the CSP hierarchy, p. 17.
91/28	F. de Boer	A compositional proof system for dynamic process creation, p. 24.
91/29	H. Ten Eikelder R. van Geldrop	Correctness of Acceptor Schemes for Regular Languages, p. 31.
91/30	J.C.M. Baeten F.W. Vaandrager	An Algebra for Process Creation, p. 29.
91/31	H. ten Eikelder	Some algorithms to decide the equivalence of recursive types, p. 26.
91/32	P. Struik	Techniques for designing efficient parallel programs, p. 14.
91/33	W. v.d. Aalst	The modelling and analysis of queueing systems with QNM-ExSpect, p. 23.
91/34	J. Coenen	Specifying fault tolerant programs in deontic logic, p. 15.

91/35	F.S. de Boer J.W. Klop C. Palamidessi	Asynchronous communication in process algebra, p. 20.
92/01	J. Coenen J. Zwiers W.-P. de Roever	A note on compositional refinement, p. 27.
92/02	J. Coenen J. Hooman	A compositional semantics for fault tolerant real-time systems, p. 18.
92/03	J.C.M. Baeten J.A. Bergstra	Real space process algebra, p. 42.
92/04	J.P.H.W.v.d.Eijnde	Program derivation in acyclic graphs and related problems, p. 90.
92/05	J.P.H.W.v.d.Eijnde	Conservative fixpoint functions on a graph, p. 25.
92/06	J.C.M. Baeten J.A. Bergstra	Discrete time process algebra, p.45.
92/07	R.P. Nederpelt	The fine-structure of lambda calculus, p. 110.
92/08	R.P. Nederpelt F. Kamareddine	On stepwise explicit substitution, p. 30.
92/09	R.C. Backhouse	Calculating the Warshall/Floyd path algorithm, p. 14.
92/10	P.M.P. Rambags	Composition and decomposition in a CPN model, p. 55.
92/11	R.C. Backhouse J.S.C.P.v.d.Woude	Demonic operators and monotype factors, p. 29.
92/12	F. Kamareddine	Set theory and nominalisation, Part I, p.26.
92/13	F. Kamareddine	Set theory and nominalisation, Part II, p.22.
92/14	J.C.M. Baeten	The total order assumption, p. 10.
92/15	F. Kamareddine	A system at the cross-roads of functional and logic programming, p.36.
92/16	R.R. Seljée	Integrity checking in deductive databases; an exposition, p.32.
92/17	W.M.P. van der Aalst	Interval timed coloured Petri nets and their analysis, p. 20.
92/18	R.Nederpelt F. Kamareddine	A unified approach to Type Theory through a refined lambda-calculus, p. 30.
92/19	J.C.M.Baeten J.A.Bergstra S.A.Smolka	Axiomatizing Probabilistic Processes: ACP with Generative Probabilities, p. 36.
92/20	F.Kamareddine	Are Types for Natural Language? P. 32.

92/21	F.Kamareddine	Non well-foundedness and type freeness can unify the interpretation of functional application, p. 16.
92/22	R. Nederpelt F.Kamareddine	A useful lambda notation, p. 17.
92/23	F.Kamareddine E.Klein	Nominalization, Predication and Type Containment, p. 40.
92/24	M.Codish D.Dams Eyal Yardeni	Bottom-up Abstract Interpretation of Logic Programs, p. 33.
92/25	E.Poll	A Programming Logic for F ω , p. 15.
92/26	T.H.W.Beelen W.J.J.Stut P.A.C.Verkoulen	A modelling method using MOVIE and SimCon/ExSpect, p. 15.
92/27	B. Watson G. Zwaan	A taxonomy of keyword pattern matching algorithms, p. 50.
93/01	R. van Geldrop	Deriving the Aho-Corasick algorithms: a case study into the synergy of programming methods, p. 36.
93/02	T. Verhoeff	A continuous version of the Prisoner's Dilemma, p. 17
93/03	T. Verhoeff	Quicksort for linked lists, p. 8.
93/04	E.H.L. Aarts J.H.M. Korst P.J. Zwietering	Deterministic and randomized local search, p. 78.
93/05	J.C.M. Bacten C. Verhoef	A congruence theorem for structured operational semantics with predicates, p. 18.
93/06	J.P. Veltkamp	On the unavoidability of metastable behaviour, p. 29
93/07	P.D. Moerland	Exercises in Multiprogramming, p. 97
93/08	J. Verhoosel	A Formal Deterministic Scheduling Model for Hard Real-Time Executions in DEDOS, p. 32.
93/09	K.M. van Hee	Systems Engineering: a Formal Approach Part I: System Concepts, p. 72.
93/10	K.M. van Hee	Systems Engineering: a Formal Approach Part II: Frameworks, p. 44.
93/11	K.M. van Hee	Systems Engineering: a Formal Approach Part III: Modeling Methods, p. 101.
93/12	K.M. van Hee	Systems Engineering: a Formal Approach Part IV: Analysis Methods, p. 63.
93/13	K.M. van Hee	Systems Engineering: a Formal Approach

93/14	J.C.M. Baeten J.A. Bergstra	Part V: Specification Language, p. 89. On Sequential Composition, Action Prefixes and Process Prefix, p. 21.
93/15	J.C.M. Baeten J.A. Bergstra R.N. Bol	A Real-Time Process Logic, p. 31.
93/16	H. Schepers J. Hooman	A Trace-Based Compositional Proof Theory for Fault Tolerant Distributed Systems, p. 27
93/17	D. Alstein P. van der Stok	Hard Real-Time Reliable Multicast in the DEDOS system, p. 19.
93/18	C. Verhoef	A congruence theorem for structured operational semantics with predicates and negative premises, p. 22.
93/19	G-J. Houben	The Design of an Online Help Facility for ExSpect, p.21.
93/20	F.S. de Boer	A Process Algebra of Concurrent Constraint Program- ming, p. 15.
93/21	M. Codish D. Dams G. Filé M. Bruynooghe	Freeness Analysis for Logic Programs - And Correct- ness?, p. 24.
93/22	E. Poll	A Typechecker for Bijective Pure Type Systems, p. 28.
93/23	E. de Kogel	Relational Algebra and Equational Proofs, p. 23.
93/24	E. Poll and Paula Severi	Pure Type Systems with Definitions, p. 38.
93/25	H. Schepers and R. Gerth	A Compositional Proof Theory for Fault Tolerant Real- Time Distributed Systems, p. 31.
93/26	W.M.P. van der Aalst	Multi-dimensional Petri nets, p. 25.
93/27	T. Kloks and D. Kratsch	Finding all minimal separators of a graph, p. 11.
93/28	F. Kamareddine and R. Nederpelt	A Semantics for a fine λ -calculus with de Bruijn indices, p. 49.
93/29	R. Post and P. De Bra	GOLD, a Graph Oriented Language for Databases, p. 42.
93/30	J. Deogun T. Kloks D. Kratsch H. Müller	On Vertex Ranking for Permutation and Other Graphs, p. 11.
93/31	W. Körver	Derivation of delay insensitive and speed independent CMOS circuits, using directed commands and production rule sets, p. 40.
93/32	H. ten Eikelder and H. van Geldrop	On the Correctness of some Algorithms to generate Finite Automata for Regular Expressions, p. 17.

- 93/33 L. Loyens and J. Moonen ILIAS, a sequential language for parallel matrix computations, p. 20.
- 93/34 J.C.M. Baeten and J.A. Bergstra Real Time Process Algebra with Infinitesimals, p.39.
- 93/35 W. Ferrer and P. Severi Abstract Reduction and Topology, p. 28.
- 93/36 J.C.M. Baeten and J.A. Bergstra Non Interleaving Process Algebra, p. 17.
- 93/37 J. Brunekreef
J-P. Katoen
R. Koymans
S. Mauw Design and Analysis of Dynamic Leader Election Protocols in Broadcast Networks, p. 73.
- 93/38 C. Verhoef A general conservative extension theorem in process algebra, p. 17.
- 93/39 W.P.M. Nuijten
E.H.L. Aarts
D.A.A. van Erp
Taalman Kip
K.M. van Hee Job Shop Scheduling by Constraint Satisfaction, p. 22.
- 93/40 P.D.V. van der Stok
M.M.M.P.J. Claessen
D. Alstein A Hierarchical Membership Protocol for Synchronous Distributed Systems, p. 43.
- 93/41 A. Bijlsma Temporal operators viewed as predicate transformers, p. 11.
- 93/42 P.M.P. Rambags Automatic Verification of Regular Protocols in P/T Nets, p. 23.
- 93/43 B.W. Watson A taxonomy of finite automata construction algorithms, p. 87.
- 93/44 B.W. Watson A taxonomy of finite automata minimization algorithms, p. 23.
- 93/45 E.J. Luit
J.M.M. Martin A precise clock synchronization protocol,p.
- 93/46 T. Kloks
D. Kratsch
J. Spinrad Treewidth and Patwidth of Cocomparability graphs of Bounded Dimension, p. 14.
- 93/47 W. v.d. Aalst
P. De Bra
G.J. Houben
Y. Kornatzky Browsing Semantics in the "Tower" Model, p. 19.
- 93/48 R. Gerth Verifying Sequentially Consistent Memory using Interface Refinement, p. 20.

94/01	P. America M. van der Kammen R.P. Nederpelt O.S. van Roosmalen H.C.M. de Swart	The object-oriented paradigm, p. 28.
94/02	F. Kamareddine R.P. Nederpelt	Canonical typing and Π -conversion, p. 51.
94/03	L.B. Hartman K.M. van Hee	Application of Markov Decision Processes to Search Problems, p. 21.
94/04	J.C.M. Baeten J.A. Bergstra	Graph Isomorphism Models for Non Interleaving Process Algebra, p. 18.
94/05	P. Zhou J. Hooman	Formal Specification and Compositional Verification of an Atomic Broadcast Protocol, p. 22.
94/06	T. Basten T. Kunz J. Black M. Coffin D. Taylor	Time and the Order of Abstract Events in Distributed Computations, p. 29.
94/07	K.R. Apt R. Bol	Logic Programming and Negation: A Survey, p. 62.
94/08	O.S. van Roosmalen	A Hierarchical Diagrammatic Representation of Class Structure, p. 22.
94/09	J.C.M. Baeten J.A. Bergstra	Process Algebra with Partial Choice, p. 16.
94/10	T. Verhoeff	The testing Paradigm Applied to Network Structure. p. 31.
94/11	J. Peleska C. Huizing C. Petersohn	A Comparison of Ward & Mellor's Transformation Schema with State- & Activitycharts, p. 30.
94/12	T. Klocks D. Kratsch H. Müller	Dominoes, p. 14.
94/13	R. Seljée	A New Method for Integrity Constraint checking in Deductive Databases, p. 34.
94/14	W. Peremans	Ups and Downs of Type Theory, p. 9.
94/15	R.J.M. Vaessens E.H.L. Aarts J.K. Lenstra	Job Shop Scheduling by Local Search, p. 21.
94/16	R.C. Backhouse H. Doombos	Mathematical Induction Made Computational, p. 36.
94/17	S. Mauw M.A. Reniers	An Algebraic Semantics of Basic Message Sequence Charts, p. 9.

94/18	F. Kamareddine R. Nederpelt	Refining Reduction in the Lambda Calculus, p. 15.
94/19	B.W. Watson	The performance of single-keyword and multiple-keyword pattern matching algorithms, p. 46.
94/20	R. Bloo F. Kamareddine R. Nederpelt	Beyond β -Reduction in Church's $\lambda \rightarrow$, p. 22.
94/21	B.W. Watson	An introduction to the Fire engine: A C++ toolkit for Finite automata and Regular Expressions.
94/22	B.W. Watson	The design and implementation of the FIRE engine: A C++ toolkit for Finite automata and regular Expressions.
94/23	S. Mauw and M.A. Reniers	An algebraic semantics of Message Sequence Charts, p. 43.
94/24	D. Dams O. Grumberg R. Gerth	Abstract Interpretation of Reactive Systems: Abstractions Preserving $\forall\text{CTL}^*$, $\exists\text{CTL}^*$ and CTL^* , p. 28.
94/25	T. Kloks	$K_{1,3}$ -free and W_4 -free graphs, p. 10.
94/26	R.R. Hoogerwoord	On the foundations of functional programming: a programmer's point of view, p. 54.
94/27	S. Mauw and H. Mulder	Regularity of BPA-Systems is Decidable, p. 14.
94/28	C.W.A.M. van Overveld M. Verhoeven	Stars or Stripes: a comparative study of finite and transfinite techniques for surface modelling, p. 20.
94/29	J. Hooman	Correctness of Real Time Systems by Construction, p. 22.
94/30	J.C.M. Baeten J.A. Bergstra Gh. Ştefănescu	Process Algebra with Feedback, p. 22.
94/31	B.W. Watson R.E. Watson	A Boyer-Moore type algorithm for regular expression pattern matching, p. 22.
94/32	J.J. Vereijken	Fischer's Protocol in Timed Process Algebra, p. 38.
94/33	T. Laan	A formalization of the Ramified Type Theory, p.40.
94/34	R. Bloo F. Kamareddine R. Nederpelt	The Barendregt Cube with Definitions and Generalised Reduction, p. 37.
94/35	J.C.M. Baeten S. Mauw	Delayed choice: an operator for joining Message Sequence Charts, p. 15.
94/36	F. Kamareddine R. Nederpelt	Canonical typing and Π -conversion in the Barendregt Cube, p. 19.

- 94/37 T. Basten
R. Bol
M. Voorhoeve
Simulating and Analyzing Railway Interlockings in
ExSpect, p. 30.
- 94/38 A. Bijlsma
C.S. Scholten
Point-free substitution, p. 10.