Simulation-based support for product development of innovative building envelope components

Citation for published version (APA):

Loonen, R. C. G. M., Singaravel, S., Trcka, M., Costola, D., & Hensen, J. L. M. (2014). Simulation-based support for product development of innovative building envelope components. *Automation in Construction*, 45, 86-95. <https://doi.org/10.1016/j.autcon.2014.05.008>

DOI:

[10.1016/j.autcon.2014.05.008](https://doi.org/10.1016/j.autcon.2014.05.008)

Document status and date:

Published: 01/01/2014

Document Version:

Accepted manuscript including changes made at the peer-review stage

Please check the document version of this publication:

- A submitted manuscript is the version of the article upon submission and before peer-review. There can be important differences between the submitted version and the official published version of record. People interested in the research are advised to contact the author for the final version of the publication, or visit the DOI to the publisher's website.
- The final author version and the galley proof are versions of the publication after peer review.
- The final published version features the final layout of the paper including the volume, issue and page numbers.

[Link to publication](#)

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal.

If the publication is distributed under the terms of Article 25fa of the Dutch Copyright Act, indicated by the "Taverne" license above, please follow below link for the End User Agreement:

www.tue.nl/taverne

Take down policy

If you believe that this document breaches copyright please contact us at:

openaccess@tue.nl

providing details and we will investigate your claim.

Simulation-based support for product development of innovative building envelope components

R.C.G.M. Loonen[✉], S. Singaravel, M. Trčka[‡], D. Cóstola[§], J.L.M. Hensen

*Building Physics and Services,
Eindhoven University of Technology, the Netherlands*

e-mail: r.c.g.m.loonen@tue.nl

1 Abstract

2 A need for innovation in building envelope technologies forms a key element of
3 technology roadmaps focusing on improvements in building energy efficiency. Many
4 new products are being proposed and developed, but often, a lack of insights into
5 building integration issues is an obstacle in typical product development processes.

6 The main objective of this paper is to demonstrate the potential of expanding the
7 application area of whole-building performance simulation and analysis towards
8 decision-making support in the domain of research and development of such
9 innovative building products. We propose a simulation-based approach that can help
10 overcome several of the existing limitations.

11 The methodology combines building performance simulation together with
12 sensitivity analysis and structured parametric studies to provide multi-scale, multi-
13 disciplinary information about the performance of different product variants. The
14 strength of this computational approach lies in increased opportunity for analysis and
15 informed decision-making on the basis of whole building performance information,
16 and therefore less dependence on trial and error procedures.

1 This methodology is illustrated in an application example of a new type of
2 switchable glazing where we give recommended directions for improved product
3 specifications.

4

5 **Keywords:**

6 Product development; building performance simulation; decision support; smart
7 windows; indoor environmental quality; energy efficient buildings

1. Introduction

The present and future of sustainability in the built environment is influenced by two opposing factors. From an environmental perspective, there is the need to reduce building-related CO₂ emissions [1]. However, at the same time, the importance of high levels of indoor environmental quality is well-recognized [2], and comfort expectations continue to rise [3, 4]. As technological solutions in response to this challenging situation, many innovative building technologies and components have recently been proposed [5, 6, 7, 8]. In particular, the integration of active and passive design elements in the building envelope is increasingly receiving attention from the research and development community [9, 10, 11].

Diffusion of new technologies into daily construction practice is a challenging but essential step towards realizing effective contributions of these innovations in terms of sustainability goals [12, 13, 14]. Wide-scale applicability and competitive cost-benefit ratios are both identified as essential conditions for making such impact happen. [15, 16].

In this paper, the application of building performance simulation (BPS) and analysis techniques is put forward as a useful additional tool in the product development of innovative building envelope components, to make the process more efficient and effective. This is done by proposing and testing a methodological framework that aims at overcoming some of the existing limiting elements in product development processes.

The paper is organized as follows. Section 2 continues with an overview of recent innovative building envelope components and identifies some of the barriers and limitations that are faced in the innovation process. In Section 3, this is followed by a short review of the current role of modeling and simulation in product development of new building envelope components. In Section 4, we propose a methodological

framework for more effective use of BPS throughout multiple stages of the product development process. This method is then applied to a case study of a new type of switchable glazing in Sections 5 and 6. After reflecting on findings from the case study, the paper is concluded in Section 7 by discussing how BPS can help overcome some of the limitations we identified.

2. Barriers in product development of innovative building envelope components

From discovery to deployment as a marketable product, new products go through several stages of the research and development (R&D) process [17]. Figure 1 presents an overview of characteristic phases that a new product typically undergoes in product development cycles of innovative building envelope components.

Figure 1: Characteristic phases in product development of innovative building envelope components.

In Figure 2, recent publications describing R&D steps of various innovative adaptable building envelope components are classified according to these phases [18-44] .

1

2

3 **Figure 2: Classification of building envelope R&D publications in relation to the characteristic**
4 **phases from Figure 1.**

5 The success or failure of innovations in the construction industry is influenced by
6 numerous factors. The ability of innovation teams to show that their new product will
7 reduce cost and enhance quality or performance, has been recognized as one of the

key enablers for success in this context [17]. A lack of effective communication about performance aspects, by contrast, was identified as one of the significant barriers hindering technical innovation [45].

Considering these drivers and barriers for innovation, a number of inefficient elements in the R&D process were identified from the studies summarized in Figure 2:

- **Mismatch between information need and availability:** Product development of building envelope components often takes an iterative, but linear problem solving approach (Figure 1) [46, 47]. Decisions in the early stages have highest impact on the end result, but in the absence of detailed whole-building performance information, tend to be based on intuition rather than analysis. Because only limited performance information is available, it is difficult to set goals, and measure whether they are achieved. Moreover, early-stage identification of most promising directions for further development is a challenging task.
- **Disconnection between material science and building scale:** Multiple stakeholders with diverse interests are involved in the product development process. As a result, there is a need for objective performance information to assist in decision-making. The innovation process moreover typically spans across multiple engineering disciplines. The expertise required for contributing to progress in technology development tends to be in a different domain than the expertise required to assess what impacts this has on the built environment. In the existing workflow, material scientists have limited guidance as to which properties are optimal [44], and it may not be straightforward to appraise how modifications on the material scale affect performance aspects on the building level. There is a demand for integrated, multi-scale, multi-disciplinary tools to provide such complex insights.

- 1 • **Lack of information on building integration issues:** Annual performance
2 of building envelope components is strongly coupled to building-specific
3 design attributes (e.g. glazing percentage, orientation) and dynamic
4 disturbances (e.g. climatic conditions, occupants' behavior). Component-level
5 performance metrics like U-value and solar heat gain coefficient, which are
6 determined under a single set of standard test conditions, can capture this
7 type of complexity only partially [48, 49]. In many situations, good design
8 solutions are those that find a balanced trade-off point considering the
9 multitude of competing performance criteria over the whole building life cycle
10 [50, 51]. Pushing component-level properties such as visible transmittance
11 towards either high or low extremes might therefore not always be the best
12 solution, but a more thorough analysis of building performance issues is
13 needed to make well-informed decisions. Moreover, an increasing number of
14 innovative components make use of materials with controllable, dynamic
15 properties. In such cases, considering the adaptive behavior under transient
16 conditions is fundamental for evaluation of the performance [11].
- 17 • **Limitations of experiments:** The task of obtaining reliable performance
18 information on the basis of experiments is not always straightforward. This
19 holds for measuring the different building energy flow paths [52], and also
20 applies to objective quantification of thermal [53] and visual comfort
21 perception [54]. Moreover, conducting series of experiments with different
22 product variants is a time-consuming and labor-intensive activity. Because of
23 planning and budget constraints, the number of product iterations often needs
24 to be kept as low as possible.
- 25 • **No what-if analysis:** In the conventional product development process, only
26 a limited number of scenarios, related to such factors as orientation, building
27 typology and climate can be examined. It is difficult to make projections of
28 performance outside the range of tested conditions on the basis of this

1 bounded and incomplete knowledge. Technological product development can
2 also be hampered by the state of innovation itself. The envisioned directions
3 for further development may be clear, but the technology is still immature, or
4 evaluated on the basis of semi-functional prototypes [44]. Test output from
5 experiments may consequently give a distorted view of reality, and thereby
6 introduce the risk that the actual performance of the end product is
7 misinterpreted [55]. Physical tests thus provide only limited insights into
8 possibilities of products with specifications that push the edge of what is
9 possible. To explore future directions, it can sometimes be worthwhile to
10 assess the performance of visionary, hypothetical product variants with
11 properties that cannot yet be manufactured [56]. The virtual world of
12 computer simulations is well-suited for supporting this type of analyses.

13 Considering these limitations in existing product design and development processes,
14 it is expected that some emerging building envelope technologies do currently not
15 reach their full potential. This situation potentially leads to sub-optimal solutions
16 which have negative impact on the competitive position of product developers, but is
17 also a missed opportunity for the innovations to contribute to sustainability goals.

18 **3. The role of simulation in new building product development**

19 BPS takes into account the dynamic interactions between building design, climatic
20 conditions, and user behavior, and is therefore considered as a valuable resource in
21 the process of refining building performance. These attributes are the reason why
22 BPS is routinely used for supporting informed decision-making in the building design
23 process [57], and make that BPS is also gradually being introduced in the building's
24 operational phase [58]. In relation to innovative building envelope components, the
25 dominant use case of BPS is in the performance evaluation of specific building
26 design concepts [59, 60, 61]. Thus far, the systematic application of BPS for

1 decision-making support in the process of product specification development
2 remained largely unexplored. Strachan (2008) [62] argues that the application of BPS
3 can “offer the bridge between outdoor tests and full-scale building performance
4 prediction”, and presents a number of applications in this last phase of product
5 development. A methodology for using BPS as an explicit R&D tool in the earlier
6 stages of the process has not been proposed before. The calculations or simulations
7 being used in these stages typically focus on the component-level only, and tend to
8 be limited to steady-state conditions for typical or extreme cases. Nevertheless, BPS
9 has occasionally been associated with terms like virtual laboratory [63, 64, 65], and
10 conducting of virtual experiments [66]. In the following sections, we take this notional
11 concept a step further, by presenting an approach that can be implemented
12 throughout all stages of the product development process.

13 **4. A methodology for BPS-based support in product development**

14 Product development processes of new building envelope components are not easily
15 captured in generally-applicable workflows or process diagrams. The reason is that
16 there are many case-specific characteristics that can be unfitting for other product
17 development processes. For example, the innovation can be (i) industry- or
18 university-driven, (ii) autonomous, or part of a family of (existing) products, or (iii) with
19 or without availability of prototypes, or access to testing facilities. Moreover, each
20 process has its case-specific stakeholders, performance aspects (conflicting or not),
21 constraints, time-lines, etc.

22 To add structure to the role of simulation in this process, without being too
23 prescriptive, we propose the following seven-step procedure for effective use of BPS
24 in the product development process of innovative building envelope components
25 (Figure 3).

Figure 3: Simulation-based methodology for decision-support in R&D of building envelope technologies

- 1. Set goals and performance objectives.** Before beginning the analysis, it is important to determine the intended purpose of the simulation study. In parallel, the performance objectives that have to be achieved by the innovative component need to be established. It is necessary to identify the multiple performance aspects that together contribute to the success or failure of the product, and to reach consensus about their priorities [13, 27]. Such a performance-based approach, with clearly defined objectives, can guide the team in decision-making through the various stages of the development process. This first step should additionally help in defining focus by specifying boundaries in terms of climatic conditions, building typology, technical constraints, etc.
- 2. Select performance indicators (PIs).** Performance of different product variants can be evaluated and compared after identification of appropriate PIs in line with the objectives. The set of PIs should address the innovative component's ability to influence the building's environmental, economic and social impacts. Note that

1 improper selection of PIs may lead to insufficient insight for decision-making
2 throughout the development process.

3 3. **Develop a modeling and simulation strategy.** The aim of this step is to
4 transform the component's observed behavior into models that can be
5 embedded in whole-building simulation programs. This model development
6 should capture all relevant physical principles and address the PIs at an
7 appropriate level of detail, by finding a right balance between model complexity
8 and resulting accuracy [67, 68].

9 Measurements form an essential part of this step. On the one hand, they are
10 used to complement the model development and for parameter identification of
11 building envelope characteristics. On the other hand, they can help build
12 confidence in model outcomes by means of empirical validation studies.

13 It should be realized that many of the product development processes are at the
14 forefront of technology (Figure 2). As a result, off-the-shelf simulation tools may
15 have limited modeling capabilities to support adequate performance prediction of
16 such innovative concepts [69]. To avoid time-consuming development of new
17 computational models from scratch, rapid virtual prototyping [70, 71] or co-
18 simulation techniques [72] may become interesting options.

19 4. **Performance benchmark.** This step provides the R&D team with information
20 about performance of the product in its present state. The analysis can be done
21 by comparing performance of the innovative component with (i) direct
22 competitors, or (ii) other technologies that fulfill similar roles. To perform this
23 study, one or more reference buildings with simple building and system features
24 are modeled in the selected BPS tools. As such, this phase serves to give an
25 indication of the scope for improvement, and builds awareness of the strengths
26 and weaknesses of the product.

1 **5. Define test case building models.** One of the differences between simulation
2 support in building design versus product development is the inherent degree of
3 variation in potential future applications in the latter case. As a general rule, the
4 R&D team seeks to develop products that can accommodate a wide range of
5 building designs. In product development, it is therefore important not to focus
6 on the specifics of one building, but instead, to explore a variety of possibilities.
7 Sensitivity analysis [73, 74] can act as a tool for defining test case buildings with
8 different design attributes in an appropriate way. In the BPS domain, sensitivity
9 analysis is normally used for identifying the set of variables which have most
10 significant influence on simulation outcomes [75]. In the present context,
11 sensitivity analysis is used to adequately define test case building models, based
12 on the ranking of design variables with respect to differences in comfort and
13 energy performance. The test case building models represent more extreme
14 cases than the reference building used in step 4. This distinction is made with
15 the following three goals in mind:

- 16 • Accentuating differences in performance, and ensuring that they can
17 be attributed to variations in product specifications.
- 18 • Identifying the need for one common product, or a family of products,
19 to be customized to the needs of different applications [76].
- 20 • Targeting the market niche with the highest potential for early
21 applications.

22 **6. Parameter study.** To identify the best performing product variants, or
23 directions for improvement, a simulation-based parametric or optimization
24 study is performed, with the innovative component integrated in the
25 previously defined test case buildings. Whereas the previous step focused on
26 differences in building design aspects, this step considers performance

1 effects related to parameter variations of the envelope component itself. It is
2 important to note that virtual prototyping experiments [77, 78, 79, 80] can be
3 performed, with product specifications that may not yet be feasible in practice.
4 In addition, a check for performance robustness, or "what-if" analyses can be
5 performed at the end of this step by considering a range of different use
6 scenarios or ambient conditions.

7 **7. Decision-making.** In this final step, simulation outcomes are compared to the
8 goals and requirements from step 1. The results can be used for decision-
9 making regarding e.g. most-promising product specifications, outlining material
10 science development objectives and directions, and communicating performance
11 benefits to stakeholders. The simulation process can be repeated in loops, to
12 represent different product generations throughout the development process.

13 To illustrate the use of BPS in the integrated development process of innovative
14 components for the building envelope, the methodology as outlined above is applied
15 and examined for a new type of switchable window that is described in the following
16 section.

17 **5. Application example: new switchable window technology**

18 For many years, switchable window technology holds the promise of becoming a
19 significant player in energy efficient building design [81]. Progress over the last years
20 has led to many advances, and recently resulted in a first generation of commercially
21 available switchable glazing products [82, 83]. Despite this progress, widespread
22 application still seems to be a few steps away. To make switchable glazing more
23 competitive with conventional types of solar shading, ongoing R&D efforts are
24 focusing on several different aspects, including: tuning of spectral properties [84, 85],
25 improving thermal performance of the window [86], reducing switching times [87],
26 enhancing long-term stability [88], and optimizing operation strategies [89].

1 The work presented in this application example is part of these developments. More
2 specifically, it is embedded in a new line of research that aims to unite the
3 complementary positive aspects of liquid crystal switchable windows and
4 luminescent solar concentrators [41, 85, 90]. A key advantage of such a window lies
5 in the potential to generate the electricity that is required for its own operation.
6 Because no external power supplies are needed, this opens up interesting
7 opportunities in renovation projects.

8 **5.1. Description of the initial situation**

9
10 **Figure 4 Overview of experimental set-up for characterization of material properties**

11 Measurements on reduced-scale samples were carried out to characterize optical
12 properties of the switchable window according to ISO 9050 (Figure 4). The
13 switchable window properties shown in Figure 5 (black dots for dark (D) and bright
14 (B) states) represent the state of development after proof-of-principle, but prior to the
15 simulation process, and contrast these to all other optical properties (grey dots) in the
16 international glazing database (IGDB) [91]. Compared to the more mature, state-of-

1 the-art electrochromic materials, the technology shows a relatively restricted
2 switchable range [83]. But as the technology is still in the earlier stages of
3 development, there is sufficient scope for adjustments. For the purpose of this study,
4 we assume that the window can only be switched in two states; the bright and dark
5 states respectively. As opposed to the switching delays observed in e.g.
6 electrochromic window systems, this type of window is able to switch
7 instantaneously.

8
9 **Figure 5 Relationship between solar and visible transmittance for the switchable window states**
10 **in relation to other glazing types in the IGDB (grey dots). Black dots indicate the current**
11 **situation for bright (B) and dark (D) state. Diamonds and triangles are only used in Section 6.6.**
12 **Diamonds indicate options for the parametric study (Section 6.6) with the same light-to solar-**
13 **gain ratio but more (+) or less (-) transmission; triangles indicate options with enhanced spectral**
14 **selectivity (Section 6.6.2).**

15 6. Results

16 In this Section we present the results of simulation studies which were performed to
17 assist decision-making during product development of the new switchable window

type. The results are described by following the same steps as outlined in the framework of Section 4.

6.1. Goals and performance objectives

Dynamic optical properties of switchable windows have a direct influence on both energy performance and indoor environmental quality of a building. Depending on the window's state, the positive and negative aspects of incoming solar radiation can be modulated over time. Switchable windows with a large dynamic switching range have, in theory, the highest potential for reducing heating and cooling energy consumption [44, 92]. In addition, a low-transparent dark state works well for reducing glare, whereas high transparency in the bright state is beneficial for daylight utilization and view to outside. Determination of these advantages is, however, not always straightforward because savings may be offset by other PIs, such as increased electricity consumption for lighting. Moreover, from the point of view of material development, it is not realistic to focus on all aspects at the same time. The goal of this simulation-based study therefore is to identify priorities for further development of the switchable glazing product based on integrated comfort and energy performance considerations.

For successful integration of the new switchable window technology in building envelopes, the following requirements should be met:

- Low energy consumption for lighting, heating and cooling;
- High degree of daylight utilization;
- Low occurrence in perception of daylight glare;
- High levels of thermal comfort.

6.2. Performance indicators

Recently, a number of studies had the goal to investigate the interrelationships between thermal, visual and energy performance indicators in the context of: window design optimization [50], computer-based daylighting analysis [93], solar shading systems [94], and smart windows [95]. Based on findings from these studies, and in line with the objectives of step 1, the PIs in Table 1 were selected for the performance assessment. Table 1 makes a distinction between absolute and relative PIs. Absolute indicators allow for generic comparisons, whereas the relative PIs specifically focus on the difference with a reference or benchmark case. To compute primary energy consumption, we assume that the seasonal heating efficiency = 0.9, cooling COP = 3, and the primary energy conversion factor for electricity = 2.5.

Table 1: Overview of performance indicators

Absolute	Relative
Total primary energy demand [kWh/m ² _{floor area}]	Total energy savings [%]
Useful daylight illuminance (UDI) [-]	Improvement in UDI [%]
Daylight glare probability (DGP) [-]	Reduction in glare [%] or daylight glare hours [hr]
Overheating hours [hr]	Reduction in overheating hours [%]

6.3. Model development and simulation strategy

Compared to BPS models for performance prediction of conventional facade systems, two additional requirements apply for the case of switchable windows:

- Flexibility in input of new window properties;
- Possibility to change and control window properties during simulation runtime.

Because of these requirements, special attention needs to be paid to the selection of BPS tools. Various simulation approaches have previously been used for analyzing the performance of switchable glazing products (e.g. [25] [89] [95] [84]). In this research, we adopt a high-resolution, coupled simulation strategy which is outlined in

Figure 6. Daylight simulations were first conducted in a preprocessing stage for all window states independently. DAYSIM [96] is used to calculate annual time-series of five-minute luminance and illuminance data and daylight glare probability (DGP) values at specific sensor-points. This data is then supplied to TRNSYS [97], which selects the right data during run-time corresponding to the operational logic in the window controller. The integration of thermal and visual domains is accomplished by feeding internal gains for lighting from DAYSIM to TRNSYS type 56 and basing window state on either thermal or lighting considerations [98].

Throughout the model development process, it was assumed that the behavior of the switchable window can be modeled using the default set of input parameters and physical relationships for specular glazing systems. The validity of this assumption was demonstrated in experiments with the liquid crystal window integrated in reduced-scale prototypes exposed to atmospheric boundary conditions. Details of this validation study are reported in [99].

15

16

Figure 6: Coupled simulation approach using TRNSYS and DAYSIM

17

1 **6.4. Performance benchmark**

2 The analysis in this part of the study focuses on a four-person South-facing perimeter
3 office zone, situated at an intermediate floor, and surrounded by identical office
4 spaces (Figure 7). Representative values for a Dutch reference office building [100]
5 were taken for other construction details. The office zone is occupied from 9 am to 5
6 pm, and results are evaluated with ambient conditions for Amsterdam, the
7 Netherlands.

8
9 **Figure 7 Office room used for the benchmarking study**

10 Previous studies show that the performance of switchable windows is strongly linked
11 to the window control strategy that is used for their operation [25, 89]. Before doing
12 comparative analyses on the product level, it is therefore important to examine these
13 control aspects first. Six different operation strategies were analyzed in this study;
14 five strategies using automated control, and one using manual operation as a
15 reference strategy (Table 2).

16
17 **Table 2: Overview of the operation strategies**

Reference operation strategy	window operated with control strategy that resembles manual operation of venetian blinds (Lightswitch) [101]
------------------------------	--

Operation strategy 1	window switches to dark when daylight illuminance on the workplane > 500 lx
Operation strategy 2	window switches to dark when exterior illuminance on the window is > 20,000 lx
Operation strategy 3	window switches to dark when room air temperature > 24°C
Operation strategy 4	window switches to dark when outdoor air temperature > 24°C
Operation strategy 5	window switches to dark from 1 May until 30 September

1

2 Figure 8 shows the results for each of the different automated window operation
3 strategies, relative to the reference strategy with manual control. It can be observed
4 that only the control strategy based on indoor daylight illuminance (strategy 1),
5 results in an improvement in all four performance aspects. Therefore, this strategy is
6 selected for use in further analyses in this paper.

7

8 **Figure 8 Performance of the switchable window for different window operation strategies**

9 As switchable windows could replace conventional types of solar shading, it is also
10 important to position their performance with respect to competing technology options.
11 To this end, a benchmark study was performed by comparing performance aspects
12 of the switchable window to cases with conventional double glazing, using the same
13 U-value, combined with solar shading in the form of (i) a 50 cm horizontal overhang
14 and (ii) internal venetian blinds. From the results presented in Table 3, it can be

observed that the switchable window is the most favorable option when it comes to energy demand and thermal comfort. However, there is still room for improvement in the windows' ability to reduce the occurrence of glare, while proving sufficient levels of daylight in the occupied space.

Table 3: Results of the benchmark study, comparing and ranking the switchable window with an overhang and venetian blinds.

		Overhang	Venetian blinds	Switchable window
Energy	kWh/m ²	113.5	127.9	101.2
	Rank	2	3	1
Overheating	hr	277	78	48
	Rank	3	2	1
UDI	<100 lux	%	6.3	18.8
	100-2000 lux	%	79.1	80.9
	>2000 lux	%	14.6	0.3
	Rank	2	1	3
DGP	Imperceptible	%	92	98
	Rank	2	1	3

6.5. Definition of test case building models

A single-variable sensitivity study was performed to define the test case building models that are used in the parametric study. This was done by modifying the parameters of a base case model over the ranges indicated in Table 4. The outcomes of the sensitivity study were post-processed using the elementary effects screening method [102, 103]. In this analysis, the sensitivity indices are calculated relative to the performance of the base case with switchable glazing. As such, we do not evaluate the absolute merits of applying a switchable window, but shift the attention towards differences with the existing product variant.

Table 4: Parameter values and samples for the sensitivity study

Parameter	Unit	Base case value	Range	Samples
-----------	------	-----------------	-------	---------

Window-to-wall ratio	[-]	0.5	0.15 – 0.95	0.15, 0.25, 0.35, 0.45, 0.55, 0.65, 0.75, 0.85, 0.95
Window orientation	[-]	south	-	north, east, west
Window position	[-]	center	-	top, bottom, left, right
Room depth	m	5.40	3 – 7	3, 4, 6, 7
Wall insulation	W/m ² K	0.3	0.1 – 0.5	0.5, 0.4, 0.2, 0.1
Thickness of thermal mass layer	cm	4	1 – 8	1, 2, 3, 6, 8

1

2 Table 5 shows the parameter ranking as outcome of the sensitivity analysis. Because
3 building performance is most sensitive to the parameters ‘window-to-wall ratio’ and
4 ‘window orientation’, it is worthwhile to investigate to what extent different
5 fenestration properties affect the performance under a wider range of values for
6 these two design attributes. To this end, eight variants of the reference office space
7 are defined as test case buildings for further analyses. These test case buildings
8 have a window-to-wall ratio (WWR) of 25% and 95%, and are evaluated in all four
9 cardinal orientations.

10

11 **Table 5: Ranking of the influence of different building parameters on performance**

Rank	Total energy savings	Increase in UDI
1	Window orientation	Window area
2	Window area	Window orientation
3	Room depth	Room depth
4	Window position	Window position
5	Insulation	Insulation / Thermal mass
6	Thermal mass	

12

6.6. Parameter study

6.6.1. Influence of orientation and window-to-wall ratio (WWR)

Figure 5 gives an overview of the range of dynamic solar-optical window properties which are tested in the parametric study. Black dots correspond to the original window properties in the bright (B) and dark (D) state. Black diamonds represent alternative sets of optical properties. For both states, alternative variants with more (+) and less (-) transparency are tested with similar light-to-solar-gain ratio. In total, this leads to nine different combination sets of glazing properties.

Table 6 shows results in terms of energy performance and UDI for every orientation and WWR. The results are ranked in such a way that 1 represents the best, and 9 represents the worst-performing alternative. By doing this, it is relatively easy to observe performance trends in the simulation output. The results for this example show that combinations with B+ and D- tend to lead to the highest performance. The product can therefore be improved by extending the range of operability between bright and dark states. Further examination of results shows that for buildings with small WWRs, higher light transmittance of the bright state has more influence on the building performance, whereas for buildings with large WWRs, lower light transmittance of the dark state leads to a more positive effect.

Table 6: Ranking of results for different orientations and window-to-wall ratios.

Orientation		South		West		East		North	
WWR		0,97	0,25	0,97	0,25	0,97	0,25	0,97	0,25
B-	D+	8	8	8	8	3	8	9	7
B-	D	5	5	5	5	4	4	5	5
B-	D-	2	3	2	4	9	1	2	4
B	D+	9	9	9	9	8	9	8	9
B	D	6	7	6	7	7	7	6	8
B	D-	3	4	3	6	5	5	3	6
B+	D+	7	6	7	3	6	6	7	2
B+	D	4	2	4	2	2	3	4	1

B+	D-	1	1	1	1	1	2	1	3
----	----	---	---	---	---	---	---	---	---

1

2 These findings suggest that perhaps it is not wise not to invest all time and effort in
3 developing just one product with the widest modulation range possible. Instead, the
4 development of customized windows, with a relatively narrow switching range, but
5 tuned to the demands of different applications, seems to be a more promising
6 approach.

7 6.6.2. Influence of spectral selectivity

8 As a potential improvement to the current glazing specifications, another set of
9 properties with enhanced spectral selectivity is analyzed, i.e. having a higher visible
10 light transmittance for the same solar transmittance (indicated with triangles in Figure
11 5). Because these alternative window sets have a higher light-to-solar-gain (LSG)
12 ratio [104], it is expected that, in the cooling-dominated office, they lead to a more
13 favorable tradeoff point in the interaction between solar gains and daylighting. In
14 terms of daylight utilization and glare, no differences in performance are observed.
15 However, as Table 7 shows, the performance gains in terms of reduced energy
16 demand are significant. Especially for applications with large WWRs, the switching of
17 optical properties in the near-infrared range is a direction that warrants further
18 exploration.

19

20 **Table 7: Energy performance improvement relative to the case regular light-to-solar-gain ratio.**
21 **The results are shown as improvements in percentage points.**

Orientation		South		West		East		North	
WWR		0,97	0,25	0,97	0,25	0,97	0,25	0,97	0,25
B-	D+	9.3%	4.2%	6.8%	2.7%	6.2%	2.3%	4.4%	1.1%
B-	D	9.8%	3.9%	7.3%	2.8%	6.2%	2.2%	4.4%	1.1%
B-	D-	9.0%	3.2%	6.7%	2.7%	6.0%	1.5%	3.7%	1.0%
B	D+	9.3%	4.3%	6.8%	2.9%	6.6%	2.4%	4.4%	1.2%

B	D	9.8%	3.9%	7.3%	2.9%	6.9%	2.3%	4.4%	1.2%
B	D-	9.0%	3.2%	6.7%	2.6%	6.7%	1.6%	3.7%	0.9%
B+	D+	9.2%	4.2%	6.7%	2.8%	6.4%	2.3%	4.4%	1.1%
B+	D	9.7%	3.7%	7.2%	2.8%	6.9%	2.2%	4.4%	1.1%
B+	D-	9.0%	3.0%	6.7%	2.5%	6.9%	1.9%	4.3%	1.0%

1

2 **6.7. Case study conclusion and reflection**

3 Identifying priorities for further development of the switchable glazing product was
4 specified as the main goal at the beginning of the simulation study. Because the
5 computational approach uses high-resolution models that effectively take into
6 account the mutual interactions between daylighting and thermal effects, we were
7 able to analyze the performance of various switchable glazing alternatives at a high
8 level of detail. Our results show different areas for improvement compared to the
9 existing product variant, translating into a challenge that can be addressed in two
10 different ways. One option is striving for the largest switching range possible, which
11 coincides with the direction that tends to be pursued by most material scientists in
12 this field [44, 92]. Analysis of our results, however, suggests that, for the conditions
13 we investigated, it is more interesting to tune window specifications in response to
14 the requirements under different design scenarios. For certain buildings it would be
15 better to have high visible transmittance in the bright state, whereas in other
16 applications low solar transmittance in the dark state is the key to obtaining higher
17 performance. For the short-term development goals towards early market
18 introduction, these divergent requirements are therefore treated in the form of two
19 different variants of the same product family. Results from our simulations moreover
20 show the importance of spectral selectivity and development of advanced control
21 strategies that can respond to the multi-criteria nature of solar shading control.

22 This computational study served the main purpose of demonstrating the proposed
23 simulation framework. It explored only a limited subset of possibilities for variable

1 window properties, and is limited in scope, but nevertheless provided valuable
2 information to the product development team, and worked well as a medium for
3 discussion and communication. Simulation-based research continues to be used in
4 the R&D process for investigating the potential of windows with e.g. intermediate
5 states in transparency, or further refined spectral selectivity, and for testing the
6 robustness of our findings in different climates. Future research could additionally
7 focus in more detail on the window control aspects and could make use of
8 optimization algorithms to more efficiently explore the design option space.

9 **7. Discussion and conclusions**

10 In this paper, we proposed a simulation-based approach to assist decision-making in
11 the process of innovative building envelope product development. By taking
12 advantage of whole-building performance predictions in combination with sensitivity
13 analyses and structured parametric studies, the method is able to provide insight into
14 building integration issues of such components at an early stage of the R&D process.
15 Through iterative evaluation of multiple product variants, the integration of simulation
16 allows for strategic decisions that acknowledge high-potential directions in the
17 development process and may therefore help creating competitive advantage by
18 improving product performance or time-to-market in a cost-effective way. Moreover,
19 the method also allows for multi-scale, quantitative, analysis of effects that are not
20 easily captured in pilot studies or field test experiments, such as what-if studies and
21 robustness evaluation of the solutions with respect to different occupancy scenarios,
22 performance indicators, or climatic contexts.

23 The simulation-based approach does, however, not intend to replace the role of
24 experiments. Yet, it can help give priority to test those candidate solutions with higher
25 chances of success. Simulations can furthermore be used for exploring the potentials

1 of systems with properties that do not yet exist. This is something one can
2 accomplish only through virtual experiments.

3 **8. Bibliography**

4

- [1] International Energy Agency, *Energy Technology Perspectives 2012 - how to secure a clean energy future*, 2012.
- [2] M. Frontczak, S. Schiavon, J. Goins, E. Arens, H. Zhang and P. Wargocki, "Quantitative relationships between occupant satisfaction and satisfaction aspects of indoor environmental quality and building design," *Indoor Air*, vol. 22, no. 2, p. 119–131, 2011.
- [3] E. Arens, M. Humphreys, R. de Dear and H. Zhang, "Are 'class A' temperature requirements realistic or desirable?," *Building and Environment*, vol. 45, pp. 4-10, 2010.
- [4] S. Roaf, F. Nicol, M. Humphreys, P. Tuohy and A. Boerstra, "Twentieth century standards for thermal comfort: promoting high energy buildings," *Architectural Science Review*, vol. 53, no. 1, pp. 65-77, 2010.
- [5] A. Omer, "Renewable building energy systems and passive human comfort solutions," *Renewable and sustainable energy reviews*, vol. 12, no. 6, p. 1562–1587, 2008.
- [6] D. Kolokotsa, D. Rovas, E. Kosmatopoulos and K. Kalaitzakis, "A roadmap towards intelligent net zero- and positive-energy buildings," *Solar Energy*, vol. 85, no. 12, p. 3067–3084, 2011.
- [7] B. Jelle, A. Hynd, A. Gustavsen, D. Arasteh, H. Goudey and R. Hart, "Fenestration of today and tomorrow: A state-of-the-art review and future research opportunities," *Solar Energy Materials and Solar Cells*, vol. 96, pp. 1-28, 2012.

- [8] S. Sadineni, S. Madala and R. Boehm, "Passive building energy savings: A review of building envelope components," *Renewable and Sustainable Energy Reviews*, vol. 15, no. 8, pp. 3617-3631, 2011.
- [9] M. Perino, "State-of-the-art Review - Responsive Building Elements," IEA ECBCS Annex 44 - Integrating Environmentally Responsive Elements in Buildings.
- [10] G. Quesada, D. Rousse, Y. Dutil, M. Basache and S. Hallé, "A comprehensive review of solar facades. Opaque solar facades," *Renewable and Sustainable Energy Reviews*, vol. 16, pp. 2820-2832, 2012.
- [11] R. Loonen, M. Trcka, D. Cóstola and J. Hensen, "Climate adaptive building shells: State-of-the-art and future challenges," *Renewable and Sustainable Energy Reviews*, vol. 25, pp. 483-493, 2013.
- [12] A. Blayse and K. Manley, "Key influences on construction innovation," *Construction Innovation: Information, Process, Management*, vol. 4, no. 3, pp. 143 - 154, 2011.
- [13] T. Häkkinen and K. Belloni, "Barriers and drivers for sustainable building," *Building Research & Information*, vol. 39, no. 3, pp. 239-255, 2011.
- [14] International Energy Agency, Technology Roadmap: Energy Efficient Building Envelopes, 2013.
- [15] M. Jakob and R. Madlener, "Riding down the experience curve for energy-efficient building envelopes: the Swiss case for 1970–2020," *International Journal of Energy Technology and Policy*, vol. 2, no. 1, pp. 153-178, 2004.
- [16] G. Nair, L. Gustavsson and K. Mahapatra, "Owners perception on the adoption of building envelope energy efficiency measures in Swedish detached houses," *Applied Energy*, vol.

87, no. 7, p. 2411–2419, 2011.

- [17] T. Toole, "Technological Trajectories of Construction Innovation," *Journal of Architectural Engineering*, vol. 7, no. 4, p. 107–114, 2001.
- [18] X. Xu, S. Van Dessel and A. Messac, "Study of the performance of thermoelectric modules for use in active building envelopes," *Building and Environment*, vol. 42, pp. 1489-1502, 2007.
- [19] X. Xu and S. Van Dessel, "Evaluation of a prototype active building envelope window-system," *Energy and Buildings*, vol. 40, p. 168–174, 2008.
- [20] W. Chun , S. Oh, H. Han, J. Kim and K. Chen, "Overview of several novel thermodiode designs and their application in buildings," *International Journal of Low Carbon Technologies*, vol. 3, no. 2, pp. 83-100, 2008.
- [21] M. Imbabi, "Modular breathing panels for energy efficient, healthy building construction," *Renewable Energy*, vol. 31, no. 5, p. 729–738, 2006.
- [22] E. Elsaragg, Y. Al-Horr and M. Imbabi, "Improving building fabric energy efficiency in hot-humid climates using dynamic insulation," *Building Simulation*, vol. 5, no. 2, pp. 127-134, 2012.
- [23] C. Granqvist, S. Green, G. Niklasson, N. Mlyuka, S. von Kraemer and P. Georén, "Advances in chromogenic materials and devices," *Thin Solid Films*, vol. 518, no. 11, pp. 3046-3053, 2010.
- [24] A. Piccolo and F. Simone, "Effect of switchable glazing on discomfort glare from windows," *Building and Environment*, vol. 44, no. 6, pp. 1171-1180, 2009.
- [25] M. Assimakopoulos, A. Tsangrassoulis, M. Santamouris and G. Guarracino, "Comparing

- the energy performance of an electrochromic window under various control strategies," *Building and Environment*, vol. 42, no. 8, p. 2829–2834, 2007.
- [26] E. Lee, E. Claybaugh and M. LaFrance, "End user impacts of automated electrochromic windows in a pilot retrofit application," *Energy and Buildings*, vol. 47, pp. 267-284, 2012.
- [27] J. Lienhard, S. Schleicher, S. Poppinga, T. Masselter, M. Milwich, T. Speck and J. Knippers, "Flectofin: a hingeless flapping mechanism inspired by nature," *Bioinspiration & Biomimetics*, vol. 6, no. 4, 2011.
- [28] Q. Li, A. Jäkel, V. Viereck and H. Hillmer, "Design of self-assembling micromirror arrays for light guiding," *Microsystem Technologies*, vol. 16, no. 5, pp. 895-899, 2010.
- [29] J. He and A. Hoyano, "Experimental study of practical applications of a passive evaporative cooling wall," *Building and Environment*, vol. 46, no. 1, pp. 98-101, 2011.
- [30] K. Ismail and J. Henriquez, "Thermally effective windows with moving phase change material curtains," *Applied Thermal Engineering*, vol. 21, no. 18, pp. 1909-1923, 2001.
- [31] S. Grynning, F. Goia, E. Rognvik and B. Time, "Possibilities for characterization of a PCM window system using large scale measurements," *International Journal of Sustainable Built Environment*, vol. 2, no. 1, pp. 56-64, 2013.
- [32] F. Goia, M. Perino and V. Serra, "Improving thermal comfort conditions by means of PCM glazing systems," *Energy and Buildings*, vol. 60, p. 442–452, 2013.
- [33] F. Goia, M. Perino and V. Serra, "Experimental analysis of the energy performance of a full-scale PCM glazing prototype," *Solar Energy*, vol. 100, p. 217–233, 2014.
- [34] H. Davidsson, B. Perers and B. Karlsson, "Performance of a multifunctional PV/T hybrid solar window," *Solar Energy*, vol. 84, pp. 365-372, 2010.

- [35] T. Runsheng, Y. Etzion and E. Erell, "Experimental studies on a novel roof pond configuration for the cooling of buildings," *Renewable Energy*, vol. 28, no. 10, p. 1513–1522, 2003.
- [36] B. Givoni, "Indoor temperature reduction by passive cooling systems," *Solar Energy*, vol. 85, no. 8, p. 1692–1726, 2011.
- [37] S. Lee, S. Kim, S. Kim, Y. Park and J. Park, "Experimental research on performance of the solar heat gain (SHG) insulation panel," *Building and Environment*, vol. 41, pp. 336–342, 2006.
- [38] E. Erell, Y. Etzion, N. Carlstrom, M. Sandberg, J. Molina, I. Maestre, E. Maldonado, V. Leal and O. Gutschker, "'SOLVENT': development of a reversible solar-screen glazing system," *Energy and Buildings*, vol. 36, no. 5, pp. 467–480, 2004.
- [39] V. Leal and E. Maldonado, "The role of the PASLINK test cell in the modelling and integrated simulation of an innovative window," *Building and Environment*, vol. 43, no. 2, p. 217–227, 2008.
- [40] A. Carbonari, R. Fioretti, B. Naticchia and P. Principi, "Experimental estimation of the solar properties of a switchable liquid shading system for glazed facades," *Energy and Buildings*, vol. 45, pp. 299–310, 2012.
- [41] M. Debije, "Solar Energy Collectors with Tunable Transmission," *Advanced Functional Materials*, vol. 20, no. 9, pp. 1498–1502, 2010.
- [42] P. Nitz and H. Hartwig, "Solar control with thermotropic layers," *Solar Energy*, vol. 79, no. 6, p. 573–582, 2005.
- [43] A. Seeboth, R. Ruhmann and O. Mühling, "Thermotropic and Thermochromic Polymer Based Materials for Adaptive Solar Control," *Materials*, vol. 3, no. 12, pp. 5143–5168,

2012.

- [44] E. Lee, X. Pang, S. Hoffmann, H. Goudey and A. Thanachareonkit, "An empirical study of a full-scale polymer thermochromic window and its implications on material science development objectives," *Solar Energy Materials and Solar Cells*, vol. 116, pp. 14-26, 2013.
- [45] J. Gambatese and M. Hallowell, "Enabling and measuring innovation in the construction industry," *Construction Management and Economics*, vol. 29, no. 6, pp. 553-567, 2011.
- [46] S. Eppinger, M. Nukala and D. Whitney, "Generalised Models of Design Iteration Using Signal Flow Graphs," *Research in Engineering Design*, vol. 9, pp. 112-123, 1997.
- [47] B. Kiss and L. Neij, "The importance of learning when supporting emergent technologies for energy efficiency—A case study on policy intervention for learning for the development of energy efficient windows in Sweden," *Energy Policy*, vol. 39, p. 6514–6524, 2011.
- [48] S. Dave and M. Andersen, "A Comprehensive Approach for Determining Performance Metrics for Complex Fenestration Systems," in *ASHRAE Winter Conference 2012*, Chicago, USA, 2012.
- [49] P. De Wilde, G. Augenbroe and M. Van der Voorden, "Design analysis integration: supporting the selection of energy saving building components," *Building and Environment*, vol. 37, no. 8/9, p. 807–816, 2002.
- [50] C. Ochoa, M. Aries, E. Van Loenen and J. Hensen, "Considerations on design optimization criteria for windows providing low energy consumption and high visual comfort," *Applied Energy*, vol. 95, p. 238–245, 2012.
- [51] G. Verbeeck and H. Hens, "Life Cycle Optimization of Extremely Low Energy Dwellings,"

Journal of Building Physics, vol. 31, no. 2, pp. 143-177, 2007.

- [52] R. Judkoff, D. Wortman, B. O'Doherty and J. Burch, "Technical Report NREL/TP-550-42059 - A Methodology for Validating Building Energy Analysis Simulations," National Renewable Energy Laboratory, Golden, Colorado, 2008.
- [53] J. Van Hoof, "Forty years of Fanger's model of thermal comfort: comfort for all?," *Indoor air*, vol. 18, no. 3, pp. 182-201, 2008.
- [54] A. Thanachareonkit and J. Scartezzini, "Modelling Complex Fenestration Systems using physical and virtual models," *Solar Energy*, vol. 84, no. 4, p. 563–586, 2010.
- [55] S. Thomke, "Experimentation in the Design of New Products," *Management Science*, vol. 44, no. 6, pp. 743-762, 1998.
- [56] G. O'Connor and R. Veryzer, "The nature of market visioning for technology-based radical innovation," *Journal of Product Innovation Management*, vol. 18, no. 4, pp. 231-246, 2001.
- [57] C. Bleil de Souza, "Studies into the use of building thermal physics to inform design decision making," *Automation in construction*, vol. 30, p. 81–93, 2013.
- [58] J. Hensen and R. Lamberts, Eds., *Building Performance Simulation for Design and Operation*, Taylor & Francis, 2011.
- [59] S. Kaçela and A. Yenera, "The Effect of Façade Design on Lighting Energy Consumption in Offices: A Case Study in Turin, Italy," *Architectural Science Review*, vol. 51, no. 4, pp. 360-368, 2008.
- [60] R. Høseggen, B. Wachenfeldt and H. S.O., "Building simulation as an assisting tool in decision making: Case study: With or without a double-skin façade?," *Energy and*

Buildings, vol. 40, no. 5, p. 821–827, 2008.

- [61] Z. Tian, J. Love and W. Tian, "Applying quality control in building energy modelling: comparative simulation of a high performance building," *Journal of Building Performance Simulation*, vol. 2, no. 3, pp. 163-178, 2009.
- [62] P. Strachan, "Simulation support for performance assessment of building components," *Building and Environment*, vol. 43, p. 228–236, 2008.
- [63] J. Hand, Removing barriers to the use of simulation in the building design professions, Glasgow, UK: PhD Thesis - University of Strathclyde, 1998.
- [64] A. Mahdavi, "Reflections on computational building models," *Building and Environment*, vol. 39, no. 8, p. 913–925, 2004.
- [65] "Optics 6," Lawrence Berkeley National Laboratory, [Online]. Available: <http://windows.lbl.gov/software/optics/optics.html>.
- [66] G. Augenbroe and C. Park, "Quantification methods of technical building performance," *Building Research & Information*, vol. 33, no. 2, pp. 159-172, 2005.
- [67] S. Attia, J. Hensen, L. Beltrán and A. De Herde, "Selection criteria for building performance simulation tools: contrasting architects' and engineers' needs," *Journal of Building Performance Simulation*, vol. 5, no. 3, pp. 155-169, 2012.
- [68] S. Robinson, "Conceptual modelling for simulation Part I: definition and requirements," *Journal of the Operational Research Society*, vol. 59, p. 278–290, 2008.
- [69] D. Crawley, J. Hand, M. Kummert and B. Griffith, "Contrasting the capabilities of building energy performance simulation programs," *Building and Environment*, vol. 43, no. 4, pp. 661--673, 2008.

- [70] J. Hensen, "Towards more effective use of building performance simulation in design," in *Proceedings of the 7th International Conference on Design & Decision Support Systems in Architecture and Urban Planning*, Eindhoven, 2004.
- [71] M. Wetter, "Modelica-based modelling and simulation to support research and development in building energy and control systems," *Journal of Building Performance Simulation*, vol. 2, no. 2, pp. 143-161, 2009.
- [72] M. Trcka, J. Hensen and M. Wetter, "Co-simulation of innovative integrated HVAC systems in buildings.," *Journal of Building Performance Simulation*, vol. 2, no. 3, pp. 209-230, 2009.
- [73] K. Lomas and H. Eppel, "Sensitivity analysis techniques for building thermal simulation programs," *Energy and Buildings*, vol. 19, no. 1, pp. 21-44, 1992.
- [74] J. Lam and S. Hui, "Sensitivity analysis of energy performance of office buildings," *Building and Environment*, vol. 31, no. 1, pp. 27-39, 1996.
- [75] W. Tian, "A review of sensitivity analysis methods in building energy analysis," *Renewable and Sustainable Energy Reviews*, vol. 20, p. 411-419, 2013.
- [76] J. Jiao, T. Simpson and Z. Siddique, "Product family design and platform-based product development: a state-of-the-art review," *Journal of Intelligent Manufacturing*, vol. 18, no. 1, pp. 5-29, 2007.
- [77] G. Wang, "Definition and Review of Virtual Prototyping," *Journal of Computing and Information Science in Engineering*, vol. 2, no. 3, pp. 232-236, 2002.
- [78] P. Hoes, M. Trcka, J. Hensen and B. Hoekstra Bonnema, "Investigating the potential of a novel low-energy house concept with hybrid adaptable thermal storage," *Energy*

Conversion and Management, vol. 52, no. 6, p. 2442–2447, 2011.

- [79] R. Loonen, M. Trcka and J. Hensen, "Exploring the potential of climate adaptive building shells," in *12th International IBPSA Conference Building Simulation*, Sydney, 2011.
- [80] R. Mangkuto, M. Aries, E. Van Loenen and J. Hensen, "Simulation of virtual natural lighting solutions with a simplified view," *Lighting Research and Technology*, 2013.
- [81] C. Lampert, "Electrochromic materials and devices for energy efficient windows," *Solar Energy Materials*, vol. 11, no. 1-2, p. 1–27, 1984.
- [82] C. Granqvist, P. Lansåker, N. Mlyuka, G. Niklasson and E. Avendaño, "Progress in chromogenics: New results for electrochromic and thermochromic materials and devices," *Solar Energy Materials and Solar Cells*, vol. 93, no. 12, p. 2032–2039, 2009.
- [83] R. Baetens, B. Jelle and A. Gustavsen, "Properties, requirements and possibilities of smart windows for dynamic daylight and solar energy control in buildings: A state-of-the-art review," *Solar Energy Materials and Solar Cells*, vol. 94, no. 2, p. 87–105, 2010.
- [84] N. DeForest, A. Shehabi, G. Garcia, J. Greenblatt, E. Masanet, E. Lee, S. Selkowitz and D. Milliron, "Regional performance targets for transparent near-infrared switching electrochromic window glazings," *Building and Environment*, vol. 61, p. 160–168, 2013.
- [85] C. Bastiaansen, A. Schenning, M. Debije and D. Broer, "Nano-textured polymers for future architectural needs," *Journal of Facade Design and Engineering*, vol. 1, no. 1-2, pp. 97-104, 2013.
- [86] S. Papaefthimiou, G. Leftheriotis, P. Yianoulis, T. Hyde, P. Eames, Y. Fang, P. Pennarun and P. Jannasch, "Development of electrochromic evacuated advanced glazing," *Energy and Buildings*, vol. 36, no. 12, p. 1455–1467, 2006.

- [87] Y. Park and J. Grunlan, "Fast switching electrochromism from colloidal indium tin oxide in tungstate-based thin film assemblies," *Electrochimica Acta*, vol. 55, no. 9, p. 3257–3267, 2010.
- [88] E. Lee and D. DiBartolomeo, "Application issues for large-area electrochromic windows in commercial buildings," *Solar Energy Materials and Solar Cells*, vol. 71, no. 4, p. 465–491, 2002.
- [89] A. Jonsson and A. Roos, "Evaluation of control strategies for different smart window combinations using computer simulations," *Solar Energy*, vol. 84, no. 1, p. 1–9, 2010.
- [90] M. Debijs and P. Verbunt, "Thirty Years of Luminescent Solar Concentrator Research: Solar Energy for the Built Environment," *Advanced Energy Materials*, vol. 2, no. 1, pp. 12–35, 2012.
- [91] IGDB, "International Glazing Database Version 23.0," 2012. [Online]. Available: <http://windowoptics.lbl.gov/data/igdb>.
- [92] S. Li, G. Niklasson and G. Granqvist, "Thermochromic fenestration with VO₂-based materials: Three challenges and how they can be met," *Thin Solid Films*, vol. 520, no. 10, p. 3823–3828, 2012.
- [93] C. Reinhart and J. Wienold, "The daylighting dashboard – A simulation-based design analysis for daylit spaces," *Building and Environment*, vol. 46, no. 2, p. 386–396, 2011.
- [94] D. Appelfeld, A. McNeil and S. Svendsen, "An hourly based performance comparison of an integrated micro-structural perforated shading screen with standard shading systems," *Energy and Buildings*, 2012.
- [95] E. Lee and A. Tavi, "Energy and visual comfort performance of electrochromic windows

with overhangs," *Building and Environment*, vol. 42, no. 6, p. 2439–2449, 2007.

- [96] "DAYSIM - Advanced daylight simulation software," 2013. [Online]. Available: www.daysim.com.
- [97] "TRNSYS - Transient System Simulation Tool," 2013. [Online]. Available: www.trnsys.com.
- [98] M. Trcka, R. Loonen, J. Hensen and J. Houben, Computational Building Performance Simulation For Integrated Design And Product Optimization, Sydney: Proceedings of Building Simulation 2011: 12th Conference of International Building Performance Simulation Association, 2011.
- [99] R. Loonen, M. Trcka, D. Cóstola and J. Hensen, "Performance simulation of climate adaptive building shells -," in *Proceedings of the System Simulation in Buildings Conference SSB2010*, Liège, 2010.
- [100] Agentschap NL, "Referentiegebouwen utiliteitsbouw," 2013. [Online]. Available: <http://www.agentschapnl.nl/sites/default/files/bijlagen/Referentiegebouwen%20utiliteitsbouw%20-%20Energieprestatie%20nieuwbouw%20-%20EPN.pdf>.
- [101] C. Reinhart, "Lightswitch-2002: a model for manual and automated control of electric lighting and blinds," *Solar Energy*, vol. 77, no. 1, p. 15–28, 2004.
- [102] A. Saltelli and I. Ebrary, Global sensitivity analysis: the primer, Wiley Online Library , 2008.
- [103] P. Heiselberg, H. Brohus, A. Hesselholt, H. Rasmussen, E. Seinre and S. Thomas, "Application of sensitivity analysis in design of sustainable buildings," *Renewable Energy*, vol. 34, no. 9, pp. 2030-2036, 2009.

[104] C. Gueymard and W. DuPont, "Spectral effects on the transmittance, solar heat gain, and performance rating of glazing systems," *Solar Energy*, vol. 83, no. 6, p. 940–953, 2009.