Development of surrogate models using artificial neural network for building shell energy labelling

Citation for published version (APA):

Melo, A. P., Costola, D., Lamberts, R., & Hensen, J. L. M. (2014). Development of surrogate models using artificial neural network for building shell energy labelling. *Energy Policy*, 69, 457-466.
<https://doi.org/10.1016/j.enpol.2014.02.001>

DOI:

[10.1016/j.enpol.2014.02.001](https://doi.org/10.1016/j.enpol.2014.02.001)

Document status and date:

Published: 01/01/2014

Document Version:

Accepted manuscript including changes made at the peer-review stage

Please check the document version of this publication:

- A submitted manuscript is the version of the article upon submission and before peer-review. There can be important differences between the submitted version and the official published version of record. People interested in the research are advised to contact the author for the final version of the publication, or visit the DOI to the publisher's website.
- The final author version and the galley proof are versions of the publication after peer review.
- The final published version features the final layout of the paper including the volume, issue and page numbers.

[Link to publication](#)

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal.

If the publication is distributed under the terms of Article 25fa of the Dutch Copyright Act, indicated by the "Taverne" license above, please follow below link for the End User Agreement:

www.tue.nl/taverne

Take down policy

If you believe that this document breaches copyright please contact us at:

openaccess@tue.nl

providing details and we will investigate your claim.

DEVELOPMENT OF SURROGATE MODELS USING ARTIFICIAL NEURAL NETWORK FOR BUILDING SHELL ENERGY LABELING

A.P. Melo^{1*}, D. Cóstola², R. Lamberts¹, J.L.M. Hensen²

¹Laboratory for Energy Efficiency in Buildings, Federal University of Santa Catarina, Brazil

²Building Physics and Systems, Eindhoven University of Technology, Eindhoven, The Netherlands

Abstract

Surrogate models are an important part of building energy labelling programs, but so far these models still present low accuracy, particularly in cooling dominated climates. The objective of this study is to evaluate the feasibility of using artificial neural network (ANN) to improve the accuracy of surrogate models for labelling purposes. ANN is applied to model the building stock of a city in Brazil, based on the results of extensive simulations using the high-resolution building energy simulation program EnergyPlus. Sensitivity and uncertainty analysis were carried out to evaluate the behaviour of the ANN model, and the variations in best and worst performance for several typologies were analysed in face of variation in input parameters and building characteristics. Results indicate that ANN can represent the interaction between input and output data in a vast and diverse building stock; with errors of $\pm 16\%$ for a confidence level of 90% of the cases. Sensitivity analysis shows that no single input parameter can be identified as the main responsible for the building energy performance. Uncertainty in building usage plays a major role in the building energy performance, as well as the facade area and the shell-to-floor. Results of this work may have a profound impact as ANN may be applied in the future in the regulation of many other countries, with further impact in the energy consumption and life quality of large amounts of people.

Keywords: artificial neural network, building energy simulation, surrogate model, low-resolution model, regulation, labelling, Latin Hypercube method.

* Corresponding author: A.P. Melo

Energy Efficiency in Buildings Laboratory, Federal University of Santa Catarina, P.O. box 476, 88040-900 Florianópolis, Brazil.

Tel.: +55 (48)3721 5184, Fax +55 (48)3721 5191, E-mail: apaula_melo@labeee.ufsc.br

1 Introduction

Building sustainability has become an important part of the building industry, particularly with the increasing demand for sustainability certifications, such as Leadership in Energy and Environmental Design (LEED) and Building Research Establishment Environmental Assessment Method (BREEAM). Thus, many countries are realizing the importance of having more energy efficient buildings and are developing local certifications programs to assist on the improvement of efficiency on their building stock, usually assigning labels to indicate the building energy performance (ASHRAE, 2010; CALIFORNIA, 2001; Dascalaki et al., 2012; Gram-Hanssen et al., 2007; Hernandez and Kenny, 2011; Klotz et al., 2010; Kong et al., 2012; Lee and Rajagopalan, 2008; Mlecnik et al., 2010; Wiel and McMahon, 2003; Yang et al., 2010b).

In most labelling programs, building energy simulation (BES) is a key element to assess building performance, both for new and existing building. It is therefore essential to have reliable BES programs in order to assign labels correctly, improving the public trust in the labelling program. High-resolution dynamic BES programs, such as EnergyPlus, EQuest, ESP-r, IES, EDSL-TAS, TRNSYS, VABI and others are usually accepted as reliable programs to assess building energy performance due to numerous validation exercises carried out over the last decades. However, these programs require expert users, detailed input and considerable computational resources depending on the building complexity. These requirements compromise the wide adoption of dynamic BES simulation in most building energy labelling programs, as labelling tools must be provide reliable results within affordable time and costs.

Dynamic BES is usually adopted for innovative and unusual buildings, while the majority of the building stock is labelled using low-resolution low-cost models. These models can be divided in two groups: (a) first-principle models, based on physical equations (such as the Fourier law) in combination with large simplifications of reality or; (b) surrogate models based on statistical modelling of large datasets produced using dynamic BES. While low-resolution first-principle models can provide reasonably accurate results in heat dominated climates, the complex dynamic in cooling dominated problems has proven to be difficult to capture using large simplifications of reality (Hensen and Radosevic, 2004). Therefore, surrogate models have been adopted in countries with cooling dominated buildings, such as in the Brazilian energy regulation for building labelling (BRASIL, 2009).

1 Surrogate models are simple and affordable to use, but the accuracy of results strongly depends on
2 the particularities of the building stock, climate, quality of the input data used and the modelling
3 technique adopted in the development of the surrogate model. The use of surrogate models for labelling
4 purposes is a new field, and recent results have shown that the accuracy of such models is still far from
5 ideal (Melo et al.). The current Brazilian energy regulation for commercial buildings, for example, adopts
6 a surrogate model with known accuracy issues, highlighting the importance of further research on this
7 topic. The importance of research in surrogate models for labelling purposes goes far beyond the
8 Brazilian case, as most developing countries with cooling dominated buildings face similar challenges in
9 their programs for energy conservation.

10 Among many techniques available for surrogate modelling, the Artificial Neural Network (ANN) has
11 been successfully used in many fields (Basheer and Hajmeer, 2000; Ben-Nakhi and Mahmoud, 2004;
12 Sung, 1998), and in particular for energy calculation in different levels (Ben-Nakhi and Mahmoud, 2004;
13 Ekici and Aksoy, 2009; Fonseca et al., 2013; González and Zamarreño, 2005; Karatasou et al., 2006; Li et
14 al., 2011; Magnier and Haghighat, 2010; Mahmoud and Ben-Nakhi, 2003; Neto and Fiorelli, 2008; Ruano
15 et al., 2006; Wong et al., 2010; Yang et al., 2005; Zemella et al., 2011). The capabilities and advantages
16 of ANN are widely known, such as the resistance to faults and noise (Bezdek and Pal, 1992). These
17 capabilities combined with the compact nature of the models makes ANN a strong candidate for energy
18 performance assessment tool in compulsory labelling programs in developing countries. However, to the
19 best knowledge of the authors, ANN has not yet being used for building energy labelling purposes.
20 Therefore, in this work we investigate the applicability of ANN as surrogate modelling technique for
21 building energy labelling purposes. This work is concentrated on the development of an accurate ANN
22 model based on extensive dynamic BES of the building stock. The labelling of commercial buildings in
23 the Brazilian city of Florianópolis is chosen as a case study, but the methods described in this paper are in
24 principle applicable to any other location, climate and building stock properties.

25 The paper is structured in 5 sections, as follows. Section 2 describes the methods and input
26 information adopted in this paper, comprising: (a) the key performance indicators addressed in the
27 Brazilian building energy regulation (BRASIL, 2009), (b) the building stock in Florianópolis which is the
28 subject of the labelling process, (c) the simulations using the dynamic BES program EnergyPlus, which
29 were later used as data source in the surrogate modelling process, and finally (d) the details on the ANN

development. Section 3 presents the results, firstly with a descriptive analysis of the developed ANN, followed by an evaluation of accuracy of ANN results. Section 3 also addresses the role of uncertainty in the building use pattern for the application of ANN in the labelling process. Moreover, Section 3 discusses the sensitivity of the ANN model as it is a fundamental aspect of modelling for labelling purposes. Section 4 discusses limitations of this research and further requirements for the use of ANN in labelling programs. The paper is then concluded in Section 5 with a summary of main findings.

2 Methodology

2.1. Certification goal and approach

The development of any surrogate model for labelling purposes shall be preceded by a clear definition of goals for this model. In the current Brazilian building energy regulation, this goal is clearly the reduction of energy consumption (in particular by heating, cooling and air conditioning (HVAC) systems) in the whole building stock. This approach is rather different from high-performance building certification such as LEED and BREEAM, where only a small fraction of innovative building is subject to evaluation. In this sense, the Brazilian regulation is close to the approach of several countries in the implementation of the European Energy Performance of Buildings Directive (EPBD), where low-resolution models estimate the performance of the majority of buildings in Europe.

The Brazilian regulation assumes the existence of HVAC systems, hence comfort is guaranteed and consequently comfort calculations are excluded from the surrogate model output. The surrogate model shall provide an indication of the performance of the shell (i.e. facades and roof), and a fixed coefficient of performance equal to 3.20 is assumed in all analysis. The importance of these assumptions is later discussed in the paper. Electricity energy consumption at the building site is reported in kWh/m²y. Brazilian energy matrix is fundamentally based on hydroelectric power, therefore CO₂ emissions, commonly used in other countries (José Vinagre Díaz et al.), are not the primary performance indicator for the building sector. In a higher level, the purpose of the existing regulation is to reduce the increasing pressure for power plants driven by fossil fuels.

Brazil, as most countries, was divided in a number of zones with similar climate conditions for regulation purposes. This study addresses only the climate zone where the city of Florianópolis is located, and the next section describes the existing building stock of this city, which is the subject of the labelling process.

2.2. Relevant characteristics of the building stock regarding the certification process

A proper description of the building stock is fundamental in any labelling process, and particularly in the development of surrogate models. In many cases detail information is not available, and large assumptions have to be made. This is the case in this section, where the information is based on a preliminary survey of characteristics of the building stock. The information provided here shall be improved in the future; nevertheless the methodology related to the use of ANN in the labelling process remains useful and, probably valid as well (although new information on the building stock requires a new validated ANN).

Buildings typologies with different constructed areas, numbers of floors, conditioned areas, and other characteristics, were taken into account to cover most of the characteristics present in the buildings located in Florianópolis, Brazil. Moreover, it was assumed that the typologies have the principal facade to North-South or East-West. A total of sixteen building typologies were adopted, taking into account small and large offices/stores, vertical offices and hotels (main dimensions in Appendix and in Figure 1). The main buildings properties are described in Table 1, where each property may assume a number of predefined discreet values chosen to represent the majority of the complex existing (and future) building stock.

Some relevant characteristics of a building may not be under the control of designers, or may be unknown during the design phase. Characteristics such as “internal load density” and “patterns of use” were considered as uncertainties in the development of the surrogate model using ANN. The same applies for infiltration rate, which is in a sense a design variable that can be improved by careful detailing. However, it is not common practice in Brazil to perform detailed studies on infiltration in commercial buildings; therefore infiltration is also considered as a source of uncertainty. Uncertainty parameters and their values are listed in Table 2.

In addition to the sixteen building typologies used in the development and validation of ANN, four extra building typologies were chosen to allow an additional quality assurance test on the accuracy of ANN results (as described in the Appendix).

2.3. High-resolution simulation of the building stock performance

The energy performance of each of the sixteen typologies in the building stock was simulated using the BES program EnergyPlus version 6.0 (2010). EnergyPlus is a state-of-the art BES program with

extensive validation. Simulations were carried out using ideal control for the HVAC system. In the cases with fixed external shading device, this device was modelled explicitly using an external surface which is considered in the solar gains calculation engine of EnergyPlus.

Latin Hypercube Sampling was adopted to generate design variations based on values in Tables 1 and 2 (de Wit and Augenbroe, 2002; Olsson et al., 2003; Xu et al., 2005). This method allows a reduction in the number of cases generated, without a reduction in the quality of the results (Mckay et al., 1979). A total of 200 samples were created for each of the sixteen typologies, in a total of 3200 cases simulated in EnergyPlus (raw data file with all input and output will be available for download in the journal website). The interaction between different parameters in the Latin Hypercube method took place using scripts developed by Ref. (Hoes, 2007), which uses the programs SimLab (2011) and MatLab (2011). In each case, all facades have the same properties. Each building floor was modelled as a single zone.

2.4. Surrogate modelling using ANN

The EasyNN-Plus program was used to develop the ANN model. The structure of the neural network was set as feed-forward, in which the output layer connects only to the previous layer. ANN training used 50% of the 3200 cases and 25% of cases were selected for the validation set. The other 25% of cases were selected to verify the performance of the network and these cases were not part of the training and validation. All cases were randomly selected by the EasyNN-Plus program. The parameters considered the input layer for the neural network training can be seen in Tables 1 and 2, combined with other parameters describing the geometry of the buildings. A total of nineteen input parameters were used in the development of the ANN model (see Appendix).

Several configurations of ANN were tested in order to find the best performing combination of number of hidden layers and nodes per layer. In all configurations, Eq. (1) was used as activation function to smooth the output signal of each node:

$$s(x) = 1/(1 + e^{-x}) \quad (1)$$

where x is the sum of the weighted input of each previous node plus the bias of the node itself.

ANN results were evaluated based on the coefficient of determination (R^2), the mean bias error - MBE ($\bar{e}$) and the error standard deviation, also known as root-mean squared error RMSE (σ_e). The frequency of errors between EnergyPlus results and neural network results were also analysed using histograms.

The role of uncertainty (from Table 2) in the ANN predictions was investigated with the support of additional ANNs. In these additional ANN, the uncertain parameters were not included as input variable. A total of four additional ANNs were constructed for this purpose: a) one ANN with all nineteen input parameters except the infiltration rate, b) one without pattern of use, c) one without internal load density, and d) one without any of the uncertain parameters from Table 2. The accuracy of these additional ANNs was then compared to the accuracy of the original ANN (which includes all nineteen input parameters).

Once the role of uncertainty was clarified, the sensitivity of the ANN to different input parameters was investigated. For this purpose, ANN was used to calculate 39 additional variations for each one of the 3200 original simulation cases. In these variations, only one parameter was change at a time using the 39 discreet input values from Table 1. This procedure allowed the calculation of individual changes in the output due to individual changes in each one of the inputs. Uncertainty was not taken into account in the sensitivity analysis, and the following values were assumed: infiltration of 1 ACH, pattern of use of 11 hours and ILD of 35 W/m².

Finally, results from sensitivity analysis were used to define scenarios with the best and worst performance for each of the sixteen typologies. These scenarios are useful to clarify the performance boundaries for each case, which is essential information to define the appropriate ranges for each energy label. ANN accuracy is then discussed in face of the possible variation in performance for each typology.

3 Results

3.1. Optimum ANN configuration

From the several configurations of ANN tested in this work, the best performing ANN to model the energy performance of this building stock has one hidden layer with nine nodes. Weights, biases, maximum and minimum values are provided in the appendix. Such simple ANN can be represented in a few equations, and a general formulation of an ANN with one hidden layer and one output node is given in eq. 2 and 3:

$$E_{CON} = E_{MIN} + (E_{MAX} - E_{MIN}) \cdot \left[1 / (1 + e^{-NET_{input}}) \right] \quad (2)$$

$$NETinput = \sum_{n=1}^H \left\{ \left[1 / \left(1 + e^{-\left\{ \sum_{i=1}^X \left[\left(\frac{x_i - x_{MIN_i}}{x_{MAX_i} - x_{MIN_i}} \right) \cdot W_{i,n} \right] + b_n} \right\}} \right) \right] \cdot W_{n,S} \right\} + b_S \quad (3)$$

where E_{con} is the energy consumption, E_{max} and E_{min} are the maximum and minimum values of energy consumption used in the ANN training, H is the number of nodes in the hidden layer, X is the number of input nodes, x_i are the input values for calculation, x_{MAX_i} and x_{MIN_i} are the maximum and minimum values of the input used in the ANN training, $W_{i,n}$ and $W_{n,s}$ are the weight values for each pair of nodes and b_n and b_s are the biases of hidden and output nodes respectively.

3.2. ANN results and error analysis

Figure 2A shows a comparison of the reference energy consumption calculated using EnergyPlus and the output of the trained ANN, where a general good agreement can be observed. This agreement can be better quantified by analysing the difference between EnergyPlus and ANN results, as shown in the histogram in Figure 2B. This histogram shows that the majority of differences between the EnergyPlus and ANN results are in the range of ± 10 kWh/m²y (84% of cases). This level of confidence is in line with calculations based on normal distribution, as follows. The mean error and the standard deviation for the cases were -3.7 kWh/m²y and 8.7 kWh/m²y, respectively. The mean error is quite small when compared to the magnitude of the energy consumption calculated (from 30 to 200 kWh/m².y). Assuming a normal distribution of errors, the standard deviation indicates a confidence interval of ± 14.2 kWh/m² in the results (for a confidence level of 90% of the cases, equivalent to 1.6 standard deviations). In relative terms, ANN results have a confidence interval of $\pm 16\%$ of the calculated value (also for a confidence level of 90%).

Results in Figure 2 are in line with the results for the four extra building typologies used for additional quality assurance of the ANN model (Table 3). In these four extra buildings the differences between EnergyPlus and ANN results are inside the confidence for most cases. This section demonstrated that the ANN can represent the relationship between input and output data, taking into account the large variation in the typologies and properties addressed in this study. The next sub-section discusses the impact of uncertainties in the input during the development of the ANN models for building energy labelling.

3.3. Role of uncertainty in the definition of ANN input parameters

The influence of three inputs data (patterns of use, infiltration and internal load density) into the performance of the ANN model was analysed. Four additional ANNs were constructed for this purpose as described in Section 2.4. Figure 3 shows histograms of errors in each one of these ANNs, where the standard deviation of the errors is also indicated. Figure 3A, 3B and 3C show large spread in the results. In the three cases the standard deviation of errors is twice higher than in the ANN described in the previous section. Figure 3D shows errors in the predictions of the ANN three times higher when patterns of use, infiltration and internal load density are not included as input values. These results demonstrate the importance of these parameters in the energy consumption of buildings and in the ANN output. These results are also in line with previous research which demonstrated the importance of these variables in other similar applications (Hassouneh et al., 2012; Kwok and Lee, 2011; Probst, 2004; Shukuya and Matsunawa, 1988; Wan and Yik, 2004). All of these parameters should therefore be considered in the ANN for labelling purposes to assure its precision.

3.4. Sensitivity of ANN results to each input parameter

The proper sensitivity of the ANN model to various input parameters is essential for building energy labelling. Energy consumption results by ANN should react to variations in input, both in qualitative terms (such as increase in energy consumption due to increase in WWR) and in quantitative terms (based on the magnitude of the change in consumption to variations in WWR). Figure 4 shows the variation of performance calculated using the ANN model for different input variables, for the case of a one-storey small office buildings. Most input parameters have a positive correlation, i.e. an increase in their value leads to an increase in the model output. This is in accordance to expectation, as higher values of WWR, SHGC, solar absorption and thermal transmittance are all associated with higher energy consumption for cooling. Vertical shading angle (AVS) is the only parameter with negative correlation, as an increase in shading reduces the energy consumption of the building. Results in this figure also show the proper behaviour of ANN regarding input values different from discreet input on Table 1, as some additional input values used in the construction of this figure were different from values in Table 1. The maximum and minimum values for each input were, nevertheless, the same ones used in the development of the ANN model. In Figure 4, the performance of this specific typology is between 71 to 86 kWh/m²y, indicating a small variation in the performance as the higher value is only 20% larger than the smaller

one. However, Figure 4 only shows the effect of one input value changing at a time, therefore combined effects are not taken into account.

Results in Figure 4 are only applicable for a particular building. Figure 5, however, shows the average sensitivity for all 200 variations of each of the sixteen typologies. Results in Figure 5 show the absolute average change in the energy consumption for the correspondent change in one of the input parameters. For example, an increase of 1 W/m²K in the U-value of wall leads to a correspondent increase of 1 kWh/m².y in the calculated energy consumption. The order of magnitude of changes in the results indicates that no single parameter is responsible for large changes in the calculation output. Sensitivity results reinforce the importance of integrated assessment of building energy performance, as the output is function of complex interaction between the relevant input parameters.

3.5. Boundary of the performance range for various typologies

Based on the sensitivity results of Figure 5, two scenarios were defined with input parameters for the best and worst shells regarding energy performance. These scenarios define the boundary performance values for a building, assuming the constraints used in this paper. The best and worst performing shells were defined using the maximum and minimum values of each input parameters, arranged according to the direction of the sensitivity in Figure 5. In the best scenario, for example, all variables with positive correlation assume minimum value, and the one with negative correlation assumes the maximum value. ANN results for the best and worst scenarios of each of the sixteen typologies are shown in Figure 6. Typologies are ordered by the minimum energy consumption value (see typology ID in the appendix).

Regarding the best performing shells, it is noticeable that values largely vary among the typologies, and in many cases the worst performing shell of one typology still have lower energy consumption than the best performing shell of another typology. The behaviour of best and worst scenarios if further analysed in Figure 7. Figure 7A shows the clear correlation between the best performance and the total facade area, where large facades (such as in cases 15 and 16 in figure 6) have the highest value for the best performing energy performance. This ANN result suggests that buildings with small facades will in general perform better than the ones with large facades.

Regarding the range of variation between best and worst shells, Figure 6 also shows a large variation between typologies. In some typologies, the best and the worst shells have similar performance (such as in typology 12), while in other typologies the worst design has up to 150% higher energy consumption

(such as in typology 4). This variation in the performance range of each typology is closely related to the ratio between conditioned volume and the area of the building shell (i.e. facades and roof), as demonstrated in Figure 7B. A larger shell-to-floor ratio indicates a higher degree of interaction with the outdoor environment; therefore changes in the facade design have larger impact in the building energy performance.

This preliminary analysis of ANN results highlights the challenges on defining acceptable performance targets for the whole building stock, as the best performing facade leads to different performance depending on other building characteristics.

The behaviour of the surrogate model for labelling purposes must be carefully evaluated in face of energy policy targets, as the required accuracy depends on the performance range of each typology. In cases where the best and worst performances are quite similar, the surrogate model must have high accuracy in order to differentiate correctly these two scenarios. However, one may argue that cases where the performance range is too narrow shall not be addressed by energy conservation measures, as the social and economic costs will not lead to high energy savings. These questions are beyond the scope of this paper, and in spite of these concerns, this paper demonstrates the applicability of ANN models for energy labelling purposes, as ANN can predict the energy consumption of a large and heterogeneous building stock under uncertainty.

4 Discussion

4.1. Limitations of this study

This paper is based on a large amount of assumptions, and some of them are briefly discussed in this section.

The definition of relevant input parameters and the range for these parameters is essential for the success of the labelling program. This paper adopts a larger number of input parameters than the currently used model in the Brazilian regulation. In spite of this improvement, other parameters with known impact in energy performance were not included, such as thermal mass. Thermal mass was omitted because currently commercial buildings in Brazil have very little variation in this parameter, but this and other input must be considered if the methods described in this paper are applied for other countries or other building functions.

1 Labelling programs must promote the adoption of proven energy conservation measures. However,
2 many of these measures were not included in this paper, such internal manually operated shading devices
3 and smart shading devices (both internal and external) (Aste et al., 2012; Baldinelli, 2009; Inoue, 2003;
4 Inoue et al., 2008; van Moeseke et al., 2007). At the current stage, the goal was to investigate the
5 applicability of ANN in the development of the surrogate model for labelling. This paper demonstrates
6 the potential of ANN to model the building stock, but the ANN model presented here requires
7 improvements in order to handle a variety of proven energy conservation measures. Moreover, advanced
8 features shall be included in the future as well, such as: climate adaptative building shells (Gosling et al.,
9 2013; Loonen et al., 2013), adaptable thermal storage (Hoes et al., 2011; Parameshwaran et al., 2012;
10 Soares et al., 2013), integration of thermal and lighting performance of the shell (Nielsen et al., 2011).

11 This paper is focused on the energy performance of the building shell; therefore variations in the
12 efficiency of the HVAC system are not included in the model. Known strategies for energy conservation
13 in the HVAC level shall be included in the model in the future, such as night ventilation (Artmann et al.,
14 2008; Geros et al., 2005; Pfafferott et al., 2003; Pfafferott et al., 2004; Wang et al., 2009), thermally
15 activated building systems (de Wit and Wisse, 2012; Lehmann et al., 2007; Pomianowski et al., 2012;
16 Rijksen et al., 2010; Saelens et al., 2011) and of course systems with higher performance such as ground
17 coupled heat pumps systems (Florides et al., 2011; Hackel and Pertzborn, 2011; Yang et al., 2010a; Zhai
18 et al., 2011).

19 Cooling dominated buildings can be divided in three groups regarding the HVAC approach adopted:
20 naturally ventilated, artificially conditioned and building operating in mixed-mode. Comfort requirements
21 are different in buildings of each group (Brager and de Dear, 1998; Cândido et al., 2011; de Dear and
22 Brager, 2002; Kim and de Dear, 2012), and so is the optimum building shell. This paper only addresses
23 fully conditioned buildings, therefore the ANN model cannot be used to analyse buildings of the other
24 two groups. Future work should investigate the applicability of ANN models to evaluate the performance
25 of naturally ventilated buildings and mixed-mode buildings, as these buildings many more degrees of
26 freedom when compared to fully conditioned ones.

27 This paper is based on a limited description of the building stock, and results are intrinsically
28 connected to this description. Further work is required on describing the building stock and trends in new
29 constructions. Moreover, a comprehensive and systematic program of building energy monitoring is

essential to support the development of surrogates models for labelling programs, as done in many develop economies (D&R International, 2012; Dall'O' et al., 2012; Dascalaki et al., 2010; Fracastoro and Serraino, 2011; Ravetz, 2008; Theodoridou et al., 2011), In addition, the proportion of cases of different typologies in the building stock must be quantified, as the surrogate modelling process is highly influenced by the amount of buildings with similar properties. For example, in this paper a large number of small commercial buildings was considered, while just a few high-rise buildings were taken into account. This relation between number of small and high-rise buildings is valid for the city of Florianópolis, but this ratio should be properly defined for each location where ANN models are applied.

The accuracy of surrogate models usually vary within the cases modelled, and this aspect was not taken into account in this paper. The occurrence of particularly higher errors in specific typologies may compromise the adoption of surrogate models in the labelling program as a specific group of user will systematically face large discrepancies between results of the surrogate model and results from high-resolution models. Therefore future work shall evaluate cases with extreme errors as well as the error in different clusters of typologies with similar properties. Moreover, analysis of error in benchmark cases, such as the BESTEST, must be performed.

4.2. Comparison with the surrogate model currently used in the Brazilian building energy labelling program

The surrogate model currently used in the Brazilian regulation was developed in the last decade and represented a major step forward in the Brazilian program for energy conservation in buildings (Carlo and Lamberts, 2010). However, limitations of this surrogate model were known even before the publication of the Brazilian regulation. Previous study on the accuracy of the current surrogate model concluded that results are up to 60% outside the limits defined in the BESTEST (Melo et al., 2012b). Regarding the accuracy, the ANN model proposed in this paper shows large improvements when compared to the current surrogate model in the Brazilian regulation.

Another limitation of the current model is the lack of support for several relevant input data for energy performance, such as the thermal transmittance which is assumed as a fixed value (Carlo, 2008; Yamakawa and Westphal, 2011). The proposed ANN shows the capability of handling a large and diverse number of input variables. Moreover, the surrogate model currently used in the Brazilian regulation is divided in two sub-models, one for large and one for small buildings, in order to improve accuracy in the

1 results (which still show large deviations from the results of high-resolution dynamic BES (ASHRAE,
2 2004)). The ANN model proposed in this paper can describe the whole building stock in one simple and
3 straightforward set of equations (Eq. 2 and 3).

4 One of the main limitations presented in the current surrogate model in the Brazilian regulation is the
5 very limited description of the building stock used in the simulations (Carlo and Lamberts, 2008; Melo et
6 al., 2012b). The present study extended the amount of typologies used to describe the building stock but
7 further work is required on this topic.

8 So far, the social and economic costs of energy conservation measures were not compared with the
9 benefits obtained by these measures in the Brazilian energy conservation program. The ANN model
10 proposed in this paper allows such analysis, providing a valuable tool in the definition of policies and
11 negotiations with stake-holders.

12 The present paper demonstrates the importance of uncertainties in the energy performance of
13 commercial buildings in Brazil. However, uncertainties in building usage and its inclusion in labelling
14 programs require further investigation, not only in Brazil but also in the international context (Cantin et
15 al., 2007; Masoso and Grobler, 2010; Nunes et al.; Yu et al., 2011). In the same line, the inclusion of
16 further performance aspects, such as daylight usage and view to the outdoor environment, is essential to
17 avoid misuse of the labelling program, such as the promotion of buildings with minimum or no
18 fenestration leading to poor overall environmental indoor quality.

19 **5 Conclusions and implications for energy policy**

20 The main objective of this study was to investigate the use of artificial neural networks to estimate the
21 energy consumption of commercial buildings to support building shell labelling programs. Based on the
22 results presented in this paper, the following conclusions can be drawn:

- 23 • The development of the low-resolution model by applying the artificial neural network technique
24 could represent the interaction between input and output data; with errors of $\pm 16\%$ for a
25 confidence level of 90% of the cases;
- 26 • The parameters of internal load density, patterns of use and infiltration presented a significant
27 influence in the artificial neural network results, and should therefore be included in the labelling
28 program;

- Sensitivity analysis shows that no single input parameter can be identified as the main responsible for the building energy performance, but rather the combination of different parameter play a role in the building performance;
- The range of performance defined by the best and worst building shells have large variation among the typologies evaluates, as well as the minimum energy consumption of the best building shell for each typology;
- The facade area and the shell-to-floor ratio play a significant role in the energy performance of the typologies analysed.

These results have some direct implications for energy policy:

- Countries adopting linear regression models in energy labelling of building shells should replace these models by ANN models, due to the simplicity and improved flexibility and accuracy of ANN.
- Policy makers involved in energy labelling of building shells should be aware that sometimes the shell plays a secondary role in the building energy performance. Building aspect ratio and usage may be dominant factors, and in this case any policies focused only on building shell properties will provide limited energy savings.
- Social, political, environmental and economic costs of different energy policies for energy conservation in buildings shall be compared to the actual gain in energy performance using ANN models of building shells such as the one presented in this paper.

Results of this work may have a profound impact in the building energy regulation in many countries, as artificial neural network may be applied to evaluate energy conservation measures improving the life quality of large amounts of people.

Acknowledgements

The work reported in this paper was supported by The Brazilian Federal Agency for Support and Evaluation of Graduate Indication – CAPES, Proc. no 2335/10-7 and Eletrobras - Centrais Elétricas Brasileiras S.A.

References

- Artmann, N., Manz, H., Heiselberg, P., 2008. Parameter study on performance of building cooling by night-time ventilation. *Renewable Energy* 33, 2589-2598.
- ASHRAE, 2004. ANSI/ASHRAE Standard 140-2004: Standard method of test for the evaluation of building energy analysis computer programs, ASHRAE, Atlanta, 2004.
- ASHRAE, 2010. ANSI/ASHRAE Standard 90.1-2010: Energy standard for building except low-rise residential buildings, ASHRAE, Atlanta, 2010.
- Aste, N., Adhikari, R.S., Del Pero, C., 2012. An Algorithm for Designing Dynamic Solar Shading System. *Energy Procedia* 30, 1079-1089.
- Baldinelli, G., 2009. Double skin façades for warm climate regions: Analysis of a solution with an integrated movable shading system. *Building and Environment* 44, 1107-1118.
- Basheer, I.A., Hajmeer, M., 2000. Artificial neural networks: fundamentals, computing, design, and application. *Journal of Microbiological Methods* 43, 3-31.
- Ben-Nakhi, A.E., Mahmoud, M.A., 2004. Cooling load prediction for buildings using general regression neural networks. *Energy Conversion and Management* 45, 2127-2141.
- Bezdek, J.C., Pal, S.K., 1992. Fuzzy models for pattern recognition: methods that search for structures in data, New York: IEEE Press.
- Brager, G.S., de Dear, R.J., 1998. Thermal adaptation in the built environment: a literature review. *Energy and Buildings* 27, 83-96.
- BRASIL, 2009. Portaria 185, de 22 de junho de 2009. Regulamento de Avaliação da Conformidade do Nível de Eficiência Energética de Edifícios Comerciais, de Serviços e Públicos (in Portuguese), Instituto Nacional de Metrologia, Normalização e Qualidade Industrial (INMETRO), Rio de Janeiro, 2009.
- CALIFORNIA, 2001. Energy efficiency standards for residential and nonresidential buildings, Sacramento.
- Cândido, C., de Dear, R., Lamberts, R., 2011. Combined thermal acceptability and air movement assessments in a hot humid climate. *Building and Environment* 46, 379-385.
- Cantin, R., Mourtada, A., Guarracino, G., Adra, N., Nasser, M., Maamari, F., 2007. Scenarios of application of energy certification procedure for residential buildings in Lebanon. *Energy Policy* 35, 3167-3178.
- Carlo, J., Lamberts, R., 2008. Development of envelope efficiency labels for commercial buildings: Effect of different variables on electricity consumption. *Energy and Buildings* 40, 2002-2008.
- Carlo, J.C., 2008. Development of a methodology for evaluating the energy efficiency of non-residential buildings envelope (in Portuguese). Federal University of Santa Catarina, Florianópolis.
- Carlo, J.C., Lamberts, R., 2010. Parameters and methods adopted in the energy efficiency labelling regulation for buildings – part 1: prescriptive method (in Portuguese). *Revista Ambiente Construído* 10, 7-26.
- D&R International, L., 2012. 2011 Buildings Energy Data Book. Buildings Technologies Program, Energy Efficiency and Renewable Energy, U.S. Department of Energy.
- Dall'O', G., Galante, A., Torri, M., 2012. A methodology for the energy performance classification of residential building stock on an urban scale. *Energy and Buildings* 48, 211-219.
- Dascalaki, E.G., Balaras, C.A., Gaglia, A.G., Drousa, K.G., Kontoyiannidis, S., 2012. Energy performance of buildings—EPBD in Greece. *Energy Policy* 45, 469-477.
- Dascalaki, E.G., Drousa, K., Gaglia, A.G., Kontoyiannidis, S., Balaras, C.A., 2010. Data collection and analysis of the building stock and its energy performance—An example for Hellenic buildings. *Energy and Buildings* 42, 1231-1237.
- de Dear, R.J., Brager, G.S., 2002. Thermal comfort in naturally ventilated buildings: revisions to ASHRAE Standard 55. *Energy and Buildings* 34, 549-561.
- de Wit, A.K., Wisse, C.J., 2012. Hydronic circuit topologies for thermally activated building systems – design questions and case study. *Energy and Buildings* 52, 56-67.
- de Wit, S., Augenbroe, G., 2002. Analysis of uncertainty in building design evaluations and its implications. *Energy and Buildings* 34, 951-958.
- DOE, 2010. EnergyPlus program. Version 6.0. U.S. Department of Energy.

- 1 Ekici, B.B., Aksoy, U.T., 2009. Prediction of building energy consumption by using artificial neural
2 networks. *Advances in Engineering Software* 40, 356-362.
- 3 Florides, G.A., Pouloupatis, P.D., Kalogirou, S., Messaritis, V., Panayides, I., Zomeni, Z., Partasides, G.,
4 Lizides, A., Sophocleous, E., Koutsoumpas, K., 2011. The geothermal characteristics of the
5 ground and the potential of using ground coupled heat pumps in Cyprus. *Energy* 36, 5027-5036.
- 6 Fonseca, R.W.d., Didoné, E.L., Pereira, F.O.R., 2013. Using artificial neural networks to predict the
7 impact of daylighting on building final electric energy requirements. *Energy and Buildings* 61, 31-
8 38.
- 9 Fracastoro, G.V., Serraino, M., 2011. A methodology for assessing the energy performance of large scale
10 building stocks and possible applications. *Energy and Buildings* 43, 844-852.
- 11 Geros, V., Santamouris, M., Karatasou, S., Tsangrassoulis, A., Papanikolaou, N., 2005. On the cooling
12 potential of night ventilation techniques in the urban environment. *Energy and Buildings* 37, 243-
13 257.
- 14 González, P.A., Zamarreño, J.M., 2005. Prediction of hourly energy consumption in buildings based on a
15 feedback artificial neural network. *Energy and Buildings* 37, 595-601.
- 16 Gosling, J., Sassi, P., Naim, M., Lark, R., 2013. Adaptable buildings: A systems approach. *Sustainable
17 Cities and Society* 7, 44-51.
- 18 Gram-Hanssen, K., Bartiaux, F., Michael Jensen, O., Cantaert, M., 2007. Do homeowners use energy
19 labels? A comparison between Denmark and Belgium. *Energy Policy* 35, 2879-2888.
- 20 Hackel, S., Pertzborn, A., 2011. Effective design and operation of hybrid ground-source heat pumps:
21 Three case studies. *Energy and Buildings* 43, 3497-3504.
- 22 Hassouneh, K., Alshboul, A., Al-Salaymeh, A., 2012. Influence of infiltration on the energy losses in
23 residential buildings in Amman. *Sustainable Cities and Society* 5, 2-7.
- 24 Hensen, J., Radošević, M., 2004. Teaching building performance simulation - some quality assurance
25 issues and experiences, *Proc.PLEA 2004 - the 21st Conference on Passive and Low Energy
26 Architecture*. Technische Universiteit Eindhoven, Eindhoven, pp. 1209-1214.
- 27 Hernandez, P., Kenny, P., 2011. Development of a methodology for life cycle building energy ratings.
28 *Energy Policy* 39, 3779-3788.
- 29 Hoes, P.-J., 2007. Gebruikersgedrag in gebouwsimulaties van eenvoudig tot geavanceerd
30 gebruikersgedragmodel (in Dutch). Technische Universiteit Eindhoven, Eindhoven.
- 31 Hoes, P., Trcka, M., Hensen, J.L.M., Hoekstra Bonnema, B., 2011. Investigating the potential of a novel
32 low-energy house concept with hybrid adaptable thermal storage. *Energy Conversion and
33 Management* 52, 2442-2447.
- 34 Inoue, T., 2003. Solar shading and daylighting by means of autonomous responsive dimming glass:
35 practical application. *Energy and Buildings* 35, 463-471.
- 36 Inoue, T., Ichinose, M., Ichikawa, N., 2008. Thermotropic glass with active dimming control for solar
37 shading and daylighting. *Energy and Buildings* 40, 385-393.
- 38 José Vinagre Díaz, J., Richard Wilby, M., Belén Rodríguez González, A., Setting up GHG-based energy
39 efficiency targets in buildings: The Ecolabel. *Energy Policy*.
- 40 Karatasou, S., Santamouris, M., Geros, V., 2006. Modeling and predicting building's energy use with
41 artificial neural networks: Methods and results. *Energy and Buildings* 38, 949-958.
- 42 Kim, J., de Dear, R., 2012. Impact of different building ventilation modes on occupant expectations
43 of the main IEQ factors. *Building and Environment* 57, 184-193.
- 44 Klotz, L., Mack, D., Klapthor, B., Tunstall, C., Harrison, J., 2010. Unintended anchors: Building rating
45 systems and energy performance goals for U.S. buildings. *Energy Policy* 38, 3557-3566.
- 46 Kong, X., Lu, S., Wu, Y., 2012. A review of building energy efficiency in China during “Eleventh Five-
47 Year Plan” period. *Energy Policy* 41, 624-635.
- 48 Kwok, S.S.K., Lee, E.W.M., 2011. A study of the importance of occupancy to building cooling load in
49 prediction by intelligent approach. *Energy Conversion and Management* 52, 2555-2564.
- 50 Lee, S.E., Rajagopalan, P., 2008. Building energy efficiency labeling programme in Singapore. *Energy
51 Policy* 36, 3982-3992.
- 52 Lehmann, B., Dorer, V., Koschenz, M., 2007. Application range of thermally activated building systems
53 tabs. *Energy and Buildings* 39, 593-598.
- 54 Li, K., Su, H., Chu, J., 2011. Forecasting building energy consumption using neural networks and hybrid
55 neuro-fuzzy system: A comparative study. *Energy and Buildings* 43, 2893-2899.

- 1 Loonen, R.C.G.M., Trčka, M., Cóstola, D., Hensen, J.L.M., 2013. Climate adaptive building shells: State-
2 of-the-art and future challenges. *Renewable and Sustainable Energy Reviews* 25, 483-493.
- 3 Magnier, L., Haghighat, F., 2010. Multiobjective optimization of building design using TRNSYS
4 simulations, genetic algorithm, and Artificial Neural Network. *Building and Environment* 45, 739-
5 746.
- 6 Mahmoud, M.A., Ben-Nakhi, A.E., 2003. Architecture and performance of neural networks for efficient
7 A/C control in buildings. *Energy Conversion and Management* 44, 3207-3226.
- 8 Masoso, O.T., Grobler, L.J., 2010. The dark side of occupants' behaviour on building energy use. *Energy*
9 *and Buildings* 42, 173-177.
- 10 MATLAB, 2011. The language of technical computing. Mathworks Inc. .
- 11 Mckay, M.D., Conover, W.J., Beckman, R.J., 1979. A Comparison of Three Methods for Selecting
12 Values of Input Variables in the Analysis of Output from a Computer Code. *Technometrics* 21,
13 239-245.
- 14 Melo, A.P., Cóstola, D., Lamberts, R., Hensen, J.L.M., 2012a. Assessing the accuracy of a simplified
15 building energy simulation model using BESTEST: The base case of Brazilian regulation. *Energy*
16 *and Buildings* 45, 219-228.
- 17 Melo, A.P., Cóstola, D., Lamberts, R.L., Hensen, J.L.M., 2012b. Assessing the accuracy of a simplified
18 building energy simulation model using BESTEST: the case study of Brazilian regulation. *Energy*
19 *and Buildings* 45, 219-228.
- 20 Mlecnik, E., Visscher, H., van Hal, A., 2010. Barriers and opportunities for labels for highly energy-
21 efficient houses. *Energy Policy* 38, 4592-4603.
- 22 Neto, A.H., Fiorelli, F.A.S., 2008. Comparison between detailed model simulation and artificial neural
23 network for forecasting building energy consumption. *Energy and Buildings* 40, 2169-2176.
- 24 NeuralPlannerSoftware, EasyNN plus, 14.0d ed. Neural Planner Software Ltd,2010.
- 25 Nielsen, M.V., Svendsen, S., Jensen, L.B., 2011. Quantifying the potential of automated dynamic solar
26 shading in office buildings through integrated simulations of energy and daylight. *Solar Energy*
27 85, 757-768.
- 28 Nunes, P., Lerer, M.M., Carrilho da Graça, G., Energy certification of existing office buildings: Analysis
29 of two case studies and qualitative reflection. *Sustainable Cities and Society*.
- 30 Olsson, A., Sandberg, G., Dahlblom, O., 2003. On Latin hypercube sampling for structural reliability
31 analysis. *Structural Safety* 25, 47-68.
- 32 Parameshwaran, R., Kalaiselvam, S., Harikrishnan, S., Elayaperumal, A., 2012. Sustainable thermal
33 energy storage technologies for buildings: A review. *Renewable and Sustainable Energy Reviews*
34 16, 2394-2433.
- 35 Pfafferoth, J., Herkel, S., Jäschke, M., 2003. Design of passive cooling by night ventilation: evaluation of
36 a parametric model and building simulation with measurements. *Energy and Buildings* 35, 1129-
37 1143.
- 38 Pfafferoth, J., Herkel, S., Wambsganß, M., 2004. Design, monitoring and evaluation of a low energy
39 office building with passive cooling by night ventilation. *Energy and Buildings* 36, 455-465.
- 40 Pomianowski, M., Heiselberg, P., Jensen, R.L., 2012. Dynamic heat storage and cooling capacity of a
41 concrete deck with PCM and thermally activated building system. *Energy and Buildings* 53, 96-
42 107.
- 43 Probst, O., 2004. Cooling load of buildings and code compliance. *Applied Energy* 77, 171-186.
- 44 Ravetz, J., 2008. State of the stock—What do we know about existing buildings and their future
45 prospects? *Energy Policy* 36, 4462-4470.
- 46 Rijksen, D.O., Wisse, C.J., van Schijndel, A.W.M., 2010. Reducing peak requirements for cooling by
47 using thermally activated building systems. *Energy and Buildings* 42, 298-304.
- 48 Ruano, A.E., Crispim, E.M., Conceição, E.Z.E., Lúcio, M.M.J.R., 2006. Prediction of building's
49 temperature using neural networks models. *Energy and Buildings* 38, 682-694.
- 50 Saelens, D., Parys, W., Baetens, R., 2011. Energy and comfort performance of thermally activated
51 building systems including occupant behavior. *Building and Environment* 46, 835-848.
- 52 Shukuya, M., Matsunawa, K., 1988. A nomograph for estimating annual cooling and heating energy
53 requirements in buildings dominated by internal loads. *Energy and Buildings* 12, 207-218.
- 54 SIMLAB, 2011. SIMLAB - Sensitivity analysis. SimLab Soft.

- 1 Soares, N., Costa, J.J., Gaspar, A.R., Santos, P., 2013. Review of passive PCM latent heat thermal energy
2 storage systems towards buildings' energy efficiency. *Energy and Buildings* 59, 82-103.
- 3 Sung, A.H., 1998. Ranking importance of input parameters of neural networks. *Expert Systems with*
4 *Applications* 15, 405-411.
- 5 Theodoridou, I., Papadopoulos, A.M., Hegger, M., 2011. A typological classification of the Greek
6 residential building stock. *Energy and Buildings* 43, 2779-2787.
- 7 van Moeseke, G., Bruyère, I., De Herde, A., 2007. Impact of control rules on the efficiency of shading
8 devices and free cooling for office buildings. *Building and Environment* 42, 784-793.
- 9 Wan, K.S.Y., Yik, F.H.W., 2004. Representative building design and internal load patterns for modelling
10 energy use in residential buildings in Hong Kong. *Applied Energy* 77, 69-85.
- 11 Wang, Z., Yi, L., Gao, F., 2009. Night ventilation control strategies in office buildings. *Solar Energy* 83,
12 1902-1913.
- 13 Wiel, S., McMahon, J.E., 2003. Governments should implement energy-efficiency standards and labels—
14 cautiously. *Energy Policy* 31, 1403-1415.
- 15 Wong, S.L., Wan, K.K.W., Lam, T.N.T., 2010. Artificial neural networks for energy analysis of office
16 buildings with daylighting. *Applied Energy* 87, 551-557.
- 17 Xu, C., He, H.S., Hu, Y., Chang, Y., Li, X., Bu, R., 2005. Latin hypercube sampling and geostatistical
18 modeling of spatial uncertainty in a spatially explicit forest landscape model simulation.
19 *Ecological Modelling* 185, 255-269.
- 20 Yamakawa, M.A., Westphal, F.S., 2011. Influência do percentual de abertura nas fachadas e do fator
21 solar dos vidros na etiquetagem do Procel/Inmetro: Método Prescritivo x Simulação (in
22 Portuguese), XI Encontro Nacional sobre Conforto no Ambiente Construído, Buzios.
- 23 Yang, H., Cui, P., Fang, Z., 2010a. Vertical-borehole ground-coupled heat pumps: A review of models
24 and systems. *Applied Energy* 87, 16-27.
- 25 Yang, J., Rivard, H., Zmeureanu, R., 2005. On-line building energy prediction using adaptive artificial
26 neural networks. *Energy and Buildings* 37, 1250-1259.
- 27 Yang, Y., Li, B., Yao, R., 2010b. A method of identifying and weighting indicators of energy efficiency
28 assessment in Chinese residential buildings. *Energy Policy* 38, 7687-7697.
- 29 Yu, Z., Haghighat, F., Fung, B.C.M., Morofsky, E., Yoshino, H., 2011. A methodology for identifying
30 and improving occupant behavior in residential buildings. *Energy* 36, 6596-6608.
- 31 Zemella, G., De March, D., Borrotti, M., Poli, I., 2011. Optimised design of energy efficient building
32 façades via Evolutionary Neural Networks. *Energy and Buildings* 43, 3297-3302.
- 33 Zhai, X.Q., Qu, M., Yu, X., Yang, Y., Wang, R.Z., 2011. A review for the applications and integrated
34 approaches of ground-coupled heat pump systems. *Renewable and Sustainable Energy Reviews*
35 15, 3133-3140.

Nomenclature

a_{roof}	Roof absorptance of solar radiation [-]
a_{wall}	Wall absorptance of solar radiation [-]
b_n	bias of hidden node n
b_s	bias of the output node
$\bar{e}$	mean bias error - MBE
E_{con}	energy consumption [kWh/m ² y]
E_{max}	maximum energy consumption used in the ANN training [kWh/m ² y]
E_{min}	minimum energy consumption used in the ANN training [kWh/m ² y]
H	number of nodes in the hidden layer
I	Infiltration [ACH]
ILD	Internal load density [W/m ²]
NETinput	as defined in Equation 3
PU	Patterns of use [h/day]
R^2	Coefficient of determination
U_{wall}	Wall thermal transmittance [W/(m ² .K)]
$W_{i,n}$	weight values for each pair of nodes connecting the input and hidden layers
$W_{n,s}$	weight values for each pair of nodes connecting the hidden and the output layers
X	number of input nodes
x_i	input value i of the ANN model
$x_{\text{MAX}i}$	maximum values of the input i used in the ANN training
$x_{\text{MIN}i}$	minimum values of the input i used in the ANN training
σ_e	error standard deviation, also known as root-mean squared error – RMSE

Acronyms

ACH	Air changes per hour [1/h]
ANN	Artificial neural network
ASHRAE	American Society of Heating, Refrigerating and Air-Conditioning Engineers
BES	Building Energy Simulation

Figure captions

Figure 1. Length and width for 16 typologies used in the simulations (as described in the appendix)

Figure 2 . ANN predictions compared to the reference data calculated using EnergyPlus. (A)

symmetry plot and (B) histogram of error in ANN calculation

Figure 3. Histogram of differences between EnergyPlus results and results by various ANNs that do

not take into account some input parameters

Figure 4. Example of sensitivity of different input parameter, for the case of a small office building

Figure 5. Average sensitivity of energy consumption calculated using the ANN model

Figure 6 . Calculated energy consumption of the best and worst performing shells of each of the

sixteen typologies

Figure 7 . Correlation between performance variation and building parameters

1

2

3

Figure 1. Length and width for 16 typologies used in the simulations (as described in the appendix)

4

5

1

Figure 2. ANN predictions compared to the reference data calculated using EnergyPlus. (A) symmetry plot and (B) histogram of error in ANN calculation

2

3

4

1

Figure 3. Histogram of differences between EnergyPlus results and results by various ANNs that do not take into account some input parameters

2

3

4

1

2

3

Figure 4. Example of sensitivity of different input parameter, for the case of a small office building

4

5

6

7

8

9

10

11

12

13

14

Figure 5. Average sensitivity of energy consumption calculated using the ANN model

1

2

3 Figure 6 . Calculated energy consumption of the best and worst performing shells of each of the
4 sixteen typologies

5

6

1

Figure 7. Correlation between performance variation and building parameters

2

3

1 **Table captions**

2 Table 1 . Building properties and assumed values describing the existing building stock for Florianópolis,
3 Brazil

4 Table 2 . Simulation parameters and correspondent uncertainty

5 Table 3. Error in ANN prediction for additional cases for validation.

6

7

1
2
3

Table 2 . Building properties and assumed values
describing the existing building stock for Florianópolis, Brazil

Building property	Discreet values
WWR - Window to wall ratio [%]	5; 15; 30; 45; 65; 90
SHGC - Solar heat gain coefficient [-]	0.87; 0.81; 0.76; 0.59; 0.49; 0.25
Uroof - Roof thermal transmittance [W/(m ² .K)]	0.62; 1.03; 1.18; 1.75; 1.92; 2.25; 4.56
AVS - Vertical shading device coverage angle [°]	0 (no shading); 35; 45
AHS - Horizontal shading device coverage angle [°]	0 (no shading); 45
Uwall - Wall thermal transmittance [W/(m ² .K)]	0.66; 1.61; 2.02; 2.28; 2.49; 3.7; 4.4
awall - Wall absorptance of solar radiation [-]	0.2; 0.5; 0.8
aroorf - Roof absorptance of solar radiation [-]	0.2; 0.5; 0.8
Orientation of the main facade [°], where North=0	0; 90

4
5

1
2

Table 2 . Simulation parameters and correspondent uncertainty

Parameters	Values
I - Infiltration [ACH]	0.5; 1; 3
ILD - Internal load density [W/m ²]	20; 35; 40; 65
PU - Patterns of use [h/day]	11; 14; 24 (hotel)

3
4
5

1

2

Table 3. Error in ANN prediction for additional cases for validation.

Building type	Energy consumption [kWh/m ²]		Difference [kWh/m ² .y]
	EnergyPlus	ANN	
Small building	182	168	14 (-7%)
Large building	95	102	-7 (+7%)
Vertical building	46	55	-9 (+20%)
Non-conventional	58	49	9 (-15%)

3

4

5

Appendixes

Appendix A . Typologies representing the building stock of Florianópolis, Brazil

Building type	Building dimensions (Width, length, ceiling height) [m,m,m]	Number of floors [-]	Exposed surface / indoor volume [1/m]	Typology ID
Small and large offices/stores.	6, 8, 2.7	1	0.95	1
	40, 80, 3	2	0.24	2
	9, 10, 2.7	4	0.51	3
	10, 16, 3.3	1	0.63	4
	5, 10, 3	3	0.71	5
	50, 50, 3.5	1	0.37	6
	45, 50, 3	5	0.17	7
	7.5, 26.7, 2.46	6	0.47	8
	30, 30, 3	10	0.14	9
	40, 80, 10	1	0.18	10
	44.5, 67, 5	2	0.17	11
	70, 70, 5	5	0.11	12
Hotels	17.4, 52.4, 3	6	0.08	13
	17.4, 52.4, 3	12	0.10	14
Vertical offices	20, 68, 2.7	13	0.19	15
	30, 50, 3.5	17	0.15	16
* Ratio of exposed building surface (facades and roof) to the conditioned indoor volume				

Appendix B . Typologies considered for additional quality assurance test of ANN

Building type	Dimensions Width, length, ceiling height [m,m,m]	Number of floors [-]
Small building	5, 6, 3	2
Large building	30, 50, 5	3
Vertical building	40, 80, 3	12
Non-conventional	100, 200, 10	7
window to wall ratio of 50%, a roof thermal transmittance of 0.95 W/(m ² .K) and...		

1

Appendix C . ANN weight values (input nodes to hidden nodes)

input node	hidden layer nodes								
	1	2	3	4	5	6	7	8	9
1	-0.12308	-0.35016	-0.40992	-0.48208	0.086147	0.215453	0.741669	-0.0943	-0.83535
2	0.004388	-0.11786	-0.17101	-0.21802	0.346246	-0.26864	-0.66445	0.172554	0.336566
3	0.186248	-0.33981	-0.17096	-0.10659	-0.32543	-5.93398	-0.21227	-0.21414	0.111231
4	0.072223	0.279413	0.121163	0.213017	0.394454	-0.35064	-0.1851	0.134382	0.42725
5	0.037709	0.087147	0.027861	-0.02397	-0.10409	-0.01142	0.192828	-0.14632	0.181567
6	0.192377	0.024764	-0.14441	-0.31155	-0.18266	-0.23567	0.581691	-0.16109	0.110236
7	-0.26023	-0.13304	-0.62842	-0.18306	-1.05263	-0.24523	0.381996	-2.40651	-0.08506
8	18.62549	1.563258	1.16034	0.675206	-21.9938	-0.26458	-24.8815	-2.27694	-19.047
9	0.095442	-0.48269	-0.20612	-0.2452	0.028968	0.0945	-0.55151	-0.10667	-0.56624
10	0.026898	-0.08773	-0.20437	-0.14106	0.191951	-2.9837	0.40572	-0.19156	0.292791
11	0.04762	-0.55983	-0.77358	-5.93024	-0.81317	-2.56719	-3.05493	-3.65517	-7.58972
12	-0.05211	-0.32534	-0.19708	0.122766	0.290045	0.489713	0.616344	0.579345	0.060928
13	-81.1039	-2.91337	-3.69507	1.00978	-4.33119	26.34617	-26.0436	1.651878	-10.188
14	11.06987	-25.2572	18.62168	-3.99185	7.052285	-14.2845	-9.10023	5.060556	18.44951
15	-6.74132	35.00231	-26.2364	7.390736	3.394253	-100.872	3.006375	-17.7776	14.53232
16	22.63756	-12.9089	-13.4423	-8.85356	-14.2736	-10.9504	-10.1224	6.403487	12.6688
17	0.731552	46.56242	-23.7549	5.069072	-0.92541	-12.6902	15.65485	-1.7385	-8.92484
18	-3.76618	0.523313	25.30659	1.598741	-0.62492	1.535674	10.11521	1.55289	-0.37837

2

3

Appendix D . ANN weight values (hidden nodes to output node)

Hidden layer	Output node
1	-2.433609
2	-1.948416
3	-2.697041
4	-1.766868
5	-1.174638
6	-1.699722
7	-0.771836
8	-1.915127
9	-0.927062

4

5

6

Appendix E . ANN bias of hidden nodes and output nodes

Layer	Node	Bias
Hidden node	1	-22.041482
	2	-3.471297
	3	-2.082993
	4	-0.291936
	5	0.783789
	6	7.535811
	7	22.135866
	8	-4.504219
	9	-14.056657
Output node	1	2.381588

7

Appendix F . ANN minimum and maximum values of input and output nodes

Layer	Node	Minimum	Maximum
Input node	1 (WWR)	5	90
	2 (SHGC)	0.25	0.87
	3 (Uroof)	0.62	4.56
	4 (AVS)	0	45
	5 (AHS)	0	45
	6 (Uwall)	0.7	4.4
	7 (I)	0.5	3
	8 (ILD)	20	65
	9 (awall)	0.2	0.8
	10 (arroof)	0.2	0.8
	11 (PU)	11	24
	12 (Orientation)	0	180
	13 (Ceiling height)	2.46	10
	14 (Length)	8	80
	15 (Number of floors)	1	17
	16 (Facade area)	75.6	9520
	17 (Roof area)	48	4900
	18 (Total conditioned floor area)	48	25152
	19 (Total non-conditioned floor area)	0	6400
Output node	Energy consumption	30.59	205.44

Appendix G . Input and output of the 3200 simulations using Energy Plus

To be included in the online version of the article as additional data for download