

Magnetically actuated glaucoma drainage device with adjustable flow properties after implantation

Citation for published version (APA):

Pereira, I. C. F., Wyss, H. M., Beckers, H. J. M., & den Toonder, J. M. J. (2021). Magnetically actuated glaucoma drainage device with adjustable flow properties after implantation. *Engineering Proceedings*, 4(3). <https://doi.org/10.3390/Micromachines2021-09584>

DOI:

[10.3390/Micromachines2021-09584](https://doi.org/10.3390/Micromachines2021-09584)

Document status and date:

Published: 16/04/2021

Document Version:

Publisher's PDF, also known as Version of Record (includes final page, issue and volume numbers)

Please check the document version of this publication:

- A submitted manuscript is the version of the article upon submission and before peer-review. There can be important differences between the submitted version and the official published version of record. People interested in the research are advised to contact the author for the final version of the publication, or visit the DOI to the publisher's website.
- The final author version and the galley proof are versions of the publication after peer review.
- The final published version features the final layout of the paper including the volume, issue and page numbers.

[Link to publication](#)

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal.

If the publication is distributed under the terms of Article 25fa of the Dutch Copyright Act, indicated by the "Taverne" license above, please follow below link for the End User Agreement:

www.tue.nl/taverne

Take down policy

If you believe that this document breaches copyright please contact us at:

openaccess@tue.nl

providing details and we will investigate your claim.

Abstract

Magnetically Actuated Glaucoma Drainage Device with Adjustable Flow Properties after Implantation [†]

Inês C. F. Pereira ^{1,2,*}, Hans M. Wyss ^{1,2}, Henny J. M. Beckers ³ and Jaap M. J. den Toonder ^{1,2}

¹ Microsystems, Department of Mechanical Engineering, Eindhoven University of Technology, 5600MB Eindhoven, The Netherlands; h.m.wyss@tue.nl (H.M.W.); J.M.J.d.Toonder@tue.nl (J.M.J.d.T.)

² Institute for Complex Molecular Systems (ICMS), Eindhoven University of Technology, 5600MB Eindhoven, The Netherlands

³ University Eye Clinic Maastricht, Maastricht University Medical Centre+ (MUMC+), 6202AZ Maastricht, The Netherlands; henny.beckers@mumc.nl

* Correspondence: i.c.figueiredo.pereira@tue.nl

[†] Presented at the 1st International Conference on Micromachines and Applications, 15–30 April 2021; Available online: <https://micromachines2021.sciforum.net/>.

Abstract: Glaucoma is the second leading cause of preventable blindness worldwide, following cataract formation. A rise in the intraocular pressure (IOP) is a major risk factor for this disease, and results from an elevated resistance to aqueous humor outflow from the anterior chamber of the eye. Glaucoma drainage devices provide an alternative pathway through which the aqueous humor can effectively exit the eye, thereby lowering the IOP. However, post-operative IOP is unpredictable and current implants are deficient in maintaining IOP at optimal levels. To address this deficiency, we are developing an innovative, non-invasive magnetically actuated glaucoma implant with a hydrodynamic resistance that can be adjusted following surgery. This adjustment is achieved by integrating a magnetically actuated microvalve into the implant, which can open or close fluidic channels using an external magnetic stimulus. This microvalve was fabricated from poly(styrene-*block*-isobutylene-*block*-styrene), or ‘SIBS’, containing homogeneously dispersed magnetic microparticles. “Micro-pencil” valves of this material were fabricated using a combination of femtosecond laser machining with hot embossing. The glaucoma implant is comprised of a drainage tube and a housing element fabricated from two thermally bonded SIBS layers with the microvalve positioned in between. Microfluidic experiments involving actuating the magnetic micro-pencil with a moving external magnet confirmed the valving function. A pressure difference of around 6 mmHg was achieved, which is sufficient to overcome hypotony (i.e., too low IOP)—one of the most common post-operative complications following glaucoma surgery.

Citation: Pereira, I.C.F.; Wyss, H.M.; Beckers, H.J.M.; den Toonder, J.M.J. Magnetically Actuated Glaucoma Drainage Device with Adjustable Flow Properties after Implantation. *Eng. Proc.* **2021**, *4*, 3. <https://doi.org/10.3390/Micromachines2021-09584>

Academic Editor: Ion Stiharu

Published: 16 April 2021

Publisher’s Note: MDPI stays neutral with regard to jurisdictional claims in published maps and institutional affiliations.



Copyright: © 2021 by the authors. Licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (<http://creativecommons.org/licenses/by/4.0/>).

Keywords: glaucoma; intraocular pressure (IOP); adjustable glaucoma implant; magnetic microvalve; microfabrication

Supplementary Materials: The following are available online at <https://www.mdpi.com/2673-4591/4/1/3/s1>.

Institutional Review Board Statement: Not applicable.

Informed Consent Statement: Not applicable.

Data Availability Statement: Not applicable.