

Error propagation assessment of enumerative coding schemes

Citation for published version (APA):

Schouhamer Immink, K. A., & Janssen, A. J. E. M. (1999). Error propagation assessment of enumerative coding schemes. IEEE Transactions on Information Theory, 45(7), 2591-2594. https://doi.org/10.1109/18.796411

DOI: 10.1109/18.796411

Document status and date:

Published: 01/01/1999

Document Version:

Publisher's PDF, also known as Version of Record (includes final page, issue and volume numbers)

Please check the document version of this publication:

• A submitted manuscript is the version of the article upon submission and before peer-review. There can be important differences between the submitted version and the official published version of record. People interested in the research are advised to contact the author for the final version of the publication, or visit the DOI to the publisher's website.

• The final author version and the galley proof are versions of the publication after peer review.

• The final published version features the final layout of the paper including the volume, issue and page numbers.

Link to publication

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- · Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
 You may freely distribute the URL identifying the publication in the public portal.

If the publication is distributed under the terms of Article 25fa of the Dutch Copyright Act, indicated by the "Taverne" license above, please follow below link for the End User Agreement:

www.tue.nl/taverne

Take down policy

If you believe that this document breaches copyright please contact us at:

openaccess@tue.nl

providing details and we will investigate your claim.

consisting of two four-state trellises. To this point, though, no new codes comparable to, for example, the rate 4/5 and the rate 8/9 MTR codes in [10] for the $(1 - D) (1 + D)^3$ and $(1 - D) (1 + D)^4$ channels have been found. For future work, an interesting research problem would be to relax the trellis-matching constraint to enlarge the constellations, thus obtaining higher-rate codes. Of course this would come with an increase in decoding complexity.

REFERENCES

- W. L. Abbott and J. M. Cioffi, "Combined equalization and coding for high-density saturation recording channels," *IEEE J. Select. Areas Commun.*, vol. 10, pp. 168–181, Jan. 1992.
- [2] A. R. Calderbank, "Multilevel codes and multistage decoding," *IEEE Trans. Commun.*, vol. 37, pp. 222–229, Mar. 1989.
- [3] G. D. Forney, Jr., "Coset codes—Part I: Introduction and geometric classification," *IEEE Trans. Inform. Theory*, vol. 34, pp. 1123–1151, Sept. 1988.
- [4] R. Haeb, "A modified trellis coding technique for partial response channels," *IEEE Trans. Commun.*, vol. 40, pp. 513–520, Mar. 1992.
- [5] K. J. Hole, "New short constraint length rate (N-1)/N punctured convolutional codes for soft-decision Viterbi decoding," *IEEE Trans. Inform. Theory*, vol. 34, pp. 1079–1081, Sept. 1988.
- [6] K. J. Hole and Ø. Ytrehus, "Improved coding techniques for precoded partial-response channels," *IEEE Trans. Inform. Theory*, vol. 40, pp. 482–493, Mar. 1994.
- [7] H. Imai and S. Hirakawa, "A new multilevel coding method using error correcting codes," *IEEE Trans. Inform. Theory*, vol. IT-23, pp. 371–377, May 1977.
- [8] P. Kabal and S. Pasupathy, "Partial-response signaling," *IEEE Trans. Commun.*, vol. COM-23, pp. 921–934, Sept. 1975.
- [9] R. Karabed and P. H. Siegel, "Matched spectral-null codes for partialresponse channels," *IEEE Trans. Inform. Theory*, vol. 37, pp. 818–855, May 1991.
- [10] R. Karabed, P. H. Siegel, and E. Soljanin, "Constrained coding for binary channels with high intersymbol interference," *IEEE Trans. Inform. Theory*, vol. 45, pp. 1777–1797, Sept. 1999.
- [11] H. Kobayashi and D. T. Tang, "Application of partial-response channel coding to magnetic recording systems," *IBM J. Res. Develop.*, vol. 14, no. 4, pp. 368–375, July 1970.
- [12] A. Lender, "Correlative coding for binary data transmission," *IEEE Spectrum*, vol. 3, no. 2, p. 104, Dec. 1966.
- [13] S. Lin and D. J. Costello, Jr., Error Control Coding: Fundamentals and Applications. Englewood Cliffs, NJ: Prentice-Hall, 1983.
- [14] J. Moon and B. Brickner, "Maximum transition run codes for data storage systems," *IEEE Trans. Magn.*, vol. 32, no. 5, pt. 1, pp. 3992–3994, 1996.
- [15] S. I. Sayegh, "A class of optimum block codes in signal space," *IEEE Trans. Commun.*, vol. COM-34, pp. 1043–1045, Oct. 1986.
- [16] P. H. Siegel and J. K. Wolf, "Modulation and coding for information storage," *IEEE Commun. Mag.*, vol. 29, pp. 68–86, Dec. 1991.
- [17] H. K. Thapar and A. M. Patel, "A class of partial response systems for increasing storage density in magnetic recording," *IEEE Trans. Magn.*, vol. MAG-23, pp. 3666–3668, Sept. 1987.
- [18] B. F. Uchôa Filho and M. A. Herro, "Good convolutional codes for the precoded (1 – D) (1 + D)ⁿ partial response channels," *IEEE Trans. Inform. Theory*, vol. 43, pp. 441–453, Mar. 1997.
- [19] B. F. Uchôa Filho, "Coding for some high-density magnetic recording channel models," Ph.D. dissertation, Univ. Notre Dame, Notre Dame, IN, Oct. 96.
- [20] G. Ungerboeck, "Channel coding with multilevel/phase signals," *IEEE Trans. Inform. Theory*, vol. IT-28, pp. 55–67, Jan. 1982.
- [21] L. F. Wei, "Trellis coded modulation with multi-dimensional constellations," *IEEE Trans. Inform. Theory*, vol. IT-33, pp. 483–501, July 1987.
- [22] J. K. Wolf and G. Ungerboeck, "Trellis coding for partial response channels," *IEEE Trans. Commun.*, vol. COM-34, pp. 765–773, Aug. 1986.
- [23] E. Zehavi and J. K. Wolf, "On saving decoder states for some trellis codes and partial response channels," *IEEE Trans. Commun.*, vol. 36, pp. 222–224, Feb. 1988.

Error Propagation Assessment of Enumerative Coding Schemes

Kees A. Schouhamer Immink, *Fellow, IEEE*, and Augustus J. E. M. Janssen, *Senior Member, IEEE*

Abstract—Enumerative coding is an attractive algorithmic procedure for translating long source words into codewords and vice versa. The usage of long codewords makes it possible to approach a code rate which is as close as desired to Shannon's noiseless capacity of the constrained channel. Enumerative encoding is prone to massive error propagation as a single bit error could ruin entire decoded words. This contribution will evaluate the effects of error propagation of the enumerative coding of runlength-limited sequences.

Index Terms—Enumerative coding, error propagation, RLL.

I. INTRODUCTION

The technique of enumerative coding [1] makes it possible to translate source words into codewords and *vice versa* by invoking an algorithmic procedure rather than performing the translation with a look-up table. The usage of long codewords makes it possible to approach a code rate which is arbitrarily close to Shannon's noiseless capacity of the constrained channel. The risk of extreme error propagation precluded its usage in practical systems. Single channel bit errors may result in error propagation that could corrupt the entire data in the decoded word, and, of course, the longer the codeword the greater the number of data symbols affected.

This correspondence will evaluate the effects of error propagation of enumerative coding, where it is assumed that the constrained code is used in the conventional code configuration. It will be shown that when certain measures are taken, the average error propagation can be controlled to a level which is quite acceptable for many applications. We start with a basic outline of the enumeration algorithm followed by the error propagation assessment of enumerative schemes applied to the coding of runlength-limited sequences.

II. ENUMERATIVE ENCODING

Let $\{0,1\}^n$ denote the set of binary sequences of length n and let S be any (constrained) subset of $\{0,1\}^n$. The set S can be ordered lexicographically as follows: if $\boldsymbol{x} = (x_1, \dots, x_n) \in S$ and $\boldsymbol{y} = (y_1, \dots, y_n) \in S$, then \boldsymbol{y} is called less than \boldsymbol{x} , in short, $\boldsymbol{y} < \boldsymbol{x}$, if there exists an $i, 1 \leq i \leq n$, such that $y_i < x_i$ and $x_j = y_j, 1 \leq j < i$. For example, "00101" < "01010." The position of \boldsymbol{x} in the lexicographical ordering of S is defined to be the *rank* of \boldsymbol{x} , denoted by $i_S(\boldsymbol{x})$, i.e., $i_S(\boldsymbol{x})$ is the number of all \boldsymbol{y} in S with $\boldsymbol{y} < \boldsymbol{x}$.

Let $n_s(x_1, x_2, \dots, x_u)$ be the number of elements in S for which the first u coordinates are (x_1, x_2, \dots, x_u) . Cover [1] showed that

Manuscript received October 5, 1997; revised March 30, 1999. This work was conducted while K. A. S. Immink was with Philips Research Labs, Eindhoven, The Netherlands.

K. A. S. Immink is with the Institute of Experimental Mathematics, 45326 Essen, Germany (e-mail: immink@exp-math.uni-essen.de).

A. J. E. M. Janssen is with Philips Research Laboratories, 5656 AA Eindhoven, The Netherlands (email: janssena@natlab.research.philips.com).

Communicated by E. Soljanin, Associate Editor for Coding Techniques. Publisher Item Identifier S 0018-9448(99)07003-0.

0018–9448/99\$10.00 © 1999 IEEE

the rank of $x \in S$ can be obtained by

$$i_S(\boldsymbol{x}) = \sum_{j=1}^n x_j n_s(x_1, x_2, \cdots, x_{j-1}, 0).$$
(1)

In Section III, we will evaluate error propagation effects. It is not a simple matter to analyze the effects of error propagation for a large class of constrained codes. We will focus on the enumeration of the set of runlength-limited (RLL) or (d, k)-constrained sequences, i.e., sequences that have at least d and at most k "zeros" between consecutive "ones." For (d, ∞) -constrained sequences (1) simplifies to

$$i_S(\boldsymbol{x}) = \sum_{j=1}^n x_j N(n-j)$$
⁽²⁾

where N(i) denotes the number of (d, ∞) -constrained sequences of length *i*. Clearly, the rank $i_S(\mathbf{x})$ can be found by simply forming the inner product of the received *n*-vector \mathbf{x} and the *n*-vector of weights $(N(n-1), \dots, N(0))$. Similar simple enumerative schemes have been derived for (0, k) [4] and (d, k) sequences [5]. The number of (d, ∞) -constrained sequences of length *n* can be found with

i)
$$N(n) = n + 1, 0 \le n \le d + 1$$

ii) $N(n) = N(n-1) + N(n-d-1), \quad n > d + 1.$ (3)

Note that if d = 0, i.e., S is the set of unconstrained sequences $\{0,1\}^n$, (2) reduces to the familiar binary-to-decimal conversion algorithm

$$i_S(\boldsymbol{x}) = \sum_{j=1}^n x_j 2^{n-j}.$$

For d > 0, we have *n* weights of approximately *n* bits, so that the amount of storage required for storing the weights is proportional to n^2 . If we use a floating-point representation of the weights, each weight is represented by a fixed number of bits *s*. As a result, the hardware required for storage grows linearly with the codeword length *n*. The finite-precision representation of the weights will entail a (small) loss in code rate [2]. Floating-point arithmetic employs a two-part radix-2 representation I = (m, e) to express the weight $I = m \times 2^e$, where *I*, *m*, and *e* are nonnegative integers. The two components *m* and *e* are usually called *mantissa* and *exponent* of the integer *I*, respectively. The translation of a weight into (m, e) is easily accomplished with the following procedure which ensures that the mantissa *m* is represented by a specified number of bits, denoted by *q*. Let *I* be a positive integer, and let

$$u = \lfloor \log_2 I \rfloor$$

then the q-bit truncation of I, denoted by $[I]_q$

$$|I|_q = |2^{-(u+1-q)}I|2^{u+1-q}$$

can be represented in binary floating-point representation whose mantissa requires at most q nonzero bits.

If the above finite-precision arithmetic is used in the enumeration algorithms we must modify the set of weights, $\{N(i)\}$, developed above. To that end, let $\hat{N}(i)$ denote the number of (d) sequences of length *i* that can be encoded with a *q*-bit mantissa representation, then

$$\hat{N}(i) = \begin{cases} i+1, & 1 \le i \le d+1 \\ \lfloor \hat{N}(i-1) + \hat{N}(i-1-d) \rfloor_q, & i > d+1. \end{cases}$$
(5)

It is tacitly assumed that N(i), $1 < i \le d + 1$, can be represented by a mantissa of q bits, i.e., $d + 2 < 2^{q}$. The enumeration algorithm itself remains unchanged, that is,

$$i_S(\mathbf{x}) = \sum_{j=1}^n x_j \hat{N}(n-j).$$
 (6)

Note that, though we have not explicitly written down the enumeration algorithms of the general (d, k) case, it can be observed from the results in [2] that the analysis of the error propagation effects given below can be used to this general case.

III. ERROR PROPAGATION

In this section, we will investigate the effects of error propagation. It is assumed that a binary source word, **b** is translated into a binary codeword **x** using the enumeration algorithm. During transmission of **x** a single error is made, i.e., we receive \mathbf{x}' , $d_H(\mathbf{x}, \mathbf{x}') = 1$, where $d_H(\mathbf{x}, \mathbf{y})$ denotes Hamming distance between \mathbf{x} and \mathbf{y} . Translation using (2) or (6) will result in the word $\mathbf{b}' = i_S(\mathbf{x}') \neq \mathbf{b} = i_S(\mathbf{x})$, where \mathbf{b}' and \mathbf{b} are the binary representations of $i_S(\mathbf{x}')$ and $i_S(\mathbf{x})$, respectively. In particular, we are interested in $d_H(\mathbf{b}, \mathbf{b}')$ and the error burst length distribution. The *error burst length* b is defined by $b = n_{\max} - n_{\min} + 1$, where n_{\min} and n_{\max} denote the smallest and largest positions where \mathbf{b}' and \mathbf{b} differ.

If an error is made at position k of the codeword, then the decoder will invoke (6) and form the inner product

$$i_{S}(\mathbf{x}') = \sum_{j=1}^{n} x_{j} \hat{N}(n-j) + a \hat{N}(n-k)$$

= $i_{S}(\mathbf{x}) + a \hat{N}(n-k),$
= $\mathbf{b} + a \hat{N}(n-k)$ (7)

where a = 1 if $x_k = 0$ or a = -1 if $x_k = 1$. All additions (or subtractions) are in binary notation. Clearly, severe error propagation can only occur if the binary addition (or subtraction) of $\boldsymbol{b} = i_S(\boldsymbol{x})$ and $\hat{N}(n-k)$ results in a long carry.

An analysis of the error statistics can be made if we make some assumptions. It is assumed that the source word **b** is a random binary vector of doubly infinite length. Secondly, the mantissa of a weight $\hat{N}(n-k)$ is the binary *q*-vector $\mathbf{y} = (y_{q-1} \cdots, y_0)$. By definition $y_{q-1} = 1$ and the remaining (q-1) elements are assumed to be random. If the above assumptions hold, the next theorem provides the error burst length distribution.

Theorem 1: With the above assumptions on the randomness of **b** and **y** the error burst length distribution p(b) is given by

$$p(b) = \begin{cases} \left(\frac{1}{2}\right)^{q}, & b = 1\\ \left(\frac{1}{2}\right)^{q-b+2}, & 2 \le b \le q\\ \left(\frac{1}{2}\right)^{b-q+1}, & b > q \end{cases}$$
(8)

and p(b) = 0 for $b \leq 0$.

Proof: We may assume that we have an addition error (i.e., a = 1 in (7)). There holds

$$p(b = l) = \sum_{k} p(n_{\max} = l + k - 1, n_{\min} = k)$$

=
$$\sum_{k} p(n_{\max} = l + k - 1 | n_{\min} = k) p(n_{\min} = k).$$
(9)

We compute for $k = 0, 1, \dots, q - 1$

$$p(n_{\min} = k) = p(y_0 = y_1 = \dots = y_{k-1} = 0, y_k = 1)$$

= $\left(\frac{1}{2}\right)^{\min(k+1,q-1)}$ (10)

(4)



Fig. 1. Comparison of error burst distribution for d = 2 and q = 9.

while $p(n_{\min} = k) = 0$ for other values of k. Furthermore, again for $k = 0, 1, \dots, q - 1$

$$p(n_{\max} = q - 1 | n_{\min} = k) = 1 - p(\text{carry at} q - 1 | n_{\min} = k)$$
(11)

while for m > q - 1 there holds

$$p(n_{\max} = m | n_{\min} = k)$$

= $p(\text{carry at } q - 1 | n_{\min} = k)$
 $\cdot p(b_q = \dots = b_{m-1} = 1, b_m = 0)$
= $\left(\frac{1}{2}\right)^{m-q+1} p(\text{carry at } q - 1 | n_{\min} = k).$ (12)

It thus follows that we only need to compute

$$p(\text{carry at } q - 1 | n_{\min} = k), \quad \text{for } k = 0, 1, \cdots, q - 1.$$

To do so, we define more generally for $k = 0, 1, \dots, q - 1$ and $j = k, \dots, q - 1$

$$r_{jk} = p \text{ (carry at } j | n_{\min} = k \text{)}.$$
(13)

Now $r_{q-1,q-1} = \frac{1}{2}$, and it is not hard to show for $k = 0, 1, \dots, q-2$ there holds

$$\begin{aligned} r_{kk} &= 1/2 \\ r_{q-1,k} &= 1/2 + (1/2)r_{q-2,k} \\ r_{jk} &= 1/4 + (1/2)r_{j-1,k}, \qquad j = k+1, \cdots, q-2. \end{aligned}$$
 (14)

It thus follows that for $k = 0, 1, \dots, q - 2$

$$r_{kk} = r_{k+1,k} = \dots = r_{q-2,k} = \frac{1}{2}$$
 and $r_{q-1,k} = \frac{3}{4}$. (15)

Finally, using (9)–(12), (15), and $r_{q-1,q-1} = \frac{1}{2}$, we get

$$p(b=1) = p(n_{\max} = n_{\min} = q - 1) = \left(\frac{1}{2}\right)^q$$
(16)

$$p(b = q - p) = \frac{1}{4} \left(\frac{1}{2}\right)^{p+1} + \left(\frac{1}{2}\right)^{2q-p-1} + \frac{3}{4} \sum_{k=p+1}^{q-2} \left(\frac{1}{2}\right)^{k-p} \left(\frac{1}{2}\right)^{\min(k+1,q-1)}$$
(17)

for $p = 0, 1, \dots, q - 2$ and

$$p(b = q + p) = \left(\frac{1}{2}\right)^{2q+p-1} + \frac{3}{4} \sum_{k=0}^{q-2} \left(\frac{1}{2}\right)^{k+p} \left(\frac{1}{2}\right)^{\min(k+1,q-1)}$$
(18)

for $p = 1, 2, \cdots$. Working out (17) and (18) we find

$$p(b) = \begin{cases} \left(\frac{1}{2}\right)^{q}, & b = 1\\ \left(\frac{1}{2}\right)^{q-b+2}, & 2 \le b \le q\\ \left(\frac{1}{2}\right)^{b-q+1}, & b > q, \end{cases}$$
(19)

while p(b) = 0 for $b \le 0$. This concludes the proof.

From Theorem 1 it is clear that the most likely burst has a length of q, q + 1 bits with probability $p(q) \approx p(q + 1) \approx 1/4$. Error bursts longer or shorter than q or q + 1 have an exponentially decaying probability. Fig. 1 compares results of a typical example of computer simulations and computations using (8). The outcomes of the simulations show a reasonable agreement with the theory developed for the longer bursts and that there is a discrepancy for shorter bursts. In [2], it has been shown that the coefficients are periodic in nature. It has been found that the period lengths for selected values of d, k, and p can be very short and that, therefore, the assumption of randomness of the coefficients, which is essential for the validity of the theorem, is not valid. However, for the majority of parameters the period length is quite long, and the coefficients show a reasonable "randomness."

Thus we can control the error propagation by a proper choice of q. The choice of q has an effect on the maximum achievable code rate which can simply be approximated by (see [2])

$$\hat{C}(d,k) \approx C(d,k) - 2^{-(q+2)}$$
 (20)

where C(d, k) is the capacity of the (d, k)-constrained channel and $\hat{C}(d, k)$ is the capacity of the same channel using enumerative encoding with floating arithmetic. With (8) and (20) a tradeoff has to be made between, on the one hand, the error propagation effects, which has a bearing on the required capability of the error control code, and on the other hand, the rate of the constrained code. This is a very subtle tradeoff requiring a detailed specification of the various coding layers, and has therefore not been pursued.

We present some results that follow from Theorem 1, or the proofs of which are of a similar nature as that of Theorem 1.

1) For the expectation E(b) and variance $\sigma^2(b)$ of b we have

$$E(b) = q - \frac{1}{2} + \left(\frac{1}{2}\right)^{q}$$

$$\sigma^{2}(b) = 2q + \frac{17}{4} - 2q\left(\frac{1}{2}\right)^{q} - \left(\frac{1}{2}\right)^{2q}.$$
 (21)

Furthermore, for the number of errors made, denoted by n, i.e., the number of positions k where $x'_k \neq x_k$, we have

$$E(n) = \frac{1}{2}(q+3)$$

$$\sigma^{2}(n) = \frac{1}{6}(q+3) + \frac{10}{9} + \frac{8}{9}\left(\frac{1}{2}\right)^{q}.$$
 (22)

2) For the damage done by a fixed additive y = (yq-1,..., y0) we have the following. Let k be the minimum index i such that yi = 1. Then

$$p(b = q - k | \mathbf{y}) = 1 - \sum_{j=0}^{q-1} \left(\frac{1}{2}\right)^{q-j} y_j$$
(23)

and

$$p(b = l | \boldsymbol{y}) = \sum_{j=0}^{q-1} \left(\frac{1}{2}\right)^{l+k-j} y_j, \quad l = q-k+1, \cdots.$$
 (24)

The above was observed by L. M. G. M. Tolhuizen. Consequently,

$$E(b|\boldsymbol{y}) = q - k + T$$

$$\sigma^{2}(b|\boldsymbol{y}) = \frac{9}{4} - \left(T - \frac{3}{2}\right)^{2}$$
(25)

where

$$T = \sum_{j=0}^{q-1} \left(\frac{1}{2}\right)^{q-1-j} y_j \in [1,2).$$
 (26)

Similar, though slightly more complex, expressions involving the correlation function of \boldsymbol{y} can be derived for $E(n|\boldsymbol{y})$ and $\sigma^2(n|\boldsymbol{y})$.

IV. CONCLUSIONS

We have investigated error propagation effects of enumerative schemes used for the coding of runlength-limited sequences. We have given a theoretical expression for the error burst length distribution. The most likely burst has a length of q, q + 1 bits. Error bursts longer or shorter than q or q + 1 have an exponentially decaying probability. It has been shown that computer simulations compare fairly well with the theoretical results.

ACKNOWLEDGMENT

We would like to thank L. Tolhuizen for his comments on earlier versions of this correspondence.

REFERENCES

- [1] T. M. Cover, 'Enumerative source coding," *IEEE Trans. Inform. Theory*, vol. IT-19, pp. 73–77, Jan. 1973.
- [2] K. A. S. Immink, "A practical method for approaching the channel capacity of constrained channels," *IEEE Trans. Inform. Theory*, vol. 43, pp. 1389–1399, Sept. 1997.
- [3] D. T. Tang and L. R. Bahl, "Block codes for a class of constrained noiseless channels," *Inform. Control*, vol. 17, pp. 436–461, 1970.
- [4] W. H. Kautz, "Fibonacci codes for synchronization control," *IEEE Trans. Inform. Theory*, vol. IT-11, pp. 284–292, 1965.
- [5] L. Patrovics and K. A. S. Immink, "Encoding of *dklr*-sequences using one weight set," *IEEE Trans. Inform. Theory*, vol. 42, pp. 1553–1554, Sept. 1996.

On Efficient High-Order Spectral-Null Codes

Luca G. Tallini and Bella Bose, Fellow, IEEE

Abstract—Let S (N, q) be the set of all words of length N over the bipolar alphabet $\{-1, +1\}$, having a qth-order spectral-null at zero frequency. Any subset of S (N, q) is a spectral-null code of length N and order q. This correspondence gives an equivalent formulation of S (N, q) in terms of codes over the binary alphabet $\{0, 1\}$, shows that S (N, 2) is equivalent to a well-known class of single-error correcting and all unidirectional-error detecting (SEC-AUED) codes, derives an explicit expression for the redundancy of S (N, 2), and presents new efficient recursive design methods for second-order spectral-null codes which are less redundant than the codes found in the literature.

Index Terms—Balanced codes, digital recording, group-theoretic balanced codes, high-order spectral-null codes, line codes, partial-response channels.

I. INTRODUCTION

The set of words in a qth-order spectral-null code

$$\mathcal{S}(N, q) \subseteq \{-1, +1\}^N \stackrel{\text{def}}{=} \Phi^N$$

satisfies the following condition [7], [10] $(Y = y_1 y_2 \cdots y_N)$:

$$\mathcal{S}(N, q) = \left\{ Y \in \Phi^N \colon \sum_{j=1}^N y_j j^i = 0, \, \forall i = 0, \, 1, \, \cdots, \, q-1 \right\}$$
(1)

where the sum and product are over the real numbers. Any word in S(N, q) is called *q*th-order spectral-null word. A binary code C is a *q*th-order spectral-null code with *k* information bits and length *N* (briefly, a *q*-OSN(*N*, *k*) code) if, and only if

- 1) C is a subset of S(N, q) and
- 2) C has, say exactly, 2^k codewords.

One of the problems is to find such C and a one-to-one function (encoding function)

$$\mathcal{E} \colon \{0, 1\}^k \longrightarrow \mathcal{C}$$

which, together with its inverse (decoding function), is very easy to compute. It is also required that the redundancy of the code N - k is as small as possible.

When q = 1, these codes coincide with the so-called balanced or DC-free block codes [1], [2], [4], [6], [7], [9], [10], [13], [14], [16]. For values of q greater than 1, the q-OSN(N, k) codes have been recently considered for digital recording; these codes are useful in achieving a better rejection of the low-frequency components of the transmitted signal and enhancing the error correction capability of codes used in partial-response channels [6]–[8], [10]. Recently, Roth, Siegel, and Vardy, in [10], have presented many results in the area of high-order spectral-null codes. In this correspondence, some of the results given in [10] are improved. In particular, a new

Manuscript received March 8, 1998; revised September 23, 1998. This work was supported by the National Science Foundation under Grant MIP-9705738. The material in this correspondence was presented in part at the 1995 IEEE International Symposium on Information Theory, Whistler, BC, Canada, Sept. 1995.

L. G. Tallini is with the Dipartimento Di. Tec., Politecnico di Milano, 20133 Milano, Italy (e-mail: luca.tallini@polimi.it).

B. Bose is with the Department of Computer Science, Oregon State University, Corvallis, OR 97331 USA (e-mail: bose@cs.orst.edu).

Communicated by A. Vardy, Editor-in-Chief.

Publisher Item Identifier S 0018-9448(99)07309-5.

0018-9448/99\$10.00 © 1999 IEEE