

## FricDiff: a novel and innovative separation process

***Citation for published version (APA):***

Breure, B., Peters, E. A. J. F., & Kerkhof, P. J. A. M. (2007). FricDiff: a novel and innovative separation process. In *Proceedings of the 6th European Congress of Chemical Engineering (ECCE 6)*, 16-21 September 2007, Denmark, Copenhagen (pp. T3-8-1842)

***Document status and date:***

Published: 01/01/2007

***Document Version:***

Publisher's PDF, also known as Version of Record (includes final page, issue and volume numbers)

***Please check the document version of this publication:***

- A submitted manuscript is the version of the article upon submission and before peer-review. There can be important differences between the submitted version and the official published version of record. People interested in the research are advised to contact the author for the final version of the publication, or visit the DOI to the publisher's website.
- The final author version and the galley proof are versions of the publication after peer review.
- The final published version features the final layout of the paper including the volume, issue and page numbers.

[Link to publication](#)

***General rights***

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal.

If the publication is distributed under the terms of Article 25fa of the Dutch Copyright Act, indicated by the "Taverne" license above, please follow below link for the End User Agreement:

[www.tue.nl/taverne](http://www.tue.nl/taverne)

***Take down policy***

If you believe that this document breaches copyright please contact us at:

[openaccess@tue.nl](mailto:openaccess@tue.nl)

providing details and we will investigate your claim.

[Sign in the manager](#) / [Report a problem](#)

European Congress of Chemical Engineering - 6

Copenhagen 16-21 September 2007

Technical program

Help

## Abstract 1842 - FricDiff: a novel and innovative separation process

✚ [Add this abstract to your personal program](#). (You need to [sign in](#) to access this feature)

### FricDiff: a novel and innovative separation process

Multi-scale and/or multi-disciplinary approach to process-product innovation

Novel Separation Techniques (T3-8)

[MSc Bianca Breure](#)

Eindhoven University of Technology  
Department of Chemical Engineering and Chemistry  
Den Dolech 2  
5612 AZ Eindhoven  
Netherlands

[Asc. Prof Frank Peters](#)

Eindhoven University of Technology  
Department of Chemical Engineering and Chemistry  
Den Dolech 2  
5612 AZ Eindhoven  
Netherlands

[Prof Piet Kerkhof](#)

Eindhoven University of Technology  
Department of Chemical Engineering and Chemistry  
Den Dolech 2  
5612 AZ Eindhoven  
Netherlands

**Keywords:** friction diffusion, novel separation process, azeotropic alcohol-water mixtures, enhancer, macro porous membrane

One of the major disadvantages of the separation processes that are currently used in the (petro-)chemical industry is their high energy-consumption. This is particular the case for distillation, the most widely applied industrial separation technology. In addition, hazardous chemicals are often required to facilitate the separation. Over the past years, the interest for membrane separation processes, like pervaporation, vapor permeation and gas permeation has grown tremendously. The relatively low energy consumption and the fact that no additional chemicals are required, makes these processes interesting candidates to replace distillation. In spite of major efforts in universities and research institutes, membrane processes are still not suitable to replace distillation. The fluxes through the membranes are still too low, requiring large membrane areas. Furthermore, the ceramic membranes that are used are very fragile and expensive, whereas polymeric membranes have a low chemical and thermal stability. In order to find a solution for these drawbacks, an alternative separation technology called □FricDiff□ was developed at Eindhoven University of Technology.

FricDiff is a novel and energy-efficient separation process that can be used for the

separation of both gas and liquid mixtures. With this technology, a gas or vapor mixture (the liquid mixture is first evaporated to bring it in the vapor phase) is separated by letting it diffuse through a third component. This third component, which is called the enhancer, is a permanent gas (in case one wants to separate a vapor mixture) or a condensable vapor (when the mixture we want to separate is a gas mixture) that will show more friction with one component in the mixture. This component will, while interdiffusing, be more retained by the enhancer, leading to an enrichment of this component in the retentate. The separation process takes place inside a non-selective porous barrier (macro porous membrane) with the feed mixture and enhancer flowing at opposite sides of it. The advantage of using a macro porous barrier instead of a selective micro porous membrane, is that the fluxes through the barrier are much higher. Furthermore, the barrier can be made of a robust and relatively cheap material, like stainless steel.

In this project, the applicability of FricDiff for the separation of azeotropic mixtures of alcohols and water is studied. Experiments are performed with a lab scale experimental set-up and compared with results obtained with 2 computer models developed in the program Aspen Custom Modeler. The first model describes the mass transport in the tubes (at opposite sides of the porous barrier) with a plug flow and assumes that the mixtures are perfectly mixed in the radial direction. The second model is a more detailed model, which takes into account axial velocity profiles and radial concentration gradients and velocities. In this case, the effect of concentration polarization on the separation can be examined. In both models, the mass transport through the porous barrier is described with the Binary Friction Model. The influence of process conditions (e.g. absolute pressure, ratio of flow rates of feed mixture to enhancer) and the geometry and characteristics of the porous barrier (e.g. pore size, thickness of the porous barrier) on the separation are studied. In this way, the FricDiff-process can be optimized for the separation of a specific mixture.

**Presentation time: Tuesday 18, 13:40 to 14:00**, in session *Novel Separation Techniques (T3-8)*.



### **Abstracts**

In topic *Novel Separation Techniques (T3-8)*.

### **Technical Program**

- [By topics](#)
- [By authors](#)
- [By sessions](#)
- [Your personal program](#)