

# The mechanical properties of the porcine coronary arterial wall determined with a mixed experimental-numerical approach

**Citation for published version (APA):**

Horst, van der, A., Broek, van den, C. N., Rutten, M. C. M., & Vosse, van de, F. N. (2008). The mechanical properties of the porcine coronary arterial wall determined with a mixed experimental-numerical approach. In *Biomechanics in vascular biology and cardiovascular diseases* (pp. 72-).

**Document status and date:**

Published: 01/01/2008

**Document Version:**

Accepted manuscript including changes made at the peer-review stage

**Please check the document version of this publication:**

- A submitted manuscript is the version of the article upon submission and before peer-review. There can be important differences between the submitted version and the official published version of record. People interested in the research are advised to contact the author for the final version of the publication, or visit the DOI to the publisher's website.
- The final author version and the galley proof are versions of the publication after peer review.
- The final published version features the final layout of the paper including the volume, issue and page numbers.

[Link to publication](#)

**General rights**

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal.

If the publication is distributed under the terms of Article 25fa of the Dutch Copyright Act, indicated by the "Taverne" license above, please follow below link for the End User Agreement:

[www.tue.nl/taverne](http://www.tue.nl/taverne)

**Take down policy**

If you believe that this document breaches copyright please contact us at:

[openaccess@tue.nl](mailto:openaccess@tue.nl)

providing details and we will investigate your claim.

## The mechanical properties of the porcine coronary arterial wall determined with a mixed experimental-numerical approach

Arjen van der Horst, Chantal N. van den Broek, Marcel C.M. Rutten, Frans N. van de Vosse

Eindhoven University of Technology

### Introduction

The coronary arterial wall is anisotropic and has a highly non-linear stress-strain relationship [1-3]. A widely used method to measure this anisotropic non-linear behavior is to evaluate the response of the arterial wall when subjected to simultaneous inflation and axial extension [1-3]. Figure 1 shows a characteristic result obtained with such an ex vivo experiment (solid line) on a porcine LAD (C.N. van den Broek, unpublished data).

The aim of this study is to investigate whether this characteristic behavior can be described by a relatively simple, single layer, fiber reinforced neo-Hookean material model.

### Methods

The arterial wall is modeled as an incompressible fiber reinforced solid tube. This model was first introduced by Holzapfel et al. [3] and extended by van Oijen [4] and Driessen et al. [5]. Here, only the main features of the model are described, for the exact derivation of the constitutive equations, see Driessen et al. [5].

The matrix material is modeled as an incompressible neo-Hookean solid with shear modulus  $G$ . The fibers are modeled one-dimensionally and are arranged as a cross-ply with main angle  $\mu$ , standard deviation of the fiber distribution  $\sigma$  and total fiber volume fraction  $\varphi_{tot}$ . Two parameters ( $k_1, k_2$ ) determine an exponential stress-strain relation of the fibers.

The difference between the experimental- and numerical response is minimized using the Levenberg-Marquardt algorithm. Since  $\sigma$  is relatively insensitive compared to  $\mu$  it is held constant at  $10^\circ$ .  $\varphi_{tot}$  is held constant at 0.5 due to its dependence on the other parameters. Therefore, a set of four material parameters ( $G, k_1, k_2, \mu$ ) is optimized.

### Results

Although the estimated material parameters can describe the axial force accurately, the computation of the radius deviates significantly for the larger axial stretches at low pressures (Figure 1). Furthermore, the estimated material parameters found are significantly different for the three different axial stretches (table 1).




Figure 1: The experimental (solid) and numerical results (+, o, □) of the radius (left) and axial force (right) for the three axial stretches ( $\lambda_z$ )(+, o, □) and the material properties listed the table.

### Discussion and conclusions

Although the model gives reasonable results for the axial force, the radius at low pressure deviates significantly from the experimental data. A single parameter set describing the material behavior was not found. A possible reason for this are the assumptions made for  $\varphi_{tot}$  and  $\sigma$ . By finding a way to overcome the dependency problem of  $\varphi_{tot}$  the estimation results could be improved. Furthermore, since the material model is more a phenomenological than a microstructural model, the model might be improved by extending it with residual stress and (passive) smooth muscle behavior.

### References

1. Weizsäcker, H.W. et al. (1983) J Biomech, 16, p. 703-715.
2. Humphrey, J.D. (2002) Springer verlag, New York.
3. Holzapfel, G.A. et al. (2000) J Elasticity, 61, p. 1- 48.
4. Van Oijen, C.H.G.A (2003) PhD thesis, Eindhoven University of Technolgy.
5. Driessen, N.J.B. et al. (2005) J Biomech Eng, 127, p. 494-503.