

# Rate-equation analysis for an integrated coupled- cavity laser with MMI anti-phase coupler

**Citation for published version (APA):**

Lenstra, D. (2016). Rate-equation analysis for an integrated coupled- cavity laser with MMI anti-phase coupler. In *ECIO 2016 (Warsaw, Poland)* [0-44]

**Document status and date:**

Published: 22/05/2016

**Document Version:**

Publisher's PDF, also known as Version of Record (includes final page, issue and volume numbers)

**Please check the document version of this publication:**

- A submitted manuscript is the version of the article upon submission and before peer-review. There can be important differences between the submitted version and the official published version of record. People interested in the research are advised to contact the author for the final version of the publication, or visit the DOI to the publisher's website.
- The final author version and the galley proof are versions of the publication after peer review.
- The final published version features the final layout of the paper including the volume, issue and page numbers.

[Link to publication](#)

**General rights**

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal.

If the publication is distributed under the terms of Article 25fa of the Dutch Copyright Act, indicated by the "Taverne" license above, please follow below link for the End User Agreement:

[www.tue.nl/taverne](http://www.tue.nl/taverne)

**Take down policy**

If you believe that this document breaches copyright please contact us at:

[openaccess@tue.nl](mailto:openaccess@tue.nl)

providing details and we will investigate your claim.

# Rate-Equation Analysis for an Integrated Coupled-Cavity Laser with MMI Anti-Phase Coupler


Daan LENSTRA

Eindhoven University of Technology, P.O.Box 513, 5600MB, The Netherlands


\* d.lenstra@tue.nl

In this paper a dynamical theory is reported for the coupled-cavity laser (CCL) with a multi-mode interference (MMI) coupler, which provides an excellent description of the locking and other operational aspects of the laser realized by D'Agostino et al. in 2015 [1]. The revived interest in CCLs as widely tuneable lasers for sensing and other applications is due to the specially designed MMI anti-phase coupler as described in [1]. The theory explains if, why and how the two individual isolated constituent modes combine to one single “super mode”, a situation referred to as locked state. A comprehensive formulation of the model and derivation of the rate equations for the CCL with quantum-well active material can be found in [2].


We consider two Fabry-Pérot (FP) lasers that are very similar except they differ 5–10 % in length and couple by a reflective MMI coupler. The amplitudes indicated (Fig.1) are evaluated at the point where each laser touches the MMI-coupler. Note that the coupling parameters have been designed in such a way that  $C_{bar}$  and  $C_x$  are 180 degrees out of phase and the sum of their absolute values equals unity. This is a property of the 3x3 reflective coupler in which only the two outer ports are used [1,2]. The ideal theoretical values for the coupling coefficients are  $C_{bar}=0.79$  and  $C_x=-0.21$  [1,2]. This implies that if the amplitudes  $E_1$  and  $E_2$  are equal and opposite, the coupler behaves as a 100% reflector for both lasers. Due to small deviations from growth specifications the ideal values for the coupling coefficients can very well be somewhat different. In fact, we found that best agreement with experimental data was achieved by taking smaller values for  $C_{bar}$ , i.e. 0.75 instead of 0.79, and for  $|C_x|$ , i.e. 0.18 instead of 0.21.



**Fig. 37.** Sketch of two FP-lasers coupled by a reflective MMI coupler with designed coupling parameters  $C_{bar}$  and  $C_x$ . The slowly-varying amplitudes are relative to the exponential time factor as indicated, where  $\omega_0$  is the locked frequency.  $\omega_1$ ,  $\omega_2$  are the frequencies of the isolated lasers, i.e. when  $C_x=0$ .



**Fig. 2. Left: Intensity  $I_1$  versus  $p_1$ , at fixed  $p_2 = \{0.67, 1.22, 1.78, 2.33, 2.89, 3.44, 4., 4.65\}$ . Right: intensity  $I_1$  versus  $p_2$ , with fixed  $p_1 = \{\text{same values}\}$ ; optimized detuning assumed. The shapes of the curves hardly depend on the precise value of  $\alpha$ . The values for  $C_{\text{bar}}$  and  $C_x$  as in table 1 were taken so as to optimize the qualitative and quantitative proportionality agreement with the measured curves in [1].**



**Fig. 3. Intensity  $I_1 (\times 10^{-7})$  and operation frequency shift  $\omega_{10} (\times 10^{-10} \text{ s}^{-1})$  versus detuning  $\omega_{21} \equiv \omega_2 - \omega_1$  within the locking range. The pump strengths are  $p_1=4, p_2=2$ .**

Fig. 2 left shows the output-intensity curves of laser 1 versus its pump strength for various values of the pump strength of laser 2; Fig. 2 right shows the output intensities versus the pump strength of laser 2 with the pump strength of laser 1 as parameter. Here we define for  $j=1,2$  the pump strengths as  $p_j \equiv \Delta J_j / J_{thr,j}$  where  $\Delta J_j$  is the injection current w.r.t. the threshold current  $J_{thr,j}$  (i.e. when each laser stands on its own, that is, without any coupling). The shapes of the curves agree well with the measured curves in [1]. Fig. 3 shows numerical results for the output intensity of laser 1 and the operation frequency within the locking range.

## References

- [1] D. D'Agostino,\* D. Lenstra, H. P. M. M. Ambrosius, and M. K. Smit, "Coupled cavity laser based on anti-resonant imaging via multimode interference", OPTICS LETTERS, vol. 40, pp. 653-656, February 2015.
- [2] D.Lenstra, "Rate-equation analysis for the coupled-cavity laser with MMI anti-phase coupler", DOI: 10.13140/RG.2.1.2747.6245, February 2016.