

Bibliografische gegevens: NL1011011 (C1) — 2000-07-14

Flooring plate for multistory building has sandwich construction with layers of different materials

Uitvinder(s): PRONK ARIE DIRK CORNELIS [NL]; LICHTENBERG JOSEPHUS JOANNES N [NL] ± (ARIE DIRK CORNELIS PRONK, ; JOSEPHUS JOANNES NORBERTUS LICHTENBERG)

Aanvrager(s): ARIE DIRK CORNELIS PRONK [NL] ± (A+, BUREAU VOOR BOUWPRODUKTONTWIKKELING B.V, ; ARIE DIRK CORNELIS PRONK)

Classificatie:

- internationaal: ***B32B13/04; B32B7/02; E04B5/19;*** (IPC1-7): B32B13/00; B32B3/22; E04B5/08; E04B5/17; E04C2/34
- cooperative: **B32B13/04 (EP, US); B32B7/02 (EP, US); E04B5/19 (EP); B32B2250/40 (US); B32B2315/06 (US); B32B2419/04 (US)**

Aanvraagnummer: NL19991011011 19990113

Prioriteitsnummer(s): NL19991011011 19990113

Samenvatting van NL1011011 (C1)

The floor has upper (4) and lower (1) layers, with various components sandwiched between them. Much of the space between the upper and lower layers is filled with light concrete (7). Intermediate blocks of heavier concrete (2) provide additional strength. Conduit tubes and pipes (9) pass through the light concrete. Support columns (8) are fixed at right angles to the floor.