

Low Temperature Combustion Concepts: Full Metal and Optical Engine Experiments Compared

Citation for published version (APA):

Leermakers, C. A. J., Zegers, R. P. C., Somers, L. M. T., Dam, N. J., Johansson, B. H., & Goey, de, L. P. H. (2012). *Low Temperature Combustion Concepts: Full Metal and Optical Engine Experiments Compared*. W2P003-. Poster session presented at conference; 34th International Symposium on Combustion; 2012-07-29; 2012-08-03, .

Document status and date:

Published: 01/01/2012

Document Version:

Publisher's PDF, also known as Version of Record (includes final page, issue and volume numbers)

Please check the document version of this publication:

- A submitted manuscript is the version of the article upon submission and before peer-review. There can be important differences between the submitted version and the official published version of record. People interested in the research are advised to contact the author for the final version of the publication, or visit the DOI to the publisher's website.
- The final author version and the galley proof are versions of the publication after peer review.
- The final published version features the final layout of the paper including the volume, issue and page numbers.

[Link to publication](#)

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal.

If the publication is distributed under the terms of Article 25fa of the Dutch Copyright Act, indicated by the "Taverne" license above, please follow below link for the End User Agreement:

www.tue.nl/taverne

Take down policy

If you believe that this document breaches copyright please contact us at:

openaccess@tue.nl

providing details and we will investigate your claim.

W2P003: LOW TEMPERATURE COMBUSTION CONCEPTS: FULL METAL AND OPTICAL ENGINE EXPERIMENTS COMPARED

*Cornelis Leermakers, R.P.C. Zegers, L.M.T. Somers, N.J. Dam, B.H. Johansson, L.P.H. de Goey
Eindhoven University of Technology, The Netherlands*

In current diesel combustion engines, legislated emission levels are generally met through aftertreatment. The development of combustion technologies with lower smoke and NO_x emissions can minimize the aftertreatment system required, and thus reduce the related costs. Combustion concepts aiming to do this mostly rely on enhanced mixing and reduced (local) temperatures and can therefore be classified as Low Temperature Combustion (LTC) concepts. Partially Premixed Combustion (PPC) and Reactivity Controlled Compression Ignition (RCCI) are the most well-known applications of this concept, developed at Lund University and the University of Wisconsin-Madison, respectively. Besides their lower smoke and NO_x emissions, these applications have shown a simultaneous efficiency improvement, and as such a CO₂ emission reduction.

Up till now, both applications have almost exclusively been demonstrated in the two university's labs. Secondly, a back-to-back comparison has yet to be performed. In the Eindhoven Engines labs, both concepts are extensively tested on a metal single cylinder engine, and extended to second-generation biofuels. These often have a lower sooting tendency, but more importantly they also offer the possibility to reduce well-to-wheel CO₂ emissions even further.

Further improvements of these LTC concepts are sustained by a detailed understanding of underlying physical and chemical processes. Laser-based diagnostics may contribute significantly to this understanding. However, turbulent combustion exhibits transient phenomena, such as extinction or ignition, which cannot be viewed as statistically stationary. For a better understanding of these phenomena and the effects of the stratification level (i.e. gradients of temperature and mixture strength) present in LTC, laser-based diagnostics of two-dimensional flow and scalar fields at rates much faster (≥ 1 kHz) than typical time-scales of turbulent flames is necessary.

To access combustion dynamics at these short time-scales, spatial distributions of diatomic molecules like OH and CH can be monitored in Eindhoven's optically accessible engine. For their excitation, a Sirah Credo HS dye laser is used, which is pumped by a high-speed EdgeWave IS8II-DE double-cavity Nd:YAG laser with a repetition rate up to 10 kHz and a pulse energy of 7 mJ at 3 kHz repetition rate (per cavity, so 6 kHz net). A 6 kHz repetition rate enables a 1.2°CA resolution at an engine speed of 1200 rpm. R6G and Styryl 8 dyes are used for excitation of OH and CH, respectively. Even when using an intensified camera system, the rather low pulse energies at high repetition rates make imaging of these molecules a challenge.

Cornelis Leermakers: c.a.j.leermakers@tue.nl