

Dutch Robotics 2011 adult-size team description

Citation for published version (APA):

Zutven, van, P. W. M., Mironchyk, P., Çilli, C., Steur, E., Ilhan, E., Caarls, J., Pieters, R. S., Filiz, A., Heijkoop, P., de Boer, T., Smorenberg, A., Breda, van, E., Liqui Lung, G., Wilbers, F., Plooi, C., Hoorn, van der, G., Kiemel, S., Reinink, R., Dertien, E., ... Warmerdam, T. P. H. (2011). Dutch Robotics 2011 adult-size team description. In *Proceedings of the 15th Annual RoboCup International Symposium 2011, 5-11 July 2011, Istanbul, Turkey* (pp. 1-7). RoboCup.

Document status and date:

Published: 01/01/2011

Document Version:

Publisher's PDF, also known as Version of Record (includes final page, issue and volume numbers)

Please check the document version of this publication:

- A submitted manuscript is the version of the article upon submission and before peer-review. There can be important differences between the submitted version and the official published version of record. People interested in the research are advised to contact the author for the final version of the publication, or visit the DOI to the publisher's website.
- The final author version and the galley proof are versions of the publication after peer review.
- The final published version features the final layout of the paper including the volume, issue and page numbers.

[Link to publication](#)

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal.

If the publication is distributed under the terms of Article 25fa of the Dutch Copyright Act, indicated by the "Taverne" license above, please follow below link for the End User Agreement:

www.tue.nl/taverne

Take down policy

If you believe that this document breaches copyright please contact us at:

openaccess@tue.nl

providing details and we will investigate your claim.

Dutch Robotics 2011 Adult-Size Team Description

Pieter van Zutven¹, Pavel Mironchik¹, Can Cilli¹, Erik Steur¹, Esin Ilhan¹,
Jurjen Caarls¹, Roel Pieters¹, Atilla Filiz¹, Philip Heijkoop², Tomas de Boer²,
Arjan Smorenberg², Eelko van Breda², Guus Liqui Lung², Freerk Wilbers²,
Corné Plooijs², Gijs van der Hoorn², Sebastiaan Kiemel², Roelof Reinink³,
Edwin Dertien³, Gijs van Oort³, Dragan Kostić⁴, Henk Nijmeijer¹, Martijn Wisse²,
Pieter Jonker², Raffaella Carloni³, Stefano Stramigioli³, Thom Warmerdam⁴

www.dutchrobotics.net

¹ Section Dynamics and Control, Department of Mechanical Engineering,
Eindhoven University of Technology, Den Dolech 2 5600 MB Eindhoven, The Netherlands

² Delft Biorobotics Laboratory, 3ME faculty, Delft University of Technology,
Mekelweg 2 2628 CD Delft, The Netherlands.

³ Control Laboratory, Department of Electrical Engineering, Twente University,
De Veldmaat 10 7522 NM Twente, The Netherlands

⁴ Philips Applied Technologies
High Tech Campus 5 5656 AE Eindhoven, The Netherlands

Abstract. This document presents the 2011 edition of the team Dutch Robotics from The Netherlands. Our team gathers three Dutch technical universities, namely Delft University of Technology, Eindhoven University of Technology and University of Twente, and the commercial company Philips. We contribute an adult-size humanoid robot TULip, which is designed based on theory of the limit cycle walking developed in our earlier research. The key of our theory is that stable periodic walking gaits can be achieved even without high-bandwidth robot position control. Our control approach is based on simultaneous position and force control. For accurate force control, we make use of the Series Elastic Actuation. The control software of TULip is based on the Darmstadt's RoboFrame, and it runs on a PC104 computer with Linux Xenomai. The vision system consists of two wide-angle cameras, each interfaced with a dedicated Blackfin processor running vision algorithms, and a wireless networking interface.

1 Introduction

It is well-recognized that the annual RoboCup events promote the implementation of biomechanical analogies in robotics. One should in particular acknowledge importance of these events for development of humanoid robots that, year after year, feature more and more human-like capabilities. Besides human-like appearance and

kinematics, which are the most obvious links between humans and humanoids, these robots progressively acquire capabilities of humans that belong to the domains of cognition, motion control and execution. Especially appealing for implementation in robots is the locomotion ability of humans, having in mind its advantages in terms of versatility and energy-efficiency. Recently, we have demonstrated human-like efficiency in robot walking [1-6], thanks to the development of the theory of “Limit Cycle Walking” [7]. It is our ambition to demonstrate merits of this theory on our humanoid robot TULip at the RoboCup 2011. Besides research on bipedal walking, our RoboCup robot will demonstrate our latest human-like vision technology.

The purpose of this document is to introduce our humanoid robot TULip, which is intended for competitions in the Adult-size Humanoid League in Istanbul, 2011.

2 Mechanical Design

TULip is an adult sized (1.30 m, 19kg) 17 degrees of freedom (DOF) autonomous humanoid robot, see Fig. 1. All DOF's are electrically actuated. It is designed to feature a wide range of motions in the lower body joints. The hips each have 3 degrees of freedom which allow for 90° about their x and z axis, and more than 180° around their y axis¹.




Fig. 1. Adult-size humanoid robot TULip: photo, CAD drawing and kinematic configuration in the lower body.

¹ N.B. We adopt X-Y-Z coordinates that correspond to depth, width and height of the robot, respectively: X is from back to front, Y is from right to left feet, and Z is from toe to head.

3 Walking

3.1 Limit Cycle Walking

Our research on bipedal locomotion focuses on design and experimental demonstrations of energy-efficient and human-like walking gaits. This research is founded upon the theory of Passive Dynamic Walking [8], which considers passive legged mechanisms capable of walking down a shallow slope without application of actuators or control. Since motions of such mechanisms are naturally stable, no active control is needed. Their energetic cost during walking is less than 0.1 Joules per unit of weight per meter traveled. Passive dynamic walkers are later on enhanced by weak actuators [1,6], leading to prototypes that can walk on level ground with energy consumption of the same range as human walking but ten times more efficient [1] than the Honda Asimo [9]. Asimo and the majority of the actual bipedal robots make use of high-bandwidth position control in all their joints for accurate tracking of the pre-defined trajectories. Position control, however, does not fit well with the purpose of walking. It does not matter much what the exact knee angle is, for example, as long as it bends sufficiently during the swing phase. We promote idea of trading the position accuracy for power efficiency, by means of force control. To realize such an idea in practice, we do not actuate our robot with standard servo motors, but we design our own actuation system.

3.2 Joint Actuation

TULip uses Series Elastic Actuation [10]; a spring is placed between the load and the motor (i.e., in the steel cable connecting the motor with the joint). The rotational difference between the motor and the joint (measured with two encoders) determines the spring expansion and thus the actuation torque.

The joints actuated through series elastic actuation are the R_y (pitch rotation) of the knee, ankle and hip as well as the R_x of the ankle. In addition to allowing accurate force control, the series elastic actuation also increases shock tolerance for the motor gearbox.

Our robot TULip is actuated with Maxon DC motors, three of which are located in each hip (R_x , R_y , R_z), two in each ankle, one in each knee, and one in each shoulder. All the motors have optical encoders. Transfer of torque in the drive trains is done via planetary gearboxes.

4 Electronics

4.1 Amplifiers and sensors

The MAXON motors are powered by ELMO WHISTLE 5/60 and 20/100 digital servo amplifiers that are PWM controlled by a PC104 stack. In addition, there is a Mesa 4I65 Anything-I/O PCB running the Mesa Hostmot12 software on its onboard Xilinx Spartan-II 200k gate FPGA.

The hip, knee and ankle of both legs have eight additional SCANCON encoders that are connected to a second 4I65 PCB running a modified version of the Hostmot12 software on its FPGA. Each foot has four Tekscan Flexiforce pressure sensors to determine position of the center of pressure. The force sensors are interfaced using a custom-designed ARM7 board, which linearizes the sensor signals and gives the pressure values to the central controller. Furthermore, the ARM7 board is equipped with a STMicroelectronics 3D accelerometer, which is used to precisely detect moments of impacts of the foot with the floor or with the ball. The feet electronics are interfaced to the main control system using a standard USB interface. Their signals are used as feedback information for walking stability control, together with readings from an Xsens Mti sensor in the upper body.

4.2 Control System

Both Mesa 4I65 PCB's and a 5VDC power supply are mounted on a PC104-Plus stack of an EPIC format sized Diamond Poseidon single board computer with a 1GHz Via Eden CPU. The Poseidon PCB contains 512MB SDRAM, a 4GB Flashdisk, digital and analog I/O's. All encoders are connected to a custom designed connection PCB, while 12 Whistle servo amps are mounted on 2 custom designed PCB's.

The computer is powered by a Kokam 3-cell 6 Ah LiPo battery, the motors by a separate 8 cell 3.3V Ah LiPo battery. Uptime with this setup is about 30 minutes. A PCB with battery monitor IC's automatically switches off the power to prevent excessive discharge of the batteries.

On the Poseidon we run an Xenomai Linux build on Debian as RTOS platform. Linux drivers for the Mesa4I65 Anything-IO boards have been developed by the Embedded Systems group of the University of Twente.

5 Software

5.1 Overview

The software control system of TULip is based on the concept of independent modules, each performing a specific own task. The corresponding software architecture is based upon the RoboFrame framework developed by the German RoboCup team of Darmstadt Technical University [11]. This C++ based framework provides a number of services to robot control applications, such as module management, timers, intra and inter-process communication, a GUI template, and wireless UDP communication using 802.11g hardware.

As the TULip robot is partly developed based on principles of the biped Flame, designed at the University of Delft, their software designs are similar. Flame uses a motion control based on hierarchical state machines. The state machines aid efficient concurrent design and implementation of the various behaviors for robot control.

To offer a particular service to the rest of the application, a module needs to publish a well-defined interface consisting of messages that can be transmitted using the communication facilities supplied by the RoboFrame. An example of the interface is the set of commands the motion module accepts from the rest of the system; each message indicates a particular type of motion and, optionally, a list of parameters.

The main modules are Motion, Vision, Communications, World Model and Strategy. All these modules run on the Poseidon SBC.

5.2 Motion

The RoboFrame has no native software support for real-time platforms required for motion control. Therefore, this part of the system is implemented outside of the RoboFrame application, but still on the Poseidon SBC. There are no dedicated hardware control systems. For operational reliability, the motion control is implemented as a separate real-time process interfacing with an adapter module which runs inside the RoboFrame application. This RoboFrame module accepts commands from other modules (strategy) and relays these to the real-time process running the actual motion control. Sensor data from the motion controller is sent back through the adapter for use by the rest of the modules. This prevents disastrous motor behavior when a non real-time application (vision and behavior modules) crashes.

5.3 World Model

The world model is responsible for maintaining information about the state of the external world. It receives sensor data from both the motion and vision modules, as

well as information through the communications module. All other modules that need information on the robot state (attitude, position, viewing direction) depend on the world model. Strategy relies on the world model for performing autonomous control of the robots actions in the soccer field.

6 Vision

6.1 Head

The stereo vision system on the head is the Surveyor SVS, and it consists of two wide-angle camera modules, each equipped with a dedicated on-board Blackfin processor. LAN communication connects both cameras to the Poseidon computer. The processors run a firmware for detection of objects by color and extraction of 3D coordinates of these objects.

The head is connected to the body by three Dynamixel RX-28 motors giving three DOF's in the neck. The head-neck combination is about 15cm of height. Ranges of motion are 180° for panning, 100° for tilting and a forward-backward stroke of about 4cm.

6.2 Control

The stabilization algorithm uses orientation and acceleration data from the Xsens to counteract head rotations and displacements. The saccade algorithm points the camera at salient features in the environment. The most challenging part here is the detection, selection and tracking in time of these features. The pursuit algorithm, finally, smoothly tracks a selected salient feature if it is moving.

6.3 Image Processing

The task of image processing is to determine the location of features in the world from the images produced by the cameras. Interesting features in a RoboCup game are ball, goal, opponents, field markers and such. The vision software proceeds as follows:

- apply lens distortion correction and epipolar alignment to the images,
- segment by color,
- detect features in segmented image,
- perform sparse stereo-vision on color-segmented features,
- combine many different hints gathered from the images to determine position in the world.

In addition, there is a possibility of dense stereo-vision. This allows, for instance, detection of the ground plane. This ground plan can be used to provide on-line color calibration information for adaptation to varying light conditions.

References

- [1] S. H Collins, A. Ruina, R. L. Tedrake, M. Wisse, "Efficient bipedal robots based on passive-dynamic walkers", *Science* (18 February 2005), V307, p.p.: 1082-1085.
- [2] M. Wisse, G. Feliksdal, J. van Frankenhuyzen, B. Moyer, "Passive-based Walking Robot", *IEEE Robotics & Automation Magazine* (2007), V14(2), p.p.: 52-62
- [3] G. van Oort and S. Stramigioli, "Using time-reversal symmetry for stabilizing a simple 3D walker model" in: *Robotics and Automation, 2007 IEEE International Conference on, IEEE RAS, Rome, pages 4673-4678, 2007*
- [4] E.C. Dertien G. van Oort and S. Stramigioli, "Realisation of an Energy Efficient Walking Robot" in: *Proceedings of the 2006 IEEE International Conference on Robotics and Automation, 2006*
- [5] P.H.M. Daemen, "ZMP based control in 3D passive dynamic walking", MSc. report, UTwente, January 2007.
- [6] E.C. Dertien "Dynamic walking with Dribbel", *IEEE robotics and automation magazine*, 13 (3). pp. 118-121. ISSN 1070-9932 (2006)
- [7] D. G. E. Hobbelen, M. Wisse, "Limit Cycle Walking", in book "Humanoid Robots; human-like machines", edited by M. Hackel, 2007, published by Advanced Robotic Systems International, Vienna. Ch.14, p.p.: 277-294, ISBN: 978-3-902613-07-3.
- [8] T. McGeer. Passive dynamic walking. *Intern. J. Robot. Res.*, 9(2):62-82, April 1990.
- [9] Y. Sakagami, R. Watanabe, C. Aoyama, S. Matsunaga, N. Higaki, and M. Fujita. The intelligent asimo: System overview and integration. In *Proc., Int. Conf. on Intelligent Robots and Systems*, pages 2478-2483, 2002.
- [10] G. Pratt and M. Williamson. Series elastic actuators. In *Proc., Int. Conf. on Intelligent Robots and Systems*, Pittsburgh, PA, 1995.
- [11] M. Friedmann, J. Kiener, S. Petters, D. Thomas, and O. von Stryk, "Modular software architecture for teams of cooperating, heterogeneous robots," in *Robotics and Biomimetics, 2006. ROBIO '06. IEEE International Conference on, 2006*, pp. 613-618.